

APC Back-UPS Pro Gaming

Technical Specifications Sheet



Life Is On

APC[®]
by Schneider Electric

Back-UPS Pro Gaming

Technical Specifications for BGM2200 & BGM2200B



Output

Power Capacity	1320W / 2200VA
Nominal Output Voltage	230+/-10%
Output Voltage Frequency (Hz)	50Hz/60Hz ± 1Hz
Output Connections	GR: 6; MSX: 6; UK: 4; AZ: 6
Waveform Type	Sine Wave
Power Factor	0.6

Input

Nominal Input Voltage	230VAC
Input Connection	GR: Schuko+C19; MSX: Schuko+C19; UK: UK+SR; AZ: Australia+C19

Protection

Surge Energy Rating	1080 joules
Coax protection	No
Dataline Surge Protection (Gigabit)	Yes
Input Over Current Protection	GR/MSX/AZ(Circuit breaker 15A); UK(Fuse 13A)

Physical

Unit Dimensions	H:11.5in * W:4.1in * D:16.1in
Unit Weight	GR: 27.21lbs; MSX: 26.98lbs; UK: 27.16lbs; AZ: 27.69lbs
Shipping Dimensions	H:6.1in * W:14.0in * D:18.9in
Shipping Weight	GR: 32.01lbs; MSX: 32.67lbs; UK: 31.88lbs; AZ: 31.70lbs
Runtime (half load)	4min15s
Runtime (full load)	50 sec
Colors	Midnight (BGM2200B) & Arctic (BGM2200)

USB Outlet

USB Voltage Range	4.75V-5.25V; Load=3A
USB Outlets	Type A= 2 Type C= 1
USB Charger	5V/3A total

Battery Information

Battery Type	Lead-acid
Replacement Battery	APCRCBC216

Management

Alarms	On-battery, low battery warning, low battery shutdown, replace battery detected
Shutdown Software	PCSS Software

Conformance

Certification and Approvals	IEC 62040-1:2017+A1:2021, IEC 62040-2 C1
Warranty and Equipment Protection	3 years

apc.com/gaming