

### Overview

#### HP EliteBook 645 14 inch G9 Notebook PC



#### Left

- |  |  |
|--|--|
| 1. Internal Microphones (2)                    | 6. Clickpad  |
| 2. Webcam LED (Optional)                       | 7. Smartcard Reader (Optional)                     |
| 3. Camera Shutter (Only available with webcam) | 8. SuperSpeed USB Type-A 5Gbps signaling rate port |
| 4. HD TNR and IR Camera (Optional)             | 9. Ethernet Port (RJ-45)                           |
| 5. IR Camera LED (Optional)                    | 10. Nano Security Lock Slot (Lock sold separately) |

### Overview



#### Right

- |  |   |
|--|---|
| 1. Power Button Key  | 6. HDMI 2.0b Port (Cable not included)      |
| 2. Power Connector   | 7. Audio Combo Jack                         |
| 3. SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) | 8. External SIM Card Slot (Optional)        |
| 4. SuperSpeed USB Type-A 5Gbps signaling rate port                                     | 9. Touch Fingerprint Sensor (Select Models) |
| 5. SuperSpeed USB Type-A 5Gbps signaling rate port                                     |   |

### Overview

#### AT A GLANCE

- Preinstalled with Windows 11 Pro, other Windows OS or FreeDOS
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 64 GB
- Choice of AMD Barcelo™ 5000 series mobile processors, R7, R5 and R3
- Choice of 35.56 cm (14") diagonal HD, Ultra-Wide Viewing Angle FHD, Touch or Non-Touch screen, and Privacy Panel option.
- Features redesigned quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Choice of solid state drives up to 1 TB
- Multi-layered security with HP SureStart Gen7, HP Privacy Camera, HP Sure View Gen4, HP Wolf Security (Includes HP Sure Sense and HP Sure Click), HP Secure Erase, HP Client Security Manager Gen7 (Includes Sure Run Gen5, Sure Recover Gen5), Touch Fingerprint reader, and Tamper Lock.
- Supports wireless options for connectivity on the go including gigabit-speed Wi-Fi® 6e and CAT9 4G/LTE WWAN
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support HP docking options
- Passed MIL-STD 810H tests
- Battery life up to 20 hours and 30 minutes with the optional 51.3Whr battery
- Optimize your video calls with an HD camera and temporal noise reduction that adjusts to the lighting in your environment.
- 180° synchronized hinge allows the EliteBook to lay completely flat, without lifting the keyboard, and includes everyone with visibility from multiple angles.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

---

### Technical Specifications

#### PRODUCT NAME

HP EliteBook 645 14 inch G9 Notebook PC

#### OPERATING SYSTEM

**Preinstalled** Windows 11 Pro <sup>1</sup>  
Windows 11 Pro Education <sup>1</sup>  
Windows 11 Home - HP recommends Windows 11 Pro for business <sup>1</sup>  
Windows 11 Home Single Language - HP recommends Windows 11 Pro for business <sup>1</sup>  
Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>  
Windows 10 Pro (available through downgrade rights from Windows 11 Pro) <sup>1,2</sup>  
FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply, and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

#### PROCESSORS

AMD Ryzen™ 7 PRO 5875U with AMD Radeon™ Graphics (2.00 GHz base clock, up to 4.50 GHz max boost clock, 16 MB L3 cache, 8 cores, 16 threads) <sup>3,4,5,6</sup>  
AMD Ryzen™ 7 5825U with AMD Radeon™ Graphics (2.00 GHz base clock, 16 MB L3 cache, 8 cores, 16 threads) <sup>3,4,5,6</sup>  
AMD Ryzen™ 5 PRO 5675U with AMD Radeon™ Graphics (2.30 GHz base clock, up to 4.30 GHz max boost clock, 16 MB L3 cache, 6 cores, 12 threads) <sup>3,4,5,6</sup>  
AMD Ryzen™ 5 5625U with AMD Radeon™ Graphics (2.30 GHz base clock, 16 MB L3 cache, 6 cores, 12 threads) <sup>3,4,5,6</sup>  
AMD Ryzen™ 3 5425U with AMD Radeon™ Graphics (2.70 GHz base clock, 8 MB L3 cache, 4 cores, 8 threads) <sup>3,4,5,6</sup>

##### Processor Family

AMD Ryzen™ processor <sup>6</sup>

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. AMD Max Boost frequency performance varies depending on hardware, software and overall system configuration.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

### Technical Specifications

#### CHIPSET

Chipset is integrated with processor.

---

#### GRAPHICS

##### Integrated

AMD Radeon Graphics

##### Supports

Support HD decode, DX12, HDMI 2.1b <sup>7</sup>

[7. HD content required to view HD images.](#)

---

#### DISPLAY

##### Non-Touch

35.56 cm (14") diagonal FHD UWVA eDP anti-glare Low Blue Light narrow bezel bent, 1000 nits, 100% sRGB for HD + IR camera and WWAN HP Sure View Gen4 integrated privacy screen (1920 x 1080) with HP Eye Ease <sup>8,9,10,11,12</sup>

35.56 cm (14") diagonal FHD UWVA eDP anti-glare, low power, bent, 400 nits, 72% NTSC for HD + IR camera and WWAN (1920 x 1080) <sup>8,9,10</sup>

35.6 cm (14") diagonal, FHD UWVA eDP anti-glare narrow bezel bent, 400 nits, 100% sRGB for HD Webcam (1920 x 1080) <sup>8,9,10</sup>

35.56 cm (14") diagonal FHD UWVA eDP anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD + IR camera and WWAN (1920 x 1080) <sup>8,9,10</sup>

35.56 cm (14") diagonal FHD UWVA eDP + W/O PSR anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD + IR camera (1920 x 1080) <sup>8,9,10</sup>

35.56 cm (14") diagonal FHD UWVA eDP anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD camera and WWAN (1920 x 1080) <sup>8,9,10</sup>

35.56 cm (14") diagonal FHD UWVA eDP anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD camera (1920 x 1080) <sup>8,9,10</sup>

35.6 cm (14") diagonal, FHD UWVA eDP1.4 w/o PSR, anti-glare, 250 nits, 45%, no mic (1920 x 1080) <sup>8,9,10</sup>

35.6 cm (14") diagonal, FHD UWVA eDP 1.2 w/o PSR, Anti-Glare, 250 nits, 45% NTSC Narrow Bezel bent (1920 x 1080) <sup>8,9,10</sup>

35.56 cm (14") diagonal HD SVA eDP anti-glare narrow bezel bent, 250 nits, 45% NTSC for HD Camera (1366 x 768) <sup>8,9,10</sup>

35.6 cm (14") diagonal, HD SVA eDP 1.2 w/o PSR, Anti-Glare, 250 nits, 45% NTSC Narrow Bezel bent (1366 x 768) <sup>8,10,12</sup>

##### Touch

35.56 cm (14") diagonal FHD Anti-Glare UWVA eDP narrow bezel bent touch-on-panel screen, 250 nits, 45% NTSC for HD + IR camera and WWAN (1920 x 1080) <sup>8,9,10,12</sup>

35.56 cm (14") diagonal FHD Anti-Glare UWVA eDP narrow bezel bent touch-on-panel screen, 250 nits, 45% NTSC for HD camera (1920 x 1080) <sup>8,9,10,12</sup>

##### Display Size

14" diagonal

35.6 cm (14") diagonal

[8. HD content required to view HD images.](#)

[9. Sold separately or as an optional feature.](#)

[10. Resolutions are dependent upon monitor capability, and resolution and color depth settings.](#)

[11. HP Sure View Reflect integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.](#)

### Technical Specifications

12. Actual brightness will be lower with touchscreen or HP Sure View.

#### DOCKING (Sold Separately)

<b>Docking station model #1</b>	HP Thunderbolt Dock G2
<b>Docking station model #2</b>	HP USB-C Dock G5
<b>Docking station model #3</b>	HP USB-C/A Universal Dock G2

For additional aftermarket options and docking specs please see page 41.

#### STORAGE AND DRIVES

##### Primary M.2 Storage

- 128 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13</sup>
- 256 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13</sup>
- 256 GB PCIe® Gen4x4 NVMe™ M.2 TLC Self Encrypted OPAL2 Solid State Drive <sup>13,14</sup>
- 256 GB PCIe® Gen4x4 NVMe™ M.2 TLC single-sided Solid State Drive <sup>13,14</sup>
- 256 GB PCIe® NVMe™ M.2 SSD <sup>13</sup>
- 512 GB PCIe® Gen4x4 NVMe™ M.2 TLC Self Encrypted OPAL2 Solid State Drive <sup>13,14</sup>
- 512 GB PCIe® Gen4x4 NVMe™ M.2 TLC Solid State Drive <sup>13,14</sup>
- 512 GB PCIe® NVMe™ M.2 SSD <sup>13</sup>
- 1 TB PCIe® Gen4x4 NVMe™ M.2 TLC Solid State Drive <sup>13,14</sup>

##### Secondary M.2 Storage (Optional)

- 128 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13,15</sup>
- 256 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13,15</sup>

13. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

14. Only functions at the Gen3x4 capacity with AMD Ryzen Barcelo processor.

15. Second storage is only available with non-WWAN base Unit AND Primary M.2 storage.

#### MEMORY

##### Maximum Memory

- 64 GB DDR4-3200 SDRAM <sup>16</sup>

##### Memory

- 64 GB DDR4-3200 SDRAM (2 x 32 GB) <sup>16</sup>
- 32 GB DDR4-3200 SDRAM (1 x 32 GB) <sup>16</sup>
- 32 GB DDR4-3200 SDRAM (2 x 16 GB) <sup>16</sup>
- 16 GB DDR4-3200 SDRAM (1 x 16 GB) <sup>16</sup>
- 16 GB DDR4-3200 SDRAM (2 x 8 GB) <sup>16</sup>
- 8 GB DDR4-3200 SDRAM (1 x 8 GB) <sup>16</sup>
- 8 GB DDR4-3200 SDRAM (2 x 4 GB) <sup>16</sup>

### Technical Specifications

#### Memory Slots

2 SODIMM

Both slots are customer accessible / upgradeable

DDR4 PC4 SODIMMS (Barcelo runs at 3200)

Supports Dual Channel Memory

16. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

---

### NETWORKING/COMMUNICATIONS

#### WLAN

Realtek RTL8852BE 802.11ax 2x2 Wi-Fi® + BT5.2 <sup>17</sup>

Qualcomm® Fast Connect 6900 Wi-Fi 6E + BT5.2 (802.11ax 2x2) <sup>18</sup>

#### WWAN

Intel® XMM™ 7560 R+ LTE-Advanced Pro Cat 16 <sup>19</sup>

#### NFC

NXP NPC300 Near Field Communication Module (NFC Mirage WNC XRAV-1)

#### Ethernet

Realtek RTL8111HSH 10/100/1000 Integrated NIC <sup>20</sup>

Realtek RTL8111FPH 10/100/1000 Integrated NIC <sup>20</sup>

17. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs.

18. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

19. WWAN module is an optional feature, requires factory configuration and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

20. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

### Technical Specifications

#### AUDIO/MULTIMEDIA

**Audio**

2 Integrated stereo speakers  
Integrated microphone (Dual Array)

**Speaker Power**

2W/4ohm Per speaker

**Camera**

720p HD camera with Temporal Noise Reduction <sup>8,9</sup>  
720p HD camera+IR Camera with Temporal Noise Reduction <sup>8,9</sup>

[8. HD content required to view HD images.](#)

[9. Sold separately or as an optional feature.](#)

---

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

**Keyboard**

HP Premium Keyboard, spill resistant with optional backlit function <sup>21</sup>

**Pointing Device**

Clickpad with multi-touch gesture support

**Function Keys**

F1 - Display Switching  
F2 - Blank or SureView On/Off  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - Insert  
F11 - Wireless  
F12 - Programmable key

**Hidden Function Keys**

Fn+R - Break  
Fn+S - Sys Rq  
Fn+C - Scroll Lock

[21. Backlit keyboard is an optional feature.](#)

---



### Technical Specifications

#### SOFTWARE AND SECURITY

##### Software

HP Quick Touch  
HP Quick Drop <sup>22</sup>  
HP PC Hardware Diagnostics Windows  
Touchpoint Customizer for Commercial  
myHP  
HP Smart Support <sup>23</sup>  
HP Connection Optimizer  
HP Hotkey Support  
HP Support Assistant <sup>24</sup>  
HP Notifications  
HP Privacy Settings  
Buy Microsoft Office (Sold separately)

##### Manageability Features

HP Connect for Microsoft Endpoint Manager<sup>25</sup>  
HP Image Assistant Gen5 (download)  
HP Manageability Integration Kit (download)<sup>26</sup>  
HP Client Management Script Library (download)  
HP Patch Assistant (download)<sup>27</sup>  
HP Driver Packs (download)  
HP Client Catalog (download)

##### Security Management

##### HP Wolf Security of Business<sup>28</sup> includes:

HP Sure Click <sup>29</sup>  
HP Sure Sense <sup>30</sup>  
HP Sure Run Gen5 <sup>31</sup>  
HP Sure Recover Gen5 <sup>32</sup>  
HP Sure Start Gen7 <sup>33</sup>  
HP Tamper Lock  
HP Sure Admin <sup>34</sup>  
HP Client Security Manager Gen7 <sup>35</sup>

##### BIOS

HP BIOSphere Gen6 <sup>36</sup>  
HP Secure Erase <sup>37</sup>  
Absolute Persistence Module <sup>38</sup>  
HP DriveLock & Automatic DriveLock  
BIOS Update via Network  
HP Wake on WLAN  
HP Fingerprint Sensor <sup>39</sup>  
Secured-Core PC Enable <sup>40</sup>  
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

##### Security

##### TPM

Model: Infineon SLB9672VU2.0  
Version:15.21

## Technical Specifications

Revision: TPM 2.0  
FIPS 140-2 Compliant: Yes

### Smartcard Reader

Model number: Alcor AU9560  
FIPS 201 Compliant: Yes

### IPv6 Compliance

Yes

### FirstNet Certified

No

### Is the BIOS on this notebook ISO/IEC 19678:2015 (formerly NIST 800-147) compliant?: Yes

UEFI version: 2.7  
Class: Class 3

22. HP Quick Drop requires Internet access and Windows 10 PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.
23. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or it can be downloaded. For more information about how to enable HP Smart Support or for download, please visit <http://www.hp.com/smart-support>.
24. HP Support Assistant requires Windows and Internet Access
25. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.
26. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.
27. HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.
28. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement.
29. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.
30. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.
31. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.
32. HP Sure Recover Gen5 is available on select HP PCs and requires Windows 10 and higher and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module.
33. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher
34. HP Sure Admin requires Windows 10 and higher, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.
35. HP Client Security Manager Gen7 requires Windows and is available on the select HP Elite and Pro PCs.
36. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
37. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

### Technical Specifications

38. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit:

<https://www.absolute.com/about/legal/agreements/absolute/>.

39. Fingerprint Reader is an optional feature that must be configured at purchase.

40. Requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.

---

### Technical Specifications

#### POWER

##### Power Supply

- AC Adapter 45 Watt nPFC Standard USB type C Straight 1.8m <sup>41</sup>
- AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>41</sup>
- AC Adapter 45 Watt Smart nPFC Standard C8 for 2 prong Barrel 4.5mm Right Angle <sup>41</sup>
- AC Adapter 65 Watt nPFC Slim USB type C Straight 1.8m <sup>41</sup>
- AC Adapter 65 Watt nPFC Standard USB type C Straight 1.8m <sup>41</sup>
- AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm <sup>41</sup>
- AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>41</sup>

##### Battery

- HP Long Life 3-cell, 42.75 Wh Polymer <sup>42,43</sup>
- HP Long Life 3-cell, 51.3 Wh Polymer <sup>42,43</sup>

##### Power Cord

- 3-wire plug - 1m
- 2-wire plug - 1m

##### Battery Life

- Up to 20 hours and 30 minutes <sup>44</sup>

##### Battery Weight

- HP Long Life 3-cell - 42.75 Wh Polymer - .40 lb
- HP Long Life 3-cell - 51.3 Wh Polymer - .45 lb
- HP Long Life 3-cell - 42.75 Wh Polymer - 181.83 g
- HP Long Life 3-cell - 51.3 Wh Polymer - 203.56 g

41. Availability may vary by country.

42. Battery is internal and not replaceable by customer. Serviceable by warranty.

43. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

44. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

---

#### WEIGHTS & DIMENSIONS

##### Product Weight

- Starting at 3.03 lb <sup>45</sup>
- Starting at 1.37 kg <sup>45</sup>

##### Product Dimensions (W x D x H)

- 12.67 x 8.42 x 0.78 in
- 32.19 x 21.39 x 1.99 cm

45. Weight will vary by configuration. Does not include power adapter.

### Technical Specifications

#### PORTS/SLOTS

##### Ports

- 1 USB4™ Type-C® 40 Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 2 SuperSpeed USB Type-A 5Gbps signaling rate Port (1 Powered port)
- 1 SuperSpeed USB Type-A 5Gbps signaling rate Port (Power delivery)
- 1 AC power
- 1 HDMI 2.1b <sup>46</sup>
- 1 Headphone/microphone combo jack
- 1 Nano SIM slot for WWAN (optional)
- 1 RJ-45

##### Expansion Slots

- Smart Card Reader (optional)

[46. HDMI cable sold separately.](#)

---

### Technical Specifications

#### SERVICE AND SUPPORT

1-year and 3-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>47</sup>

47. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---

#### CERTIFICATION AND COMPLIANCE

Energy Efficiency Compliance: ENERGY STAR® certified

Energy Efficiency Compliance: EPEAT® 2019 Gold<sup>48</sup>

Environmental Specifications: Low halogen<sup>49</sup>

Environmental Specifications: TCO 9.0 Certification

48. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information

49. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

### Technical Specifications

#### SYSTEM UNIT

<b>Nominal Operating Voltage</b>	19V
Average Operating Power	7.52W (Idle)
Integrated graphics	Yes (AMD Radeon™ Graphics)
Discrete Graphics	N/A
Max Operating Power	Discrete < 65W UMA < 45W
<b>Temperature</b>	
Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)
<b>Relative Humidity</b>	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Shock</b>	
Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine
<b>Random Vibration</b>	
Operating	1.043 grams
Non-operating	3.5 grams
<b>Altitude (unpressurized)</b>	
Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Planned Industry Standard Certifications</b>	
Regulatory Model Number	HSN-Q35C-4
UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR®	Yes <sup>50</sup>
EPEAT®	EPEAT® 2019 Gold in United States <sup>51</sup>
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes
UKRSERTCOMPUTER	Yes

### Technical Specifications

50. Configurations of the HP EliteBook 645 G9 that are ENERGY STAR® certified are identified as HP EliteBook 645 G9 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

51. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

#### DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

1. Actual brightness will be lower with touchscreen or HP Sure View.

<p><b>14.0 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2Y 1000 eDP 1.3+PSR 100 PrivacyG4 Plus bent LCD Panel</b></p>	<p><b>Outline Dimensions (W x H)</b> <b>Active Area</b> <b>Weight</b> <b>Diagonal Size</b> <b>Thickness</b> <b>Interface</b> <b>Surface Treatment</b> <b>Touch Enabled</b> <b>Contrast Ratio</b> <b>Refresh Rate</b> <b>Brightness</b> <b>Pixel Resolution</b> <b>Format</b> <b>Backlight</b> <b>Color Gamut Coverage</b> <b>Color Depth</b> <b>Viewing Angle</b> <b>Low Blue Light</b> <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b></p>	<p>314.612x 185.330 (max) 309.312 x 173.990 mm (typ) 230 g 14 inch 2.2/3.9 (max) eDP 1.3 Anti-Glare No 1500:1 60 Hz 1000 nits 1920 x1080 (FHD) WLED RGB sRGB 100% 8 UWVA 85/85/85/85 Yes NA</p>
---	---	---

<p><b>Panel LCD 14 inch FHD (1920 x 1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent Touch on Panel NWBZ</b></p>	<p><b>Outline Dimensions (W x H)</b> <b>Active Area</b> <b>Weight</b> <b>Diagonal Size</b> <b>Thickness</b> <b>Interface</b> <b>Surface Treatment</b> <b>Touch Enabled</b> <b>Contrast Ratio</b> <b>Refresh Rate</b> <b>Brightness</b> <b>Pixel Resolution</b> <b>Format</b> <b>Backlight</b></p>	<p>316.170 x 186.400 (max) 309.370 x 174.020 mm (typ) 305 g (max) 14.0 inch 3.0 / 5.0 (max) eDP 1.2 Anti-Glare On-cell Yes<sup>1</sup> 600:1 (typ) 60 Hz 250 nits<sup>1</sup> 1920 x 1080 (FHD) WLED RGB</p>
--	---	--



### Technical Specifications

<b>Color Gamut Coverage</b>	NTSC 45%
<b>Color Depth</b>	6 (Hi FRC w/ condition to enable)
<b>Viewing Angle</b>	UWVA 85/85/85/85
<b>Low Blue Light</b>	No
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.30 (max)/ 2.80 (max)

**Panel LCD 14 inch FHD (1920 x 1080) Anti-Glare WLED UWVA sRGB 100percent cg 400nits eDP 1.4+PSR2 bent LP NB2X**

<b>Outline Dimensions (W x H)</b>	315.070 x 186.600 (max)
<b>Active Area</b>	309.370 X 174.020 mm (typ)
<b>Weight</b>	200 g (max)
<b>Diagonal Size</b>	14.0 inch
<b>Thickness</b>	2.0 /4.0 (max)
<b>Interface</b>	eDP 1.4
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	1200:1 (typ)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	400 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	WLED
<b>Backlight</b>	RGB
<b>Color Gamut Coverage</b>	sRGB 100%
<b>Color Depth</b>	6
<b>Viewing Angle</b>	UWVA 85/85/85/85
<b>Low Blue Light</b>	No
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.07 (max)/ 2.50 (max)

**Panel LCD 14-in FHD (1920 x 1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent**

<b>Outline Dimensions (W x H x D)</b>	316.170 x 186.400 (max)
<b>Active Area</b>	309.370 x 174.020 mm (typ)
<b>Weight</b>	300 g (max)
<b>Diagonal Size</b>	14.0 inch
<b>Thickness</b>	3.0 / 5.0 (max)
<b>Interface</b>	eDP 1.2
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	600:1 (typ)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	250 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	WLED
<b>Backlight</b>	RGB
<b>Color Gamut Coverage</b>	NTSC 45%
<b>Color Depth</b>	6 (Hi FRC w/ condition to enable)

### Technical Specifications

<b>Viewing Angle</b>	UWVA 85/85/85/85
<b>Low Blue Light</b>	No
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.205 (max)/ 2.716 (max)

**Panel LCD 14-in HD (1366 x 768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent**

<b>Outline Dimensions (W x H x D)</b>	316.110 x 186.370 (max)
<b>Active Area</b>	309.400 x 173.950 mm (typ)
<b>Weight</b>	300 g (max)
<b>Diagonal Size</b>	14.0 inch
<b>Thickness</b>	3.0 / 5.0 (max)
<b>Interface</b>	eDP 1.2
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	300:1 (typ)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	250 nits
<b>Pixel Resolution</b>	1366 x 768 (HD)
<b>Format</b>	WLED
<b>Backlight</b>	RGB
<b>Color Gamut Coverage</b>	NTSC 45%
<b>Color Depth</b>	6
<b>Viewing Angle</b>	SVA 45/45/15/35
<b>Low Blue Light</b>	No
<b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>	2.52 (max) / 2.86 (max)

### Technical Specifications

#### STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

<b>SSD 128GB 2230 PCIe NVMe Value</b>	<b>Drive Weight</b>	M.2 2230
	<b>Rotation speed</b>	128GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.01 lb (5 g)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	Up to 2100 MB/s
	<b>Maximum Sequential Write</b>	Up to 1200 MB/s
	<b>Logical Blocks</b>	250069680
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	Pyrite; TRIM; L1.2

<b>SSD 256GB 2230 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2230
	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	up to 2500 MB/s
	<b>Maximum Sequential Write</b>	up to 1300 MB/s
	<b>Logical Blocks</b>	500118192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	Pyrite; TRIM; L1.2

<b>SSD 256GB 2280 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	Value
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	Up to 2900 MB/s
	<b>Maximum Sequential Write</b>	Up to 1400 MB/s
	<b>Logical Blocks</b>	500118192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security; TRIM; L1.2

### Technical Specifications

<b>SSD 256GB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	3D TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	9.0g
	<b>Interface</b>	PCIe NVMe Gen4
	<b>Maximum Sequential Read</b>	Up to 6,400 MB/s
	<b>Maximum Sequential Write</b>	Up to 2,700 MB/s
	<b>Logical Blocks</b>	500118192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	Pyrite 2.0; TRIM; L1.2

<b>256GB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen4
	<b>Maximum Sequential Read</b>	6400
	<b>Maximum Sequential Write</b>	2700
	<b>Logical Blocks</b>	500118192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security (Option); TCG Opal 2.0; TRIM; L1.2

<b>SSD 512GB 2280 PCIe NVMe Value</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	Value
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	Up to 3500 MB/s
	<b>Maximum Sequential Write</b>	up to 3000 MB/s
	<b>Logical Blocks</b>	1000215216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	TRIM; L1.2

### Technical Specifications

<b>SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	3D TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	9.0g
	<b>Interface</b>	PCIe NVMe Gen4
	<b>Maximum Sequential Read</b>	Up to 6,600 MB/s
	<b>Maximum Sequential Write</b>	Up to 5,100 MB/s
	<b>Logical Blocks</b>	1000215216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	Pyrite 2.0; TRIM; L1.2

<b>512GB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen4
	<b>Maximum Sequential Read</b>	Up to 6,600 MB/s
	<b>Maximum Sequential Write</b>	Up to 5,100 MB/s
	<b>Logical Blocks</b>	1000215216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security (Option); TCG Opal 2.0; TRIM; L1.2

<b>SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	1TB
	<b>NAND Type</b>	3D TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen4
	<b>Maximum Sequential Read</b>	Up to 7,100 MB/s
	<b>Maximum Sequential Write</b>	Up to 5,200 MB/s
	<b>Logical Blocks</b>	2000409264
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	Pyrite 2.0; TRIM; L1.2

### Technical Specifications

#### NETWORKING/COMMUNICATIONS

**Qualcomm® Fast Connect Wireless LAN Standards 6900 Wi-Fi 6E + BT5.2 (802.11ax 2x2, AMD AIM-T AME, supporting gigabit file transfer speeds)<sup>1</sup>**

IEEE 802.11a  
IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n  
IEEE 802.11ac  
IEEE 802.11ax  
IEEE 802.11d  
IEEE 802.11e  
IEEE 802.11h  
IEEE 802.11i  
IEEE 802.11k  
IEEE 802.11r  
IEEE 802.11u  
IEEE 802.11v  
IEEE 802.11w

**Interoperability  
Frequency Band**

Wi-Fi certified  
•802.11b/g/n/ax  
2.402 – 2.482 GHz  
•802.11a/n/ac/ax  
5.15 – 5.25 GHz  
5.25 – 5.35 GHz  
5.47 – 5.725 GHz  
5.825 – 5.850 GHz  
5.925 – 7.125 GHz

**Data Rates**

•802.11b: 1, 2, 5.5, 11 Mbps  
•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)  
•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)  
• 802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)

**Modulation**

Direct Sequence Spread Spectrum  
OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM

**Security<sup>3</sup>**

•AES-CCMP: 128 bit in hardware  
•802.1x authentication  
•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.  
•WPA2 certification  
•IEEE 802.11i

**Network Architecture  
Models**

Wi-Fi Direct in Win10 for peer-to-peer connection.  
Infrastructure (Access Point Required)

**Roaming**

IEEE 802.11 compliant roaming between access points

**Output Power<sup>2</sup>**

2.4GHz (MIMO, typical):  
• 802.11b: +18dBm  
• 802.11g: +16.5dBm  
• 802.11n/ac/ax (HT20/VHT20/HE20): +16dBm  
• 802.11n/ac/ax (HT40/VHT40/HE40): +12.5dBm  
5GHz (MIMO, typical):  
• 802.11a: +13dBm  
• 802.11n/ac/ax (HT20/VHT20/HE20): +13.5dBm  
• 802.11n/ac/ax (HT40/VHT40/HE40): +12.5dBm  
• 802.11ac/ax (VHT80/HE80): +11.5dBm

### Technical Specifications

- 802.11ax HE160: +11.5dBm
- 6GHz LPI mode (MIMO, typical):
- 802.11a: 0dBm
- 802.11ax HE20: +1dBm
- 802.11ax HE40: +4dBm
- 802.11ax HE80: +7dBm
- 802.11ax HE160: +7.5dBm

#### Power Consumption

- Transmit mode: 3.0 W
- Receive mode: 2.0 W
- Idle mode (WLAN associated): 300mW
- Idle mode (WLAN unassociated): 100mW
- Modern Connected Standby: 10mW
- Radio disabled: 8 mW

#### Power Management

ACPI and PCI Express compliant power management  
802.11 compliant power saving mode

#### Receiver Sensitivity<sup>4</sup>

- 2.4GHz (SISO):
- 802.11b, 11Mbps: -82dBm maximum
  - 802.11g, 54Mbps: -71dBm maximum
  - 802.11n, MCS7: -64dBm maximum
  - 802.11ac, MCS9: -52dBm maximum
  - 802.11ax, MCS11(HT40): -49dBm maximum
- 5GHz (SISO):
- 802.11a, 54Mbps: -71dBm maximum
  - 802.11n, MCS07: -64dBm maximum
  - 802.11ac, MCS9: -52dBm maximum
  - 802.11ax, MCS11(HE80/HE160): -46dBm maximum
- 6GHz (SISO):
- 802.11a, 54Mbps: -71dBm maximum
  - 802.11n, MCS7: -64dBm maximum
  - 802.11ac, MCS9: -52dBm maximum
  - 802.11ax, MCS11(HE160): -46dBm maximum"

#### Antenna type

High efficiency antenna with spatial diversity, mounted in the display enclosure.  
Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

#### Form Factor

PCI-Express M.2 MiniCard

#### Dimensions

Type 2230: 2.3 x 22.0 x 30.0 mm

#### Weight

Type 2230: 3g

#### Operating Voltage

3.3 +/- 0.165v

#### Temperature

**Operating** -10° to 60° C  
**Non-operating** -40° to 85° C

#### Humidity

**Operating** 10% to 60% (non-condensing)  
**Non-operating** 5% to 95% (non-condensing)"

#### Altitude

**Operating** 0 to 10,000 ft (3,048 m)  
**Non-operating** 0 to 50,000 ft (15,240 m)

#### LED Activity

N/A

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2 Wireless Technology

##### Bluetooth Specification

4.0/4.1/4.2/5.0/5.1/5.2 Compliant

##### Frequency Band

2402 to 2480 MHz

##### Number of Available Channels

Legacy : 0~79 (1 MHz/CH)  
BLE : 0~39 (2 MHz/CH)

##### Data Rates and

Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps

### Technical Specifications

Throughput	BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

**Realtek RTL8852BE  
802.11ax 2x2 Wi-Fi® +  
BT5.2 (802.11ax 2x2,  
supporting gigabit data  
rate) <sup>1</sup>**

#### Wireless LAN Standards

IEEE 802.11a  
IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n  
IEEE 802.11ac  
IEEE 802.11ax  
IEEE 802.11d  
IEEE 802.11e  
IEEE 802.11h  
IEEE 802.11i  
IEEE 802.11k  
IEEE 802.11r  
IEEE 802.11v

#### Interoperability Frequency Band

Wi-Fi certified modules  
•802.11b/g/n/ax  
2.402 – 2.482 GHz  
•802.11a/n/ac/ax  
4.9 – 4.95 GHz (Japan)  
5.15 – 5.25 GHz  
5.25 – 5.35 GHz  
5.47 – 5.725 GHz  
5.825 – 5.850 GHz

#### Data Rates

•802.11b: 1, 2, 5.5, 11 Mbps  
•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11n: max 300Mbps  
•802.11ac: max 866.7Mbps  
•802.11ax: max 1201Mbps

#### Modulation

Direct Sequence Spread Spectrum  
BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM

#### Security<sup>3</sup>

•IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only  
•AES-CCMP: 128 bit in hardware  
•802.1x authentication



### Technical Specifications

	<ul style="list-style-type: none"> <li>•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>•WPA2 certification</li> <li>•WPA3 certification</li> <li>•IEEE 802.11i</li> <li>•WAPI</li> </ul>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +18.5dBm minimum</li> <li>• 802.11g: +17.5dBm minimum</li> <li>• 802.11a: +18.5dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +14.5dBm minimum</li> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ax HE40(2.4GHz): +10dBm minimum</li> <li>• 802.11ax HE80(5GHz): +10dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>•Transmit mode:2.5 W</li> <li>•Receive mode:2 W</li> <li>•Idle mode (PSP)180 mW(WLAN Associated)</li> <li>•Idle mode:50 mW(WLAN unassociated)</li> <li>•Connected Standby/Modern Standby: 10mW</li> <li>•Radio disabled: 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	<ul style="list-style-type: none"> <li>•802.11b, 1Mbps : -93.5dBm maximum</li> <li>•802.11b, 11Mbps : -84dBm maximum</li> <li>•802.11a/g, 6Mbps : -86dBm maximum</li> <li>•802.11a/g, 54Mbps : -72dBm maximum</li> <li>•802.11n, MCS07 : -67dBm maximum</li> <li>•802.11n, MCS15 : -64dBm maximum</li> <li>•802.11ac, MCS0 : -84dBm maximum</li> <li>•802.11ac, MCS9 : -59dBm maximum</li> <li>•802.11ax, MCS11(HE40): -57dBm maximum</li> <li>•802.11ax, MCS11(HE80): -54dBm maximum</li> </ul>
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230: 2.8g 2. Type 126: 1.3g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	<b>Operating</b> 14° to 158° F (-10° to 70° C) <b>Non-operating</b> -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating</b> 10% to 90% (non-condensing) <b>Non-operating</b> 5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating</b> 0 to 10,000 ft (3,048 m) <b>Non-operating</b> 0 to 50,000 ft (15,240 m)

### Technical Specifications

**LED Activity**

LED Amber – Radio OFF  
LED Off – Radio ON

**HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2 Wireless Technology**

**Bluetooth Specification**

4.0/4.1/4.2/5.0/5.1/5.2 Compliant

**Frequency Band**

2402 to 2480 MHz

**Number of Available Channels**

Legacy: 0~79 (1 MHz/CH)  
BLE: 0~39 (2 MHz/CH)

**Data Rates and Throughput**

Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps  
BLE: 1 Mbps data rate; throughput up to 0.2 Mbps  
Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels  
Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

**Transmit Power**

The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11ax) is backwards compatible with prior 802.11 specs. Wi-Fi 6™ is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Technical Specifications

<b>Intel® XMM™ 7560 R+ LTE-Advanced Pro<sup>1</sup></b>	<b>Technology/Operating bands</b>	<p>FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1900 (Band 25), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 1700/2100 (Band 66), 600 (band 71).</p> <p>TDD LTE: 2100 (Band 34), 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41), 3500 (Band 42), 3700 (Band 43), 3700 (band 48), 5200 (Band 46 RX only) MHz; HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz</p>
	<b>Wireless protocol standards</b>	3GPP Release 12 LTE Specification DL-CAT.16, DL 100MHz BW throughput up to 978Mbps; UL-CAT.13 40MHz throughput up to 150Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	<b>GPS GPS bands</b>	Standalone GPS/Beidou/Glonass, A-GPS (MS-A, MS-B) 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	<b>Maximum data rates</b>	LTE: 978 Mbps (Download), 150 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	<b>Maximum output power</b>	LTE: 23 dBm in all band except B41 LTE B41 HPUE = 26dBm HSPA+: 23.5 dBm
	<b>Maximum power consumption</b>	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
	<b>Form Factor</b>	M.2, 3042-S3 Key B
	<b>Weight</b>	6 g
	<b>Dimensions (Length x Width x Thickness)</b>	42 x 30 x 2.3 mm

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

## Technical Specifications

<b>NXP NPC300 Near Field Communication Module</b>	<b>Dimensions (L x W x H)</b>	Module 17 mm by 10 mm by 2.0 mm
	<b>Chipset</b>	NPC300
	<b>System interface</b>	I2C
	<b>NFC RF standards</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	<b>NFC Forum Support Reader (PCD-VCD) Mode(1)</b>	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2 ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
	<b>Card Emulation (PICC-VICC) Mode(1)</b>	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
	<b>Frequency</b>	13.56 MHz
	<b>NFC Modes Supported</b>	Reader/Writer, Peer-to-Peer
	<b>Raw RF Data Rates</b>	106, 212, 424, 848 kbps
	<b>Operating temperature</b>	0°C to 70°C
	<b>Storage temperature</b>	-20°C to 125°C
	<b>Humidity</b>	10-90% operating 5-95% non-operating
	<b>Supply Operating voltage</b>	2.97 to 5.5 Volts
	<b>I/O Voltage</b>	1.8V or 3.3V
	<b>Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)</b>	
	<b>Mode</b>	Power Consumption, Typical
	<b>Polling</b>	7.3 mA
	<b>Detected Test Tag Type 1</b>	32.9 mA
	<b>Detected Test Tag Type 2</b>	70.7 mA
	<b>Detected Test Tag Type 3</b>	79.2 mA
	<b>Detected Test Tag Type 4</b>	64.9 mA
	<b>Antenna</b>	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

### Technical Specifications

1. WWAN module is an optional feature, requires factory configuration and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. LTE not available on all products, in all regions

<b>Realtek RTL8111HSH</b> <b>10/100/1000</b> <b>Integrated NIC</b>	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
	<b>Manageability</b>	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	<b>Interface</b> <b>NIC Device Driver Name</b>	PCIe + SMBus Realtek PCIe GBE Ethernet Family Controller

<b>Realtek RTL8111FPH</b> <b>10/100/1000</b> <b>Integrated NIC</b>	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K

### Technical Specifications

**Manageability**

Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)  
PXE 2.1 Remote Boot  
Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))  
Comprehensive diagnostic and configuration software suite  
Virtual Cable Doctor for Ethernet cable status

**Interface**

PCIe + SMBus

**NIC Device Driver Name**

Realtek PCIe GBE Ethernet Family Controller

---

### Technical Specifications

#### POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

<b>AC Adapter 45 Watt nPFC Standard USB type C Straight 1.8m</b>	<b>Dimensions (H x W x D)</b>	94.0mm x 40.0mm x 26.5mm
	<b>Weight</b>	192.5g +/-10%
	<b>Input</b>	<b>Input Efficiency</b> Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%"
	<b>Output</b>	<b>Input frequency range</b> 47 ~ 63Hz <b>Input AC current</b> Max. 1.4 A at 90 Vac <b>Output power</b> 5V/15W 9V/27W 12V/36W 15V/45W <b>DC output</b> 5V/9V/12V/15V <b>Hold-up time</b> 5ms at 115 Vac input <b>Output current limit</b> <5.0A
	<b>Connector</b>	USB Type-C
	<b>Environmental Design</b>	<b>Operating temperature</b> 32°F to 95°F (0° to 35°C) <b>Non-operating (storage) temperature</b> -4°F to 185°F (-20° to 85°C) <b>Altitude</b> 0 to 16,400 ft (0 to 5,000m) <b>Humidity</b> 20% to 95% <b>Storage Humidity</b> 10% to 95%
	<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

<b>AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b>	<b>Dimensions</b>	95x45x26.5mm
	<b>Weight</b>	unit: 200g +/- 10g
	<b>Input</b>	<b>Input Efficiency</b> 87.74 % at 115 Vac and 88.4 % at 230Vac <b>Input frequency range</b> 47 ~ 63 Hz <b>Input AC current</b> Max. 1.4 A at 90 Vac
	<b>Output</b>	<b>Output power</b> 45W <b>DC output</b> 19.5V <b>Hold-up time</b> 5ms at 115 Vac input <b>Output current limit</b> <8.0A

### Technical Specifications

<b>Connector</b>	4.5mm Barrel Type
<b>Environmental Design</b>	<b>Operating temperature</b> 32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b> -4°F to 185°F (-20°to 85°C)
	<b>Altitude</b> 0 to 16,400 ft (0 to 5,000m)
	<b>Humidity</b> 20% to 95%
	<b>Storage Humidity</b> 10% to 95%
<b>EMI and Safety Certifications</b>	Eg:
	*CE Mark - full compliance with LVD and EMC directives
	* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV;
	Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.
	* MTBF - over 200,000 hours at 25°C ambient condition.

#### AC Adapter 65 Watt nPFC Standard USB type C Straight 1.8m

<b>Dimensions</b>	90.0 x 51 x 28.5mm
	<b>Weight</b> unit: 250g +/- 10g
<b>Input</b>	<b>Input Efficiency</b> Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 12V : 88% 15V : 88% 20V : 89%
	<b>Input frequency range</b> 47 ~ 63 Hz
<b>Output</b>	<b>Input AC current</b> 1.6 A at 90 VAC and maximum load 5V/15W 9V/27W 12V/60W 15V/60W 20V/65W
	<b>Output power</b> 5V/9V/12V/15V/20V
	<b>DC output</b>
	<b>Hold-up time</b> 5ms at 115 Vac input
	<b>Output current limit</b> <8.0A
<b>Connector</b>	USB Type C
<b>Environmental Design</b>	<b>Operating temperature</b> 32°Fto 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b> -4°Fto 185°F (-20°to 85°C)
	<b>Altitude</b> 0 to 16,400 ft (0 to 5,000m)
	<b>Humidity</b> 20% to 95
	<b>Storage Humidity</b> 10% to 95%



### Technical Specifications

#### EMI and Safety Certifications

Eg:  
 \*CE Mark - full compliance with LVD and EMC directives  
 \* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV;  
 Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.  
 \* MTBF - over 200,000 hours at 25°C ambient condition.

#### AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm

#### Dimensions

102 x 55 x 30mm

#### Weight

unit: 250g +/- 10g

#### Input

**Input Efficiency** 88.0 % at 115 Vac and 89.0 % at 230Vac  
**Input frequency range** 47 ~ 63 Hz  
**Input AC current** Max. 1.7 A at 90 Vac

#### Output

**Output power** 65W  
**DC output** 19.5V  
**Hold-up time** 5ms at 115 Vac input  
**Output current limit** <11.0A

#### Connector

4.5mm Barrel Type

#### Environmental Design

**Operating temperature** 32°F to 95°F (0°to 35°C)  
**Non-operating (storage) temperature** -4°F to 185°F (-20°to 85°C)  
**Altitude** 0 to 16,400 ft (0 to 5,000m)  
**Humidity** 20% to 95%  
**Storage Humidity** 10% to 95%

#### EMI and Safety Certifications

Eg:  
 \*CE Mark - full compliance with LVD and EMC directives  
 \* Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV;  
 Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE.  
 \* MTBF - over 200,000 hours at 25°C ambient condition.

#### AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m

#### Dimensions

90 x 51 x 28.5mm

#### Weight

230g +/-10%

#### Input

**Input Efficiency** 88.0 % at 115 Vac and 89.0 % at 230 Vac  
**Input frequency range** 47 ~ 63 Hz  
**Input AC current** Max. 1.7 A at 90 Vac

#### Output

**Output power** 65W  
**DC output** 19.5V  
**Hold-up time** 5 ms at 115 Vac input  
**Output current limit** <11.0A

#### Connector

4.5mm Barrel Type

### Technical Specifications

<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
	<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

<b>AC Adapter 65 Watt nPFC Slim USB type C Straight 1.8m</b>	<b>Dimensions</b>	88x53.5x21mm		
	<b>Weight</b>	unit: 220g +/- 10g		
	<b>Input</b>	<b>Input Efficiency</b>	81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A	
		<b>Input frequency range</b>	47 ~ 63 Hz	
		<b>Input AC current</b>	1.7 A at 90 VAC and maximum load	
		<b>Output</b>	<b>Output power</b>	65W
			<b>DC output</b>	5V/9V/12V/15V/20V
	<b>Hold-up time</b>		5ms at 115 Vac input	
	<b>Connector</b>	<b>Output current limit</b>	<8.0A	
	<b>Environmental Design</b>	USB Type C		
		<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)	
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)	
		<b>Altitude</b>	0 to 16,400 ft (0 to 5,000m)	
<b>Humidity</b>		5% to 95%		
<b>Storage Humidity</b>		5% to 95%		
<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950-1 and/or IEC62368-1, EN60950-1 and/or EN62368-1, UL60950-1 and/or UL62368-1 , Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, NOM-001 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.			

### Technical Specifications

<b>RH 42Whr Long Life Polymer Fast Charge 3 cell Battery</b>	<b>Dimensions (H x W x L)</b>	6.2 x 76.25 x 249.50 mm (0.244 x 3.002 x 9.823 inch)
	<b>Weight</b>	0.18 kg (0.397 lb)
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / 545974
	<b>Energy</b>	
	<b>Voltage</b>	11.4V
	<b>Amp-hour capacity</b>	3.752Ah
	<b>Watt-hour capacity<sup>1</sup></b>	42.75Wh
	<b>Temperature</b>	
	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
	<b>Fuel Gauge LED</b>	N/A
	<b>Warranty</b>	
	<b>Optional Travel Battery Available</b>	No

---

<b>RH 51Whr Long Life Polymer Fast Charge 3 cell Battery</b>	<b>Dimensions (H x W x L)</b>	6.50 x 67.80 x 254.00 mm (0.256 x 2.669 x 10 inch)
	<b>Weight</b>	0.2025 kg (0.446 lb)
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / 566075
	<b>Energy</b>	
	<b>Voltage</b>	11.58V
	<b>Amp-hour capacity</b>	4.431Ah
	<b>Watt-hour capacity<sup>1</sup></b>	51.3Wh
	<b>Temperature</b>	
	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
	<b>Fuel Gauge LED</b>	N/A
	<b>Warranty</b>	
	<b>Optional Travel Battery Available</b>	No

---

### Technical Specifications

#### AUDIO

<b>HD Stereo Codec</b>	ALC3247-CG
<b>Audio I/O Ports</b>	Headset: CTIA only and Headphone-out
<b>Internal Speaker Amplifier</b>	ALC 3247 has Embedded Class-D 2W Stereo Amplifier
<b>Multi-streaming Capable</b>	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behavior
<b>Sampling</b>	DAC: 48kHz ADC: 44.1k/48kHz
<b>Wavetable Syntheses</b>	N/A
<b>Analog Audio</b>	Support 3.5mm Headset: CTIA only and Headphone-out
<b># of Channels on Line-Out</b>	N/A
<b>Internal Speaker</b>	Yes

#### FINGERPRINT READER

<b>Sensor vendor</b>	Model: Elan efsa80ST (module P1515E)
<b>Sensor type</b>	Capacitive
<b>DPI resolution</b>	508 dpi
<b>Scan area</b>	80*80 pixels
<b>False Rejection Rate</b>	FRR: ≤ 3%
<b>False Acceptance Rate</b>	FAR: 1:100K
<b>Mobile Voltage Operation</b>	2.7V to 3.6V
<b>Operating Temperature</b>	-4°F – 175°F (-20° ~ +80°C)
<b>Current Consumption</b>	50mA peak
<b>Image</b>	
<b>Low Latency Wait For Finger</b>	900uA
<b>Capture Rate</b>	30 frame/sec
<b>ESD Resistance</b>	+15KV
<b>Detection Matrix</b>	80*80 pixels/ 508 dpi / 4*4mm sensor area

### Technical Specifications

#### ENVIRONMENTAL DATA

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul>		
<b>Sustainable Specifications</b>	<p><b>Impact</b></p> <ul style="list-style-type: none"> <li>• Ocean-bound plastic in Speaker</li> <li>• 15% post-consumer recycled plastic</li> <li>• Low halogen</li> <li>• Outside Box and corrugated cushions are 100% sustainably sourced and recyclable</li> <li>• Recycled Plastic cushions</li> <li>• Bulk packaging available</li> </ul>		
<b>System Configuration</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>		
<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Sort idle)	5.57 W	5.47 W	5.01 W
Normal Operation (Long idle)	0.95 W	1.31 W	1.23 W
Sleep	0.95 W	1.31 W	1.23 W
Off	0.30 W	0.30 W	0.28 W
	<p>Note:            Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	19 BTU/hr	18.7 BTU/hr	17.1 BTU/hr
Normal Operation (Long idle)	3.2 BTU/hr	4.5 BTU/hr	4.2 BTU/hr
Sleep	3.2 BTU/hr	4.5 BTU/hr	4.2 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr
	<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>		

### Technical Specifications

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	2.2	13.3	
Fixed Disk – Random writes	2.7	18.3	
Optical Drive – Sequential reads	2.9	22.4	
<b>Longevity and Upgrading</b>	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.		
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT) standard at the <b>Gold</b> level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product is 93.2% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	220 g
	<b>Internal:</b>	PLASTIC/EPE (Expanded Polyethylene)	170 g
		PLASTIC/Polyethylene low density - LDPE	55 g
		PLASTIC/Polypropylene - PP	3 g
	The plastic packaging material contains at least 0.0% recycled content.		
The corrugated paper packaging materials contains at least 54.5% recycled content.			
<b>RoHS Compliance</b>	<p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p>		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> </ul>		

### Technical Specifications

	<ul style="list-style-type: none"> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Bis(2-Ethylhexyl) phthalate (DEHP)</li> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>
<p><b>Packaging Usage</b></p>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<p><b>End-of-life Management and Recycling</b></p>	<p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>

### Technical Specifications

<b>HP, Inc. Corporate Environmental Information</b>	For more information about HP's commitment to the environment:  Global Citizenship Report <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a> Eco-label certifications <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a> ISO 14001 certificates: <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a> and <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a>
<b>footnotes</b>	<ul style="list-style-type: none"><li>• Percentage of ocean-bound plastic contained in each component varies by product</li><li>• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.</li><li>• External power supplies, WWAN modules, power cords, cables and peripherals excluded.</li><li>• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</li><li>• Plastic cushions are made from &gt;90% recycled plastic.</li></ul>

### COUNTRY OF ORIGIN

China



### Options and Accessories (sold separately and availability may vary by country)

#### DOCKING (Sold Separately)

<b>Docking station model #1</b>	HP Thunderbolt Dock G2
<b>Total number of supported displays (incl.the notebook display)</b>	4
<b>Max.resolutions supported</b>	Dual 4K @30Hz or dual 4K UHD @ 60Hz is supported Dual 8K@ 60Hz for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode 2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode
<b>Dock Connectors</b>	
<b>Technical limitations</b>	Thunderbolt Hosts: Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host. Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz Non-Thunderbolt hosts: The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is (1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.
<b>Docking station model #2</b>	HP USB-C Dock G5
<b>Total number of supported displays (incl.the notebook display)</b>	3
<b>Max.resolutions supported</b>	Dual 5K@ 30Hz + 1 4K UHD (multi-function mode)
<b>Dock Connectors</b>	1xHDMI, 2xDP
<b>Technical limitations</b>	Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode. Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode The highest resolution for a non-Thunderbolt host in multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.
<b>Docking station model #3</b>	HP USB-C/A Universal Dock G2
<b>Total number of supported displays (incl.the notebook display)</b>	3
<b>Max.resolutions supported</b>	Triple 4K UHD@ 60Hz 3840 x 2160
<b>Dock Connectors</b>	1xHDMI, 2xDP
<b>Technical limitations</b>	The best resolution for dual or triple displays is 4K UHD@ 60Hz. For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host.

### Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
Audio/Video	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
Cases	HP Business 14.1 Sleeve	2UW01AA
	HP Business Slim 17.3 Top Load	2UW02AA
	HP Executive 14.1 Tote	6KD10AA
	HP Executive 15.6 Backpack	6KD07AA
	HP Executive 15.6 Top Load	6KD06AA
	HP Executive 17.3 Backpack	6KD05AA
	HP Executive 17.3 Top Load	6KD08AA
	HP Executive Leather 15.6 Top Load	6KD09AA
	HP Executive Slim 14.1 Top Load	6KD04AA
	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew 14 Laptop Sleeve	2E6U9AA,2E6V0AA
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
HP Renew Business 14.1 Laptop Bag	3E5F9AA	
HP Renew Business 15.6 Laptop Bag	3E5F8AA	
Docking	HP Thunderbolt 120W G2 Dock	2UK37AA
	HP Thunderbolt 120W G2 Dock w/Audio	3YE87AA
	HP Thunderbolt 120W G4 Dock	4J0A2AA
	HP Thunderbolt 230W G2 Dock w/Combo Cable	3TR87AA
	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4AA
	HP USB-C/A 120W G2 Universal Dock	5TW13AA
	HP USB-C 120W G5 Dock	26D32AA
Hub	HP Universal USB-C Multiport Hub	50H55AA
	HP USB-C Travel Dock G2	7PJ38AA
	HP USB-C to USB-A Hub	Z6A00AA
Adapter	HP HDMI to DVI Adapter	F5A28AA
	HP HDMI to VGA Adapter	H4F02AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA
	HP USB-C to VGA Adapter	N9K76AA
Keyboard/Combo	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 455 Programmable Wireless Keyboard	4R177AA

### Options and Accessories (sold separately and availability may vary by country)

	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA
<b>Mouse</b>	HP USB Premium Wireless Mouse	1JR31AA
	HP 435 Multi-Device Wireless Mouse	3B4Q5AA
	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 320M USB-A Wired Mouse	9VA80AA
	HP Creator USB-A+Bluetooth 935 Wireless Mouse Black	1D0K8AA
	HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black	1D0K2AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA
<b>Power</b>	HP 65W USB-C Auto Chevy AC Power Adapter	5TQ76AA
	HP 45W 4.5 mm Smart AC Power Adapter	H6Y88AA
	HP 45W USB-C G2 Zeus AC Power Adapter	1HE07AA
	HP 45W USB-C LC Dali AC Power Adapter	1MZ01AA
	HP 65W 4.5 mm LC Smart non-EM India Ony AC Power Adapter	3FF84AA#ACJ
	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA
	HP 65W 4.5 mm wDongle 7.4 mm Slim AC Power Adapter	H6Y82AA
	HP 65W USB-C Hades AC Power Adapter	1HE08AA
	HP 65W USB-C LC AC Power Adapter	1P3K6AA
<b>Commodity</b>	HP USB DVD-Writer EXT ODD	F2B56AA
	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA

### Summary of Changes

Date of change	Version History		Description of change
January 25, 2022	V1 to V2	Add	TPM, Smart reader, IPv6 Compliance and FirstNet Certified in Security section and Battery Life
	V2 to V3		

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.