



## Voxicon DC155UHPAP UHD 24/7 High Haze



### Key features:

- 55"
- 4K
- 24/7 operation
- 500cd/m<sup>2</sup>
- Haze Level 25

### Large monitor with UHD resolution

The Voxicon DC155UHPAP has a sleek and stylish design designed to run for hours on end without interruption. The monitor is 55" and Ultra HD for the perfect sharpness and is ideal for the retail market as well as the conference room or reception.

Header		Performance	
Manufacturer	<a href="#">Voxicon</a>	Purpose	Corporate
<b>Display</b>		Miracast	Yes
Display diagonal	55"	Operating hours (hours/days)	24/7
Panel type	IPS	Browsing	Yes
Display technology	LED	<b>Power</b>	
LED backlighting type	Direct-LED	Power consumption (typical)	138 W
LED backlight	Yes	Power consumption (standby)	0.5 W
Display resolution	3840 x 2160 pixels	Energy efficiency class (SDR)	G
Display brightness	500 cd/m <sup>2</sup>	AC input voltage	230 V
HD type	4K Ultra HD	Power consumption (off)	0.3 W
Touchscreen	No	Energy efficiency class (HDR)	G
Response time	8 ms	Power consumption (max)	180 W
Native aspect ratio	16:9	AC input frequency	60 Hz
Contrast ratio (typical)	1200:1	Energy consumption (SDR) per 1000 hours	138 kW·h
Viewing angle, horizontal	178 °	Energy consumption (HDR) per 1000 hours	138 kW·h
Display number of colours	1.073 billion colours		
Viewing angle, vertical	178 °		
Contrast ratio (dynamic)	50000:1		
Active display area (W x H)	1209.6 x 680.4 mm		
Panel life	50000 h		
Native refresh rate	60 Hz		
Haze rate	25 %		
RGB colour space	NTSC		

<b>Ports &amp; interfaces</b>		<b>Computer system</b>	
HDMI ports quantity	5	Internal memory	2 GB
HDMI version	2.0	Computer system	Yes
DVI port	No	Built-in processor	Yes
HDMI input ports quantity	4	Processor manufacturer	ARM
HDMI output ports quantity	1	Processor model	A55
USB port	Yes	On-board graphics card model	ARM Mali-G31 MP2
USB ports quantity	3	Processor cores	4
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	<b>Weight &amp; dimensions</b>	
Ethernet LAN	Yes	Display width	1236 mm
Ethernet LAN (RJ-45) ports	1	Display depth	63 mm
PC Audio in	No	Display height	709 mm
Ethernet LAN data rates	100 Mbit/s	Display weight	18500 g
Wi-Fi	Yes	<b>Packaging content</b>	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Stand included	No
USB connector type	USB Type-A	Remote control included	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Power adapter included	Yes
Microphone in	No	Power adapter model	110 - 240 VAC 50/5C
<b>Audio</b>		Mounting kit	Yes
Built-in speaker(s)	Yes	<b>Packaging data</b>	
Number of built-in speakers	2	Package width	1369 mm
RMS rated power	10 W	Package depth	165 mm
<b>Design</b>		Package height	874 mm
Product design	Digital signage flat panel	Package weight	24100 g
Product colour	Black	<b>Operational conditions</b>	
Placement supported	Indoor	Operating temperature (T-T)	0 - 40 °C
VESA mounting	Yes	Operating relative humidity (H-H)	10 - 90 %
Panel mounting interface	400 x 400 mm		