

Voxicon DC165UHPAP UHD 24/7 High Haze



Key features:

- 65"
- 4K
- 24/7 operation
- 500cd/m²
- Haze Level 25

Large monitor with UHD resolution

The Voxicon DC165UHPAP has a sleek and stylish design designed to run for hours on end without interruption. The monitor is 65" and Ultra HD for the perfect sharpness and is ideal for the retail market as well as the conference room or reception.

Header		Performance	
Manufacturer	<u>Voxicon</u>	Purpose	Corporate
		Operating hours	
Display		(hours/days)	24/7
Display diagonal	65 "	Browsing	Yes
Display technology	LED		
Panel type	IPS	Power	
LED backlighting type	Direct-LED	Power consumption	
LED backlight	Yes	(typical)	194 W
Display resolution	3840 x 2160 pixels	Power consumption	
Display brightness	500 cd/m ²	(standby)	0.5 W
HD type	4K Ultra HD	Power consumption (sleep)	0.3 W
Touchscreen	No	Input voltage	220 V
Response time	8 ms	Power consumption (off)	O W
Native aspect ratio	16:9	AC input voltage	220 V
Contrast ratio (typical)	1200:1	Energy efficiency class	
Viewing angle, horizontal	178 °	(SDR)	G
Display number of colours	1.073 billion colours	Power consumption (max)	220 W
Viewing angle, vertical	178 °	Energy consumption (SDR)	
Contrast ratio (dynamic)	50000:1	per 1000 hours	194 kW·h
Active display area (W x H)	1428.5 x 803.5 mm	Energy efficiency class	
Panel life	50000 h	(HDR)	G
Native refresh rate	60 Hz	AC input frequency	50 - 60 Hz
Frame width	1456 mm	Energy consumption (HDR)	
Haze rate	25 %	per 1000 hours	194 kW·h
Maximum frame rate	60 fps	Energy efficiency scale	A to G
RGB colour space	NTSC		

		Computer system	
Ports & interfaces		Internal memory	2 GB
HDMI ports quantity	5	Computer system	Yes
HDMI version	2.0	Built-in processor	Yes
HDMI input ports quantity	4	Processor manufacturer	ARM
HDMI output ports		Processor model	A55
quantity	1	On-board graphics card	
DVI port	No	model	ARM Mali-G31 MP2
USB port	Yes	Processor cores	4
USB ports quantity	3		
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Weight & dimensions	
Ethernet LAN	Yes	Display width	1456 mm
Ethernet LAN (RJ-45)		Display depth	74 mm
ports	1	Display height	834 mm
PC Audio in	No	Display weight	24700 g
Ethernet LAN data rates	100 Mbit/s	B 1 1	
Wi-Fi	Yes	Packaging content Remote control included	V
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5	Stand included	Yes
	(802.11ac)		No Yes
USB connector type	USB Type-A	Mounting kit	Yes
USB 3.2 Gen 1 (3.1 Gen 1)		Power adapter included	
Type-A ports quantity	1	Power adapter model	110 - 240 VAC 50/50Hz
Microphone in	No	Packaging data	
		Package width	1650 mm
Audio		Package depth	190 mm
Built-in speaker(s)	Yes	Package height	997 mm
Number of built-in		Package weight	34750 g
speakers	2		
RMS rated power	10 W	Operational conditions	
		Operating temperature (T-	
Design		T)	0 - 40 °C
Product design	Digital signage flat panel	Operating relative humid-	
Product colour	Black	ity (H-H)	10 - 90 %
Placement supported	Indoor		
VESA mounting	Yes		
Panel mounting interface	600 x 400 mm		
Bezel width (side)	10 mm		
Bezel width (bottom)	14 mm		
Bezel width (top)	10 mm		