

## Voxicon DC175UHPAP UHD 24/7 High Haze



## Key features:

- 75"
- 4K
- 24/7 operation
- 500cd/m<sup>2</sup>
- Haze Level 25

## Large monitor with UHD resolution

The Voxicon DC175UHPAP has a sleek and stylish design designed to run for hours on end without interruption. The monitor is 75" and Ultra HD for the perfect sharpness and is ideal for the retail market as well as the conference room or reception.

Header		Performance	
Manufacturer	Voxicon	Purpose	Corporate
		Miracast	Yes
Display		Operating hours	
Display diagonal	75 "	(hours/days)	24/7
Panel type	IPS	Browsing	Yes
Display technology	LED		
LED backlighting type	Direct-LED	Power	
LED backlight	Yes	Power consumption	
Display resolution	3840 x 2160 pixels	(typical)	240 W
Display brightness	500 cd/m <sup>2</sup>	Power consumption	
HD type	4K Ultra HD	(standby)	0.5 W
Touchscreen	No	Power consumption (sleep)	0.3 W
Response time	8 ms	Input voltage	110 - 230 V
Native aspect ratio	16:9	AC input voltage	110 - 230 V
Contrast ratio (typical)	1200:1	Energy efficiency class	
Viewing angle, horizontal	178 °	(SDR)	G
Display number of colours	1.073 billion colours	Power consumption (off)	O W
Viewing angle, vertical	178 °	Energy efficiency class	
Contrast ratio (dynamic)	50000:1	(HDR)	G
Active display area (W x H)	1650 x 928 mm	Power consumption (max)	320 W
Panel life	30000 h	Energy consumption (SDR)	
Native refresh rate	60 Hz	per 1000 hours	235 kW·h
Frame width	1456 mm	AC input frequency	50 - 60 Hz
Haze rate	25 %	Energy consumption (HDR)	
RGB colour space	NTSC	per 1000 hours	235 kW·h
·		Energy efficiency scale	A to G

Ports & interfaces			
HDMI ports quantity	5	Computer system	
HDMI version	2.0	Internal memory	2 GB
HDMI output ports		Computer system	Yes
quantity	1	Built-in processor	Yes
DVI port	No	Processor manufacturer	ARM
HDMI input ports quantity	4	Processor model	A55
USB port	Yes	On-board graphics card	
USB ports quantity	3	model	ARM Mali-G31 MP2
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Processor cores	4
Ethernet LAN	Yes		
PC Audio in	No	Weight & dimensions	
Ethernet LAN data rates	100 Mbit/s	Display width	1684 mm
Ethernet LAN (RJ-45)		Display depth	73 mm
ports	1	Display height	967 mm
Wi-Fi	Yes	Display weight	37500 g
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5	Packaging content	
	(802.11ac)	Remote control included	Yes
USB connector type	USB Type-A	Stand included	No
USB 3.2 Gen 1 (3.1 Gen 1)		Mounting kit	Yes
Type-A ports quantity	1	Power adapter included	Yes
Microphone in	No	Power adapter model	110 - 240 VAC 50/50Hz
		rower adapter moder	110 - 240 VAC 30/30112
Audio		Packaging data	
Built-in speaker(s)	Yes	Package width	1948 mm
Number of built-in		Package depth	210 mm
speakers	2	Package height	1170 mm
RMS rated power	10 W	Package weight	50300 g
Davis		. 9 9	9
Design Draduct design	Digital signage flat panel	Operational conditions	
Product design	Digital signage flat panel	Operating temperature (T-	
Product colour	Black	T)	0 - 40 °C
Placement supported	Indoor	Operating relative humid-	
VESA mounting	Yes	ity (H-H)	10 - 90 %
Panel mounting interface	600 x 400 mm		
Bezel width (bottom)	14 mm		
Bezel width (side)	11 mm		
Bezel width (top)	11 mm		