



U50 5G Mobile Hotspot

U50 is a ZTE 5th-generation affordable premium 5G portable router that supports the 5G NR Rel.15 technologies and integrates Wi-Fi6, and an large battery of 4500mAh capacity. It enables users to smoothly connect to 5G networks anytime & anywhere on tablets, mobile phones, laptops, and control consoles, allowing incredible new experience in ARs, cloud games, and 4K videos.



Ultra-high-speed internet connection

With its compact single-chip architecture, U50 achieves ultrahigh performance-to-cost ratio, with a 5G NR download rate of 2.63Gbps, and Wi-Fi 6 downlink rate of AX1800, demonstrating the ultra-high rate and ultra-low latency of 5G networks end to end.

Rich combinations to exploit the potential of spectrum

U50 supports global mainstream 3G/4G/5G frequency bands and combinations of multi-band ENDC, making full use of operators' existing spectrum resources, and providing users with high-speed, wide-coverage, and smooth-handover cellular network roaming experience.

Abundant management and configuration interfaces

U50 supports local configuration management based on Web-UI and mobile apps*, and remote management based on the TR069 and MQTT protocols. This improves user experience and provides cost-effective, efficient, and reliable solutions for operators' requirements for FWA terminal deployment, firmware upgrade, and O&M.



Interface Description



Specifications

Hardware specifications

5G NR Interface

- 3GPP Release 15
- Supports both NSA and SA modes
- Frequencies:
- n1/3/7/8/20/28/38/40/77/78

4G LTE Interface

- DL Category20, UL Category20(FDD)/18(TDD)
- Frequencies: B1/3/7/8/20/28/32/38/40

UMTS Interface

- DC-HSDPA/HSPA+
- Frequencies: B1/8

Wi-Fi Technology

- Wi-Fi6, 802.11b/g/n/a/ac/ax, 2.4G&5G
- MIMO: 5GHz 2MIMO, 2.4GHz 2MIMO
- Speed: AX1800
- Access number: up to 32

Battery

• Nominal capacity (Catalog value): 4500mAh

Artwork

- Dimensions: 118mm*72mm*18mm
- Weight: about 164g

Speed**

- 5G ENDC(LTE FDD + Sub6G): DL 2.63Gb/s, UL 155Mb/s
- 5G SA: DL 1.43 Gb/s,UL 160Mb/s
- LTE FDD:DL 2.0Gb/s,UL 150Mb/s
- LTE TDD:DL 1.46Gb/s,UL 30Mb/s

Interface

- USB Type-C: USB3.0, DATA & Charging
- SIM slot: 4FF/eSIM (default is SIM slot)
- Reset hole to restore factory default
- Power button
- 2 x TS-9 External Antenna Ports* (Support band: n38/77/78)

LED

- Power indication
- WIFI indication
- Network mode indication

Maximum power consumption

• about 5.5w

Environment

- Operating temperature 0 to 35°C
- Storage temperature -20 to 45°C
- Humidity 5% to 95%

Product Description U50

Package contents

- AC Adapter (Optional) Input: 100-240VAC, 50/60Hz Output: DC 5V/2A
- Battery
- Quick Start Guide

Software specfications

IP Networking & Routing

- IPv4/IPv6 dual stack (NDP IPv6)
- DHCP server
- VPN client: L2TP\PP2P
- VPN pass-through
- NAT/NAPT
- Sip ALG
- Multiple APNs*

Firewall

- Port Forwarding
- Port Filtering
- Port Mapping
- Domain Filtering
- Upnp
- DMZ
- Remote Access/Ping switch
- MAC address filtering

Special Feature

- PC/Phone/PAD WebUI management selfadaptation
- Device Diagnosis will list all device running key status and give fix solution

Certification

• CE, WEEE, ROHS, Wi-Fi

Device Managemnt

- Connected device Management
- SMS
- PIN/PUK management
- APN management
- Lock Frequency/Lock Cell
- TR069 with TR181 data model default*
- Upgrade: FOTA
- ZTE Smartlife APP*

Wi-Fi

- Wi-Fi Switch
- Bandsteering
- Security mode: WPA-PSK/WPA2-PSK, WPA2-PSK/WPA3-PSK,WPA2-PSK
- Wi-Fi Broadcast
- Wi-Fi Isolation
- Auto channel selection
- WPS
- Guest SSID support
- Wi-Fi Sleep Mode
- * Optional customized features.

** The maximum data rates is a theoretical value. The actual data rates depend on the network environment. *** ZTE Lab test data.

For more product information, visit us on the web at https://ztedevices.com

© ZTE. All rights reserved. No spreading without permission of ZTE. All specifications are subject to change without notice.



ZTE Smartlife APP