

[UniFi](#) [UISP](#) [Branding](#)[Switching](#)[WiFi](#)[Camera Security](#)[Door Access](#)[CloudKeys & Gateways](#)[Power Tech](#)[Inte](#)[PoE & Power](#) > [2.5G PoE+ Adapter \(30W\)](#)[Datasheet](#)[Marketing Images](#)[Installation Guide](#)

Dimensions	93 x 62 x 35 mm (3.7 x 2.4 x 1.4")
Weight	156 g (5.5 oz)
Output voltage	48V DC @ 0.65A
LAN activity indicator	No
Gigabit LAN port	Yes, up to 2.5 GbE
Remote reset capability	No
Reset button	No
Rated voltage	100—240V AC @ 50/60Hz
Input current	0.75A max.
Inrush current	<150A peak @ 230V AC
Efficiency	>87%
Output ripple	1% max.
Switching frequency	65 kHz max.

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site

Surge protection	Difference and common mode
Clamping protection	11V data, 60V power
Max. surge discharge	1500A (8/20 μ s) power
Peak pulse current	36A (10/1000 μ s) data
Shunt capacitance	<5 pF data
Response time	<1 ns
Ambient operating temperature	0 to 40° C (32 to 104° F)
Storage temperature	-30 to 70°C (-22 to 158° F)
Ambient operating humidity	10 to 95% noncondensing
Certifications	CE, FCC, IC, UL, UKCA, KC, CCC, RoHS

Stay in Touch

 

[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site