

[UniFi](#) [UISP](#) [Branding](#)

Q

Search UniFi products

[Switching](#) [WiFi](#) [Camera Security](#) [Door Access](#) [CloudKeys & Gateways](#) [Power Tech](#) [Inte](#)

[RJ45 & Copper](#) > [UniFi Indoor Cable Cat6A CMP](#)

Datasheet

Marketing Images

Mechanical

Box dimensions	494 x 302 x 481 mm (19.4 x 11.9 x 18.9")
Box weight	21.3 kg (47 lb)
Cable length	305 m (1000 ft)
Cable color	White
Cable type	Category 6A
Shielding type	UTP
Flame rating	CMP
Conductor wire gauge	23 AWG
Conductor type	Solid bare copper
Jacket material	Low smoke flame retardant polyvinyl chloride (LSFRPVC)
Jacket diameter	6.6 ±0.5 mm
Installation temperature	0 to 50°C (32 to 122°F)
Ambient operating temperature	-20 to 60°C (-4 to 140°F)
Anti-crosstalk divider	Yes
Ripcord	Yes
Date rate	10/100/1000 Base-T

Standards

Electrical transmission:

ANSI/TIA-568-C.2 (2009)

ISO/IEC 11801 (Edition 2.2)

IEC 61156-5 (Edition 2.1)

Flame test:

NFPA 262 (CMP)

Material and construction:

UL 444

CSA 22.2 NO.214

EU Directive 2011/65/EU (RoHS2)

EU Directive 2006/95/EC (LVD)

Stay in Touch



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.