

Altas PT Ultra

4K Continuous Recording Battery Camera with ColorX

- 4K Continuous Recording
- 360° All-around Security Auto Tracking
- ColorX True Full Color Night Vision
- 20000mAh Long Battery Life



Specifications

| Video & Audio | |
|-----------------------|---|
| Image Sensor | 1/1.8" CMOS sensor |
| Video Resolution | 3840x2160 (8 megapixels) @15fps |
| Lens | f=4mm , fixed |
| Video Compression | H.264/H.265 |
| Field of View | Diagonal : 110° Horizontal: 90° Vertical: 50° |
| Infrared Night Vision | NO |
| Color Night Vision | YES |
| Frame Rate | Main/Sub stream: 10fps - 15fps |
| Audio | Two-way audio |
| Power | |

| | |
|---------------------------|--|
| Battery | 3.6V 20000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.) 72Wh(Power capacity) |
| Solar | Reolink Solar Panel 2 (6W) |
| Pan & Tilt | |
| PT Angle(Max.) | Pan: 355°, Tilt: 90° |
| Auto Tracking | YES |
| Bluetooth Standard | |
| Bluetooth Standard | Bluetooth V5.0 |
| Interface | |
| Power Port | USB Type-C Port (*Support USB-A to UsB-C cable only.) |
| SD Card Slot | Supports Max. 512GB microSD card |
| Reset Button | YES |
| Audio In/Out | Built-in microphone and speaker |
| Wi-Fi | |
| Wireless Standard | IEEE 802.11 a/b/g/n/ac/ax |
| Operating Frequency | 2.4GHz/5GHz |
| Wireless Security | WPA/WPA2/WPA3 |
| Software | |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Protocols & Standards | SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P |
| User Access | Max. 12 simultaneous streams (2 main & 10 sub streams) |
| Other Features | |
| Smart Alarm | PIR detection; motion detection; person detection; vehicle detection; animal detection |
| PIR Detecting Distance | Adjustable, up to 10m (33ft) |

| | |
|----------------------------|---|
| PIR Detecting Angle | 100° horizontal |
| Recording Modes | Motion recording, schedule recording, 24/4 recording |
| Time Lapse | YES |
| Smart Home Compatibility | Google Assistant |
| Home Hub Compatibility | YES |
| Cloud Storage | Supports Reolink Cloud (available in selected countries) |
| Working Environment | |
| Operating Temperature | -10°C~55°C (14°F~131°F) |
| Operating Humidity | 20% ~ 85% |
| Weatherproof | IP65 |
| Mechanical | |
| Dimensions | 178*151*102mm |
| Weight (Without Bracket) | 853g |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ . |

Gallery & Specs



1. Antenna
2. Ceiling Mounting Bracket
3. Spotlight
4. Lens
5. PIR Lens
6. Daylight Sensor
7. Microphone Hole
8. Indicator Light



1. Power Button
2. Type-C Interface
3. Speaker Hole
4. microSD Card Slot



www.reolink.com