

Voxicon O34QHDCE Ergonomic Monitor TCO ETHERNET



Product Overview

The Voxicon O34QHDCE is a 34-inch ultrawide curved monitor designed for professional-grade productivity and immersive visuals. Its 21:9 aspect ratio and 3440 x 1440 resolution provide extensive workspace, ideal for multitasking. With a high 165Hz refresh rate, USB-C power delivery, and integrated Ethernet, this model delivers seamless functionality in both office and studio environments.

Key Features

- 34" Ultrawide VA Curved Panel
- 3440 x 1440 UWQHD Resolution at 165Hz (via DP and USB-C)
- 165Hz Refresh Rate with FreeSync/G-Sync Compatibility
- HDR10, Flicker-Free, and Low Blue Light Technologies
- KVM Switch Support
- USB-C with 65W Power Delivery
- LAN (Ethernet) Port for Direct Network Access

Ergonomics & Design

- Tilt: -20° to +5°
- Swivel: -30° to $+30^{\circ}$
- Rotate: -5° to +5°
- Height Adjustment: 130mm
- 100x100mm VESA Mount
- Quick Release Support

Warranty & Support

All Voxicon monitors include a 3-year warranty covering manufacturer and material defects. Units eligible for warranty replacement are handled via a swap process, including DOA claims within 14 days of receipt. Returned products must include all accessories. Claims involving damage due to misuse or external factors such as lightning or water are not covered.

Warranty and Support Process

- 1. The customer contacts Dustin's customer service.
- 2. Dustin assesses whether the issue is covered by warranty and if it qualifies as a DOA (Dead on Arrival) or standard warranty case.
- 3. If the warranty applies, clear return and shipping instructions are sent to the customer.
- 4. The customer returns the product complete with all accessories.
- 5. A replacement (swap) unit is sent to the customer.

Contact Information

For warranty or support issues, contact Dustin customer service at: asiakaspalvelu@dustin.fi

Technical Specifications

Specification	Details
1	34"
Display Size	=
Panel Type	VA Curved
Resolution	3440 x 1440 @165Hz
Aspect Ratio	21:9
Brightness	500 cd/m ² (Typ), 450 cd/m ² (Min)
Contrast Ratio	4000:1
Response Time	5ms (panel), 4ms (OD)
Color Depth	16.7 Million Colors
Color Gamut	NTSC 72%
Viewing Angles	178° (H/V)
Curvature	1500R
Inputs	1 x HDMI 2.0, 2 x DP, 1 x USB-C (65W)
USB Ports	2 x USB 3.0-A, 1 x USB 3.0-B, 1 x USB 2.0
	(Upgrade only)
LAN	1 x Ethernet Port
Audio	1 x Headphone Out
Stand Adjustments	Tilt, Swivel, Rotate, Height
Power Input	DC 24V/7A
Power Consumption	≤168W (Working), ≤0.5W (Standby)
VESA Mount	100 x 100 mm
Dimensions (with stand)	811.8 x 565.4 x 240 mm
Weight	8.3 kg (Net), 11.5 kg (Gross)
Certifications	CE, CB, ERP, TCO 9.0