



Back-UPS Pro BR Series 900VA

Premium, uninterrupted backup power
for demanding electronics.

Schneider
Electric

se.com

Uninterrupted power when it matters most.

The new APC Back-UPS Pro BR Series offers guaranteed power protection for high-performance computer systems, routers/modems, external storage devices, game consoles, and other electronics in your home or business. Our UPS comes with a variety of advanced features that help you protect your critical devices and stay connected during outages.



Premium power protection

4 battery + surge outlets

Safeguards your essential devices from spikes and surges without draining backup capacity.

Automatic voltage regulation (AVR)

Smooths voltage fluctuations from mains power supply without switching to battery, safeguarding equipment against a wider range of power instabilities.

70% longer runtime*

Than leading competitors. Provides a great buffer during outages, crucial for gracefully shutting down equipment and preventing data loss.

Built for performance and longevity

User replaceable batteries

Saves you time and money by allowing easy, on-site battery swaps, extending the UPS's lifespan and minimizing downtime.

Energy efficient design

15% lower carbon emission, 98% energy efficiency, and fully recyclable, low-waste packaging reduces environmental impact and long-term energy costs.

3-year warranty**

Plus a €150,000 lifetime connected equipment protection policy, and free technical support exclusive for European community countries only



*Based on runtime data of comparable models in 2026.

**Only applicable to EU countries.

Smart & user-friendly features

LCD display

Quickly check your UPS and power status with easy-to-understand visual indicators.

USB charging ports

2 USB-C charging ports to charge critical mobile devices directly from the UPS, freeing your outlets and ensuring communication tools stay powered during outages.

Compact, sleek design

New, sleek look and feel suitable for modern homes and workspaces.




Manage your UPS for peace of mind

The APC Back-UPS Pro BR series is compatible with **PowerChute Serial Shutdown**, a UPS management software that enables graceful system shutdown and energy management capabilities.

PowerChute Serial Shutdown provides:

- UPS monitoring and management
- Unattended, graceful shutdown during power events
- Secure web user interface (UI) access
- Energy and CO2 emissions reporting
- Configurable energy cost
- Multiple languages support
- Multiple operating system support



How much runtime will this Back-UPS provide?*

Internet modem + Wifi router (40W)	105 mins
Laptop + Internet modem + Wifi router (79W)	50 mins
Mid-range PC + 20" LED display + Internet modem + Wifi router (119W)	30 mins
Performance PC with 24" LED monitor, External power speakers + Internet modem and router (240W)	11.7 mins
43" LED television + game console system (335W)	6.2 mins

*Runtime and energy savings will vary according to device(s), usage, and power settings.

Technical Specs

BR900G2-FR

Output

Power Rating	900VA / 540W
Nominal Output Voltage	230V
Output Voltage (On Battery)	230+/-10% @ 100% R load
Output Frequency (Hz)	50 or 60 Hz +/- 1Hz autosensing
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Surge Energy Rating	1080 Joules
Output Connections	4* French CEE 7/5

Input

Nominal Input Voltage	230 Vac
Input Connections	French
USB charging ports	2* USB Type-C (5V, 15W)
Input Cord Length	5 ft
Input Frequency	50-60 Hz +/- 3Hz

Batteries & Runtime

Battery Type	Lead-acid battery 12V-9AH
Typical Backup Time at ½ Load	9 mins
Typical Backup Time at Full Load	2.5 mins
Typical Recharge Time	8 hours to 90% capacity
Runtime For Typical Devices	Please see runtime table on Page 3.
User Replaceable Battery	Yes (APCRBC164 sold separately)

Communications & Management

LCD Screen	Yes
Data Line Protection	1GB
Software	PowerChute Serial Shutdown via USB port

Physical

Dimensions (HxWxD)	<190x91x310 mm
Weight	7.5 kg

Environmental

Ambient Operating Temperature	0~40 °C
Operating Relative Humidity	0-95%, non-condensing
Operating Elevation	0 ~ 3000 meters
Storage Temperature	-15~40 °C
Storage Relative Humidity	0-95%, non-condensing

Conformance

Approvals	CE, CB IEC 62040-1 2nd edition
Standard Warranty	36 months for UPS, 12 months for Battery (only applicable to EU, UK, and Ireland)
RoHS Compliant	Yes

Advancing Energy Tech

se.com

Schneider Electric

One Boston Place
Floor 27
Boston, MA 02108
United States
www.apc.com

May 2026

©2026 Schneider Electric. All Rights Reserved.
Schneider Electric is a trademark and the property of Schneider Electric SE, its subsidiaries, and affiliated companies.