

Product datasheet

Specifications



APC Back-UPS PRO 650VA/
400W,6 IEC outlets, LCD
interface, USB Charging
ports,Tower, 230V

BR650G2I

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated power in W	400 W
rated power in VA	650 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 IEC 60309
output connection type	6 IEC 60320 C13 surge
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS
USB Charging Port	USB type C + C

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

UPS connectivity	USB port
Battery type	Lead-acid internal included
Mounting mode	Tower

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery charger power	20 W rated
Battery power in VAh	108 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	190 mm
Width	91 mm
Depth	310 mm
Net weight	6.4 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	IEC 60309
Input voltage limits	176...294 V
Maximum input current	10 A

Output

Maximum configurable power in W	400 W
Output frequency	47...63 Hz +/- 0.1 % for 50 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Output voltage tolerance	+/- 5% static and 100% load step
Maximum output current	10 A
Maximum configurable power in VA	650 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 150000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %

Acoustic level	45 dBA
Heat dissipation	77.1 Btu/h

Communications & Management

Control panel	LED Status display with on line : on battery : replace battery and overload indicators LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Control panel	LED status display with on line : on battery : replace battery and building wiring fault

Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.0 cm
Package 1 Width	16.3 cm
Package 1 Length	39.5 cm
Package 1 Weight	7.7 kg
SCC14	10731304792076

Contractual warranty

Warranty (in months)	36 UPS 12 Battery
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	147 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	55 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	68 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	16 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	43
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No

Image of product / Alternate images

Alternative



