



Prokord DP2HDMI2MM-2m-B

Data sheet

Core Specs

Cable length	2 m
Connector 1	DisplayPort
Connector 2	HDMI
Product colour	Black
HDMI version	1.4
DisplayPort version	1.2

Summary

- ✓ Converts DisplayPort to HDMI for easy connection to TVs and projectors
- ✓ Gold plated contacts ensure reliable signal transfer and low corrosion
- ✓ Supports up to 4Kx2K at 30Hz, suitable for presentations and video
- ✓ Shielded PVC jacket with tinned copper cores reduces interference
- ✓ Compatible with HDCP and DisplayPort 1.2, supports HBR2 data rates

Product description

Why choose this DisplayPort to HDMI cable?

Prokord Displayport to HDMI 2m Black - Gold plated provides a reliable way to connect a DisplayPort-equipped computer to an HDMI monitor or projector. It supports HDCP-protected content and up to 4K resolution at 30Hz, while gold-plated contacts and braided shielding improve signal stability for meeting rooms, workstations, and AV setups.

Displayport to HDMI 2m Black - Gold plated in short:

- Connects DisplayPort sources to HDMI displays, suitable for monitors, projectors, and conference-room AV systems.
- Supports up to 4Kx2K resolution at 30Hz with 12-bit colour depth, adequate for presentations and standard 4K video.
- Gold-plated contacts and aluminium-foil plus braid shielding help maintain a reliable connection and resist corrosion.
- 2 m length, black PVC jacket and straight male-to-male connectors for neat, durable installations.
- Note: HDMI 1.4 and DisplayPort 1.2 limit 4K output to 30Hz, consider this if you require 60Hz for gaming or high-frame-rate video.

Product details

The Prokord Displayport to HDMI 2m Black - Gold plated carries video from a DisplayPort 1.2 output to an HDMI 1.4 input, with HBR2 and HDCP support for protected content. Tinned copper conductors and a 7.3 mm cable diameter with aluminium-foil plus braid shielding help reduce interference in office environments. The PVC jacket and straight, gold-plated male connectors provide a durable, low-maintenance connection for typical desktop and AV installations.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	2 m
Connector 1	DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	HDMI
Connector 2 gender	Male
Connector 2 form factor	Straight
Product colour	Black

HDMI version	1.4
DisplayPort version	1.2
Connector contacts plating	Gold plated
HDCP	Yes
Refresh rate at maximum resolution	30 Hz
Colour depth	12 bit
Maximum resolution	4Kx2K pixels
High Dynamic Range (HDR) supported	No
HBR2 support	Yes
Maximum refresh rate	30 Hz
Cable material	Tinned copper
Cable shielding	Aluminium foil + braid
Jacket material	PVC
AWG wire size	28AWG
Data transfer rate	3 Gbit/s

Weight & dimensions

Cable diameter	7.3 mm
Weight	148 g

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Other features

Supported resolutions	Up to 4Kx2K
Material	Tinned copper

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------