



Prokord DP2HDMI2MM-3m-W

Data sheet

Core Specs

Cable length	3 m
Connector 1	DisplayPort
Connector 2	HDMI
Product colour	White
HDMI version	1.4
DisplayPort version	1.2

Summary

- ✓ Connect DisplayPort sources to HDMI displays, supports up to 4K@30Hz
- ✓ Gold-plated contacts resist corrosion, maintain a steady signal
- ✓ Aluminium foil and braid shielding reduces interference in busy setups
- ✓ Flexible 3m length and 7.3mm PVC jacket ease routing in office setups
- ✓ DP1.2 and HDMI1.4 with HDCP support ensure compatible, protected playback

Product description

Why choose this Displayport to HDMI cable?

Prokord Displayport to HDMI 3m White - Gold plated gives a dependable way to link DisplayPort sources to HDMI displays. It supports DP 1.2 and HDMI 1.4 with HDCP for protected content, and carries up to 4Kx2K at 30Hz. The gold-plated contacts and dual shielding improve durability and signal stability in office and AV setups.

Prokord Displayport to HDMI 3m White - Gold plated in short:

- Converts a DisplayPort output to an HDMI display, useful for presentations, meeting rooms, and AV installations.
- Supports up to 4Kx2K at 30Hz, suitable for digital signage and high-resolution slides or video.
- Gold-plated contacts and aluminium foil plus braid shielding for reliable connections and reduced interference.
- 3 m length, flexible 7.3 mm diameter and lightweight design make routing and installation easier.
- Consider that the cable is limited to 30Hz at maximum resolution and does not support HDR, so it is not aimed at high-refresh gaming setups.

Product details

This Prokord cable is a straight male-to-male DisplayPort to HDMI lead that carries DP 1.2 signals to HDMI 1.4 displays while maintaining HDCP compatibility. The tinned copper conductors and 28AWG wiring provide steady transmission over the 3 metre run, and the PVC jacket protects the cable in everyday office and AV use. It is a practical choice when you need a simple, durable link between modern graphics sources and HDMI screens.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	3 m
Connector 1	DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	HDMI
Connector 2 gender	Male
Connector 2 form factor	Straight
Product colour	White
HDMI version	1.4
DisplayPort version	1.2

Connector contacts plating	Gold plated
HDCP	Yes
Refresh rate at maximum resolution	30 Hz
Colour depth	12 bit
Maximum resolution	4Kx2K pixels
High Dynamic Range (HDR) supported	No
HBR2 support	Yes
Maximum refresh rate	30 Hz
Cable material	Tinned copper
Cable shielding	Aluminium foil + braid
Jacket material	PVC
AWG wire size	28AWG
Data transfer rate	3 Gbit/s

Weight & dimensions

Cable diameter	7.3 mm
Weight	223 g

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Other features

Connector(s)	DisplayPort, HDMI
Supported resolutions	Up to 4Kx2K
Material	Tinned copper

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------