



Cable Displayport Ext 0.5m0.5m DisplayPort DisplayPort Black

Data sheet

Summary

- ✓ 0.5 m DisplayPort 1.2 male-to-female extension, ideal for short reach adjustments and hard-to-access ports.
- ✓ Supports up to 4Kx2K at 60Hz and MST, suitable for single high-resolution displays and chained monitors.
- ✓ Gold-plated contacts, aluminium foil plus braid shielding, and tinned copper conductors for stable connections and reduced interference.
- ✓ TPE with LSZH jacket and 6 mm diameter, designed for safer use in enclosed environments.
- ✓ Note: HDR is not supported; verify device compatibility for full feature support.

Product description

Why choose this cable?

Prokord Cable Displayport Ext 0.5m gives you a short, reliable extension for tight desktop or rack installations. It supports DisplayPort 1.2 for up to 4Kx2K at 60Hz and enables Multi-Stream Transport for daisy-chaining. The LSZH jacket and robust shielding help maintain signal integrity and provide a safer cable option in confined spaces.

Cable Displayport Ext 0.5m in short:

- 0.5 m DisplayPort 1.2 male-to-female extension, ideal for short reach adjustments and hard-to-access ports.
- Supports up to 4Kx2K at 60Hz and MST, suitable for single high-resolution displays and chained monitors.
- Gold-plated contacts, aluminium foil plus braid shielding, and tinned copper conductors for stable connections and reduced interference.
- TPE with LSZH jacket and 6 mm diameter, designed for safer use in enclosed environments.
- Note: HDR is not supported; verify device compatibility for full feature support.

Cable Displayport Ext 0.5m

Prokord Cable Displayport Ext 0.5m is a straightforward extension cable that lets you increase reach without replacing existing DisplayPort leads. It supports HDCP protected content and provides a data transfer rate of 5.4 Gbit/s to carry video signals up to 4K at 60Hz. The straight male and female connectors, gold plating, and 30AWG conductors combine with foil and braid shielding to reduce signal loss and interference, while the low-smoke, zero-halogen jacket improves safety where ventilation is limited.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	0.5 m
Connector 1	DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	DisplayPort
Connector 2 gender	Female
Connector 2 form factor	Straight
Product colour	Black
Maximum resolution	4Kx2K pixels

Connector contacts plating	Gold plated
DisplayPort version	1.2
Cable material	Tinned copper
Maximum refresh rate	60 Hz
HDCP	Yes
Data transfer rate	5.4 Gbit/s
Cable shielding	Aluminium foil + braid
Jacket material	LSZH, TPE
AWG wire size	30AWG
High Dynamic Range (HDR) supported	No
Multi-Stream Transport (MST)	Yes

Packaging data

Weight	51 g
Cable diameter	6 mm

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------