



Prokord DP-MDP 0043

Data sheet

Core Specs

Cable length	2 m
Connector 1	DisplayPort
Connector 2	Mini DisplayPort
Product colour	White
DisplayPort version	1.2

Summary

- ✓ Straight male-to-male DisplayPort to Mini DisplayPort, 2m white
- ✓ DisplayPort 1.2 with HBR3 delivers 4Kx2K at 60Hz
- ✓ MST and HDCP support enable multi-display and protected content
- ✓ Gold-plated contacts and foil plus braid shielding reduce signal loss
- ✓ Slim 4.8mm PVC jacket and tinned copper conductors stay flexible

Product description

Why choose this DisplayPort to Mini DisplayPort cable?

Prokord Cable Displayport - Mini-Displayport 2m White gives a dependable, high-resolution link between devices with DisplayPort and Mini DisplayPort ports. It supports DisplayPort 1.2 and HBR3 for 4Kx2K at 60Hz, making it suitable for external monitors and docking stations. Gold-plated contacts and aluminium foil plus braid shielding help maintain signal integrity in everyday office and meeting-room use.

Cable Displayport - Mini-Displayport 2m White in short:

- 2 m white cable with a flexible PVC jacket, useful for desk setups and short runs to monitors or docking stations.
- Supports DisplayPort 1.2, HBR3, MST and HDCP for 4Kx2K at 60Hz, suitable for high-resolution displays and multi-monitor setups.
- Gold-plated connector contacts, tinned copper conductor and aluminium foil plus braid shielding reduce interference and improve longevity.
- Straight male DisplayPort to straight male Mini DisplayPort connectors, compatible with laptops, docking stations and monitors that use these ports.
- Note: High Dynamic Range (HDR) is not supported, so HDR content will not be passed through this cable.

Key features

The cable connects DisplayPort sources to Mini DisplayPort inputs for video transmission up to 4Kx2K at 60Hz. Its slim 4.8 mm diameter and 32AWG conductors keep the cable flexible while the PVC jacket protects against wear. Gold-plated contacts and robust shielding improve signal stability in office and meeting-room environments. The male-to-male, straight connector design makes it easy to plug into laptops, docking stations and monitors without adapters.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	2 m
Connector 1	DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	Mini DisplayPort
Connector 2 gender	Male
Connector 2 form factor	Straight

Product colour	White
Maximum resolution	4Kx2K pixels
Connector contacts plating	Gold plated
DisplayPort version	1.2
Cable material	Tinned copper
Maximum refresh rate	60 Hz
HDCP	Yes
Data transfer rate	5.4 Gbit/s
Cable shielding	Aluminium foil + braid
Jacket material	PVC
AWG wire size	32AWG
High Dynamic Range (HDR) supported	No
Multi-Stream Transport (MST)	Yes
HBR3 support	Yes

Packaging data

Cable diameter	4.8 mm
Weight	89 g

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------