



Cable SATA/SAS Internal Straight 0.3m Red

Data sheet

Summary

- ✓ Compact 0.3m length keeps internal layouts neat and reduces cable clutter.
- ✓ Supports SATA III data rates up to 6Gbit/s, suitable for SSDs and HDDs.
- ✓ Straight 7-pin SATA connectors on both ends for secure internal connections.
- ✓ Red flat cable with black connectors for easy identification inside cases and racks.
- ✓ Note: designed for internal use only, not for extended external connections.

Product description

Why choose this cable?

Prokord Cable SATA/SAS Internal Straight 0.3m Red provides a reliable internal connection for SATA devices, supporting SATA III transfers up to 6Gbit/s. Its short, flat design keeps internal wiring tidy and improves airflow. Straight 7-pin connectors fit securely in compact builds, making installation straightforward and maintenance easier.

Prokord Cable SATA/SAS Internal Straight 0.3m Red in short:

- Compact 0.3m length keeps internal layouts neat and reduces cable clutter.
- Supports SATA III data rates up to 6Gbit/s, suitable for SSDs and HDDs.
- Straight 7-pin SATA connectors on both ends for secure internal connections.
- Red flat cable with black connectors for easy identification inside cases and racks.
- Note: designed for internal use only, not for extended external connections.

Usage

The Prokord Cable SATA/SAS Internal Straight 0.3m Red connects SATA storage devices to host controllers in desktops and servers. Male/female straight connectors provide a firm fit on drive bays and motherboard headers. The flat, flexible cable routes neatly behind drive cages and is sold as a single unit, making it well suited to small form factor systems and short internal runs where a tidy, dependable link is required.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	0.3 m
Cable type	SATA III
Connector 1	SATA
Connector 2	SATA
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector gender	Male/Female
Product colour	Black, Red
Maximum data transfer rate	6 Gbit/s

Packaging data

Quantity per pack

1 pc(s)

Logistics data

Harmonized System (HS) code

84733080