



# Prokord USB-0024

Data sheet

## Core Specs

|                          |         |
|--------------------------|---------|
| Cable length             | 2 m     |
| Connector 1              | USB-A   |
| Connector 2              | USB-A   |
| Product colour           | Grey    |
| USB version              | USB 2.0 |
| USB Power Delivery up to | 2.5 W   |

## Summary

- ✓ 2m length gives flexible placement and tidy cable routing
- ✓ USB 2.0 at 480Mbit/s for dependable everyday data transfers
- ✓ LSZH jacket reduces smoke and harmful emissions in enclosed areas
- ✓ Nickel-plated contacts keep connections stable and resist corrosion
- ✓ Male-to-male USB-A plugs link hosts and peripherals without adapters

# Product description

## Why choose this cable?

Prokord Cable USB 2.0 Type A-A Male-Male 2m Grey gives you a dependable, everyday connection for linking USB-A devices and transferring files. It balances reach and flexibility with a 2 metre length and a round LSZH jacket for reduced smoke and emissions in enclosed spaces. The cable is built for stable, routine use where consistent data transfer and safety are priorities.

## Prokord Cable USB 2.0 Type A-A Male-Male 2m Grey in short:

- 2 metre USB-A to USB-A cable for connecting peripherals, docking stations, and device-to-device transfers
- USB 2.0 performance with up to 480 Mbit/s for typical file sync and peripheral communication
- Low smoke zero halogen (LSZH) jacket, suitable for offices and installations with stricter safety requirements
- Straight, nickel-plated connectors for reliable contact and corrosion resistance
- Consideration: not intended for high-power charging, supports standard USB 2.0 power up to 2.5 W

## Practical use

The Prokord Cable USB 2.0 Type A-A Male-Male 2m Grey provides a simple way to connect compatible devices where USB-A endpoints are required. It works well for data exchange between PCs and peripherals, connecting legacy equipment, and temporary device linking during maintenance or setup. The LSZH jacket helps reduce harmful emissions in confined environments, and the straight, nickel-plated connector ends keep connections stable during regular handling.

# Technical Specification Matrix

## Header

|              |         |
|--------------|---------|
| Manufacturer | Prokord |
|--------------|---------|

## Features

|                         |            |
|-------------------------|------------|
| Max data transfer rate  | 480 Mbit/s |
| Cable length            | 2 m        |
| USB version             | USB 2.0    |
| Connector 1             | USB-A      |
| Connector 1 gender      | Male       |
| Connector 1 form factor | Straight   |
| Connector 2             | USB-A      |
| Connector 2 gender      | Male       |
| Connector 2 form factor | Straight   |

|                                       |                               |
|---------------------------------------|-------------------------------|
| USB Power Delivery                    | No                            |
| USB Power Delivery up to              | 2.5 W                         |
| Product colour                        | Grey                          |
| Cable type                            | Round cable                   |
| Cable jacket material                 | Low smoke zero halogen (LSZH) |
| Connector contacts plating            | Nickel plating                |
| Reversible connectors                 | No                            |
| USB Type-C DisplayPort Alternate Mode | No                            |

**Power**

|               |     |
|---------------|-----|
| Input voltage | 5 V |
|---------------|-----|

**Packaging data**

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

**Logistics data**

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733080 |
|-----------------------------|----------|