



# Prokord USB-0030

Data sheet

## Core Specs

|                          |                   |
|--------------------------|-------------------|
| Cable length             | <b>2 m</b>        |
| Connector 1              | <b>USB-A</b>      |
| Connector 2              | <b>Mini USB-B</b> |
| Product colour           | <b>Black</b>      |
| USB version              | <b>USB 2.0</b>    |
| USB Power Delivery up to | <b>2.5 W</b>      |

## Summary

- ✓ 2m length gives flexible reach for desks, workstations and equipment
- ✓ USB 2.0 at 480Mbit/s handles everyday file transfers reliably
- ✓ Low smoke zero halogen jacket reduces toxic fumes, enhances safety
- ✓ Nickel plated contacts resist corrosion for consistent connections
- ✓ Supplies up to 2.5W, suitable for low-power peripherals

# Product description

## Why choose this cable?

Prokord Cable USB 2.0 Type A-B Mini Male-Male 2m Black gives reliable, everyday connectivity between USB-A hosts and devices with a mini USB-B port. Its 2 meter length and straight connectors make device placement flexible, while the low smoke zero halogen jacket improves safety and durability in shared workspaces.

## Cable USB 2.0 Type A-B Mini Male-Male 2m Black in short:

- Connects standard USB-A ports to mini USB-B devices, suitable for older cameras, GPS units, and external peripherals.
- 2 meter length allows flexible device placement without clutter.
- Low smoke zero halogen (LSZH) jacket for improved safety in offices and public areas.
- Nickel-plated contacts and straight connectors for secure, corrosion-resistant connections.
- Not suitable when higher USB speeds or greater charging power are required.

## Product details

This Prokord cable supports USB 2.0 data rates, making it suitable for file transfers, device sync and routine backups. It carries low-power charging for compatible devices and features a round, flexible design that routes easily through workspaces. The LSZH jacket reduces toxic smoke and halogen in case of fire, and the nickel-plated contacts help maintain a reliable connection over repeated use.

# Technical Specification Matrix

## Header

|              |         |
|--------------|---------|
| Manufacturer | Prokord |
|--------------|---------|

## Features

|                          |            |
|--------------------------|------------|
| Max data transfer rate   | 480 Mbit/s |
| Cable length             | 2 m        |
| USB version              | USB 2.0    |
| Connector 1              | USB-A      |
| Connector 1 gender       | Male       |
| Connector 1 form factor  | Straight   |
| Connector 2              | Mini USB-B |
| Connector 2 gender       | Male       |
| Connector 2 form factor  | Straight   |
| USB Power Delivery up to | 2.5 W      |

|                            |                               |
|----------------------------|-------------------------------|
| Product colour             | Black                         |
| Cable type                 | Round cable                   |
| Cable jacket material      | Low smoke zero halogen (LSZH) |
| Connector contacts plating | Nickel plating                |
| Reversible connectors      | No                            |

Power

|                     |       |
|---------------------|-------|
| Input current (max) | 0.5 A |
|---------------------|-------|

Packaging data

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

Logistics data

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733080 |
|-----------------------------|----------|