



Prokord UTP-0062

Data sheet

Core Specs

Connector 1	RJ-45
Connector 2	RJ-45
Cable standard	Cat 6
Cable shielding	U/UTP (UTP)
Cable length	20 m
Jacket material	LSZH

Summary

- ✓ Cat6 performance up to 10Gbps at 250MHz for high-speed links
- ✓ LSZH jacket lowers toxic smoke, ideal for offices and comms rooms
- ✓ PoE compatible, powers devices and carries data on a single cable
- ✓ 20m white 26AWG copper cable with RJ45 plug-and-play connectors

Product description

Why choose this Ethernet cable?

Prokord TP-Cable UTP CAT.6 Unshielded Lszh RJ45 20m White provides a dependable link for office and data-room cabling, combining high data throughput with safe, low-emission jacketing. It helps reduce cable runs and additional patch points, supports power-over-Ethernet to simplify device installation, and offers a neutral white finish that fits visible installations.

TP-Cable UTP CAT.6 Unshielded Lszh RJ45 20m White in short:

- Cat 6 U/UTP cable for reliable network connections and higher bandwidth needs, rated to 250 MHz and up to 10000Mbit/s.
- LSZH jacket reduces smoke and halogen release, suitable for enclosed or public areas where safety is a priority.
- Ready-to-use RJ-45 male-to-male ends, ideal for connecting switches, routers, patch panels, access points, and networked devices.
- Supports Power over Ethernet, so you can power compatible access points and VoIP phones without separate power lines.
- Note the fixed 20 m length, so confirm it matches your planned cable route before purchase.

Product details

TP-Cable UTP CAT.6 Unshielded Lszh RJ45 20m White is a single-pack, 20-metre patch cable with 26 AWG copper conductors for consistent signal quality. The unshielded design is suited to typical office and data-room environments. Flexible white jacket and molded connector boots make routing and panel connections straightforward, while PoE compatibility reduces installation complexity for powered devices.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	20 m
Cable standard	Cat 6
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 1 gender	Male
Connector 2	RJ-45
Connector 2 gender	Male

Product colour	White
Jacket material	LSZH
Conductor material	Copper
AWG wire size	26
Data transfer rate	10000 Mbit/s
Frequency	250 MHz
Power over Ethernet (PoE)	Yes

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------