



Prokord UTP-0077

Data sheet

Core Specs

Connector 1	RJ-45
Connector 2	RJ-45
Cable standard	Cat 6
Cable shielding	U/UTP (UTP)
Cable length	3 m
Jacket material	LSZH

Summary

- ✓ Cat 6 performance, 250 MHz supports high-speed LAN and short 10Gb links
- ✓ LSZH jacket reduces smoke and toxic gases in enclosed spaces
- ✓ PoE compatible, powers APs, cameras and VoIP phones without extra wiring
- ✓ Molded RJ45 plugs and 3m length simplify neat desktop and rack connections
- ✓ U/UTP unshielded, 26 AWG keeps cable flexible and easy to route

Product description

Why choose this network cable?

Prokord TP-Cable UTP CAT.6 Unshielded Lszh RJ45 3m Black delivers reliable, high-speed connectivity for desktop and patch-panel connections. It supports Power over Ethernet so you can power devices without extra wiring. The LSZH jacket reduces smoke and toxic gases in confined spaces. The 3 meter length and molded RJ-45 plugs make installation simple and tidy.

TP-Cable UTP CAT.6 Unshielded Lszh RJ45 3m Black in short:

- Cat 6 performance for fast LAN links, rated to 250 MHz and up to 10,000 Mbit/s where infrastructure allows.
- Low smoke zero halogen (LSZH) jacket for safer use in offices, public buildings, and confined spaces.
- PoE compatible, suitable for powering access points, cameras, and VoIP phones.
- Unshielded U/UTP design with 26 AWG conductors, flexible and easy to route in cable trays.
- Note: unshielded construction is not intended for environments with high electromagnetic interference.

Product details

This Prokord cable has male RJ-45 connectors on both ends for plug-and-play use with switches, routers, patch panels, and network devices. The molded RJ-45 connectors with strain relief give a secure fit and reduce wear during installation. The Cat 6 standard and 250 MHz frequency support modern Ethernet applications and short-run 10 Gbit/s links when supported by the rest of your network. The LSZH jacket lowers fire-related risks, and the 3 meter length is convenient for connecting wall outlets to workstations or linking equipment in racks. Each pack contains one cable.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	3 m
Cable standard	Cat 6
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 1 gender	Male
Connector 2	RJ-45
Connector 2 gender	Male
Product colour	Black
Jacket material	LSZH

Data transfer rate	10000 Mbit/s
AWG wire size	26
Frequency	250 MHz
Power over Ethernet (PoE)	Yes

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------