



Smart Power Station 6 X USBBlack

Data sheet

Summary

- ✓ Six USB 2.0 ports let you charge multiple smartphones, tablets, and accessories simultaneously.
- ✓ Up to 2.4A output per port for consistent charging across a range of USB devices.
- ✓ Universal compatibility and 100–240V input, suitable for use with international AC supplies.
- ✓ Built-in protection for overheating, short circuit, and over-voltage to protect connected devices.
- ✓ Indoor use only; requires a standard AC outlet and is supplied with an AC cable.

Product description

Why choose this charger?

Cirafon Smart Power Station 6 X USB centralizes charging for up to six USB devices, reducing clutter and freeing wall outlets in shared workspaces. It delivers steady per-port current for reliable device charging, includes an AC cable for quick setup, and keeps devices protected with built-in safeguards against overheating, short circuit, and over-voltage.

Smart Power Station 6 X USB in short:

- Six USB 2.0 ports let you charge multiple smartphones, tablets, and accessories simultaneously.
- Up to 2.4A output per port for consistent charging across a range of USB devices.
- Universal compatibility and 100–240V input, suitable for use with international AC supplies.
- Built-in protection for overheating, short circuit, and over-voltage to protect connected devices.
- Indoor use only; requires a standard AC outlet and is supplied with an AC cable.

Product details

Smart Power Station 6 X USB charges several devices at once while keeping desks tidy. The unit connects to standard AC power and supports a wide input voltage range, making it adaptable for different locations. A battery-level LED provides visual status, and the compact black housing fits easily on work surfaces.

Technical Specification Matrix

Header

Manufacturer	Cirafon
--------------	---------

Performance

Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
USB 2.0 ports quantity	6
Power protection features	Over voltage, Overheating, Short circuit

Design

Product colour	Black
LED indicators	Battery level

Power

Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Output current (5V)	2.4 A

Packaging data

Cables included	AC
-----------------	----

Logistics data

Harmonized System (HS) code	85044090
-----------------------------	----------