



HDMI 2.0 3X1 Switch

Data sheet

Summary

- ✓ Route three HDMI sources to one display with manual, IR remote, and intelligent switching.
- ✓ Supports up to 4K*2K at 60Hz, full 3D and common compressed audio formats including DTS Digital and Dolby Digital.
- ✓ EDID bypass and HDCP pass through improve compatibility between sources and displays.
- ✓ Compact metal housing with front LED indicators, select knob, IR receiver and external AC adapter included.
- ✓ Consideration: ensure your display and source devices support 4K@60 and HDCP when using high-resolution content.

Product description

Why choose this HDMI switch?

Prokord HDMI 2.0 3X1 Switch helps you connect three HDMI sources to a single display while keeping switching simple and reliable. The metal housing and compact size make it easy to mount or tuck away. It supports 4K@60Hz, full 3D and common surround formats, so you can consolidate AV sources without sacrificing picture or audio quality.

Prokord HDMI 2.0 3X1 Switch in short:

- Route three HDMI sources to one display with manual, IR remote, and intelligent switching.
- Supports up to 4K*2K at 60Hz, full 3D and common compressed audio formats including DTS Digital and Dolby Digital.
- EDID bypass and HDCP pass through improve compatibility between sources and displays.
- Compact metal housing with front LED indicators, select knob, IR receiver and external AC adapter included.
- Consideration: ensure your display and source devices support 4K@60 and HDCP when using high-resolution content.

Product details

Prokord HDMI 2.0 3X1 Switch lets you switch between three HDMI inputs using the front select knob, the supplied remote, or automatic input sensing. LED indicators and an IR receiver on the front panel make operation clear and convenient. The unit supports HDCP pass through and EDID bypass to help maintain correct audio and video handshake, and it passes common compressed audio formats for home and meeting-room setups. The metal casing is compact and lightweight, and the switch is powered via the included AC adapter and DC-in jack for stable operation.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Ports & interfaces

Video port type	HDMI
HDMI version	2.0
HDMI ports quantity	4
HDMI in	3
Number of HDMI outputs	1
DC-in jack	Yes

Features

Material	Metal
Product colour	Black
Maximum refresh rate	60 Hz
Bandwidth	600, 6 MHz
Maximum resolution	4096 x 2160 pixels
Supported video modes	1080i, 1080p, 2160p, 480i, 480p, 576i, 576p, 720p
LED indicators	Yes
3D	Yes

Packaging content

AC adapter included	Yes
---------------------	-----

Power

Power consumption (max)	1.72 W
-------------------------	--------

Weight & dimensions

Width	51 mm
Depth	80 mm
Height	20 mm
Weight	109.3 g

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	10 - 85 °C
Operating relative humidity (H-H)	-10 - 80 %
Storage relative humidity (H-H)	5 - 90 %