



Video Adapter Premium Minidp-HDMI0.42m Mini DisplayPort HDMI Aluminium

Data sheet

Summary

- ✓ Connects Mini DisplayPort sources to HDMI displays, ideal for laptops to monitors, projectors, or TVs.
- ✓ Supports 4K video at 60Hz and common video modes like 1440p, suitable for presentations and media playback.
- ✓ Active conversion with PS176 chipset helps maintain stable video output across different devices.
- ✓ Aluminium housing, nickel-plated contacts, and a short 0.42 m cable for a neat, durable connection.
- ✓ Consider that this adapter is designed for single-link connections and not for chaining multiple adapters in large AV installations.

Product description

Why choose this video adapter?

Prokord Video Adapter Premium Minidp-HDMI gives you a compact, plug-and-play way to connect Mini DisplayPort devices to HDMI displays. It supports up to 3840 x 2160 pixels at 60Hz and uses an active converter for reliable signal handling. The aluminium housing and short cable keep your desk tidy while reducing connection issues during meetings or presentations.

Video Adapter Premium Minidp-HDMI in short:

- Connects Mini DisplayPort sources to HDMI displays, ideal for laptops to monitors, projectors, or TVs.
- Supports 4K video at 60Hz and common video modes like 1440p, suitable for presentations and media playback.
- Active conversion with PS176 chipset helps maintain stable video output across different devices.
- Aluminium housing, nickel-plated contacts, and a short 0.42 m cable for a neat, durable connection.
- Consider that this adapter is designed for single-link connections and not for chaining multiple adapters in large AV installations.

Product details

The Prokord Video Adapter Premium Minidp-HDMI has a male Mini DisplayPort plug and a female HDMI socket, so you can quickly extend or mirror screens without installing drivers. The cable features a PVC jacket and a straight form factor on both ends, and the aluminium housing matches modern workspaces. Plug-and-play setup makes it suitable for meeting rooms, classrooms, and everyday desk use where reliable video output matters.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	0.42 m
Connector 1	Mini DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	HDMI
Connector 2 gender	Female
Connector 2 form factor	Straight
Product colour	Aluminium

Connector contacts plating	Nickel
Refresh rate at maximum resolution	60 Hz
Maximum resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Supported video modes	1440p, 2160p
Jacket material	PVC
Plug and Play	Yes
Data transfer rate	21.6 Gbit/s
Chipset	PS176(C0)
Converter type	Active

Weight & dimensions

Weight	20 g
--------	------

Operational conditions

Operating temperature (T-T)	0~45 °C
Storage temperature (T-T)	-10~70 °C
Operating relative humidity (H-H)	10~85 %
Storage relative humidity (H-H)	5~90 %

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Other features

Material	PVC
----------	-----

Packaging data

Quantity per pack	1 pc(s)
Package weight	20 g
Package width	160 mm
Package depth	0.1 mm
Package height	208 mm