



Prokord MDP-MDP2B

Data sheet

Core Specs

Cable length	2 m
Connector 1	Mini DisplayPort
Connector 2	Mini DisplayPort
Product colour	Black
DisplayPort version	1.2

Summary

- ✓ Delivers stable 4K@60Hz video for clear presentations and editing
- ✓ 2m length provides flexible placement without adapters
- ✓ Gold plated contacts and tinned copper conductors ensure stable signals
- ✓ Aluminium foil and braid shielding reduces interference
- ✓ Supports MST and HDCP so you can run multi displays and secure content

Product description

Why choose this Mini DisplayPort cable?

Prokord Cable Mini Displayport - Mini-Displayport 2.0m provides dependable high-definition connectivity for Mini DisplayPort devices. The 2 m length and straight gold plated male connectors make it easy to link laptops, docking stations, or monitors. Robust TPE jacketing and aluminium foil plus braid shielding reduce interference and improve long-term reliability, while support for DisplayPort 1.2 keeps visuals clear at up to 4K at 60Hz.

Cable Mini Displayport - Mini-Displayport 2.0m in short:

- 2 m Mini DisplayPort male-to-male cable, suitable for linking laptops, docks, and monitors in workstations and studio setups.
- Supports up to 4K x 2K at 60Hz, useful for high-resolution presentations, video playback, and color-accurate design work.
- Multi-Stream Transport support lets you drive multiple displays from a compatible source.
- Gold plated contacts and TPE jacket resist corrosion and improve durability for frequent connections.
- Note: 60Hz may not meet the needs of high-end gaming or ultra-smooth motion workflows.

Function and use

Prokord Cable Mini Displayport - Mini-Displayport 2.0m carries video and protected audio streams between Mini DisplayPort-enabled devices while preserving content protection through HDCP. Its construction, including tinned copper conductors and reinforced shielding, helps maintain a stable signal in office and creative environments. The flexible yet sturdy jacket makes routing and regular handling easier, and the straight male connectors fit standard Mini DisplayPort sockets for straightforward setup.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	2 m
Connector 1	Mini DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	Mini DisplayPort
Connector 2 gender	Male
Connector 2 form factor	Straight
Product colour	Black

Maximum resolution	4Kx2K pixels
Connector contacts plating	Gold plated
DisplayPort version	1.2
Cable material	Tinned copper
Maximum refresh rate	60 Hz
HDCP	Yes
Data transfer rate	5.4 Gbit/s
Cable shielding	Aluminium foil + braid
Jacket material	TPE
AWG wire size	32AWG
High Dynamic Range (HDR) supported	No
Multi-Stream Transport (MST)	Yes

Packaging data

Cable diameter	5 mm
Weight	79 g

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------