



Prokord UTC-H-1m

Data sheet

Core Specs

Cable length	1 m
Connector 1	USB-C
Connector 2	HDMI
Product colour	Black
HDMI version	1.4
DisplayPort version	HDCP

Summary

- ✓ USB-C
- ✓ HDMI
- ✓ 3840 x 2160@30hz
- ✓ 1m

Product description

Why choose this USB-C to HDMI adapter?

Prokord USB-C To HDMI 4K 30Hz Adapter gives a simple, reliable way to connect USB-C devices to HDMI displays. The 1 m black cable with gold-plated connectors and aluminium-foil braid shielding ensures stable digital video up to 4K at 30 Hz, making it suitable for presentations, design review, and general screen extension without extra drivers.

Prokord USB-C To HDMI 4K 30Hz Adapter in short:

- Connect your USB-C laptop, tablet, or phone to HDMI displays for presentations, extended desktops, or video playback.
- Supports up to 3840 x 2160 at 30 Hz, suitable for slides, design previews, and standard 4K content.
- Gold-plated contacts, tinned copper conductors, and aluminium-foil plus braid shielding help maintain a steady signal.
- Plug-and-play with HDCP support and straight male connectors, using a flexible 1 m PVC-jacketed cable.
- Consider that the 30 Hz refresh rate is not intended for fast-paced gaming.

Prokord USB-C To HDMI 4K 30Hz Adapter

This adapter converts a USB-C video output to HDMI so you can mirror or extend your screen to TVs, monitors, or projectors. It complies with HDMI 1.4 and supports HDCP, which helps with playback of protected content. The compact design, gold-plated contacts and robust shielding reduce interference, and the straight male connectors with a 1 m PVC cable make it easy to connect in typical office and home setups.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	1 m
Connector 1	USB-C
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	HDMI
Connector 2 gender	Male
Connector 2 form factor	Straight
Product colour	Black
HDMI version	1.4

DisplayPort version	HDCP
Connector contacts plating	Gold plated
HDCP	Yes
Supported graphics resolutions	3840 x 2160
Maximum resolution	4kx2k pixels
High Dynamic Range (HDR) supported	No
Maximum refresh rate	30 Hz
Cable material	Tinned copper
Cable shielding	Aluminium foil + braid
Supported video modes	2160p
Jacket material	PVC
AWG wire size	34AWG
Data transfer rate	2.7 Gbit/s

Weight & dimensions

Weight	52 g
Cable diameter	3.9 mm

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	-----------------

Packaging data

Quantity per pack	1 pc(s)
-------------------	----------------