



Prokord DP1.4-DP1.4 0055

Data sheet

Core Specs

Cable length	3 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Product colour	Black
DisplayPort version	1.4

Summary

- ✓ 3m cable length offers flexible setup across desks and racks
- ✓ Supports 8K at up to 30Hz and HDR for clearer images on displays
- ✓ Gold contacts and double shielding ensure reliable signal
- ✓ LSZH and TPE jacket reduces smoke and improves safety
- ✓ MST and HDCP support enable multi display setups and protected content

Product description

Why choose this DisplayPort cable?

Prokord Cable Displayport 1.4 - Displayport 3.0m Black gives reliable high-resolution video and audio over a robust LSZH and TPE jacket. It supports 8K and HDR for clear images, and includes MST and HDCP compatibility for multi-monitor setups and protected content. Gold-plated contacts and braided shielding help maintain signal integrity in professional installations.

Cable Displayport 1.4 - Displayport 3.0m Black in short:

- Supports DisplayPort 1.4 with HDR and up to 8K resolution, suitable for high-resolution monitors and digital signage.
- Male-to-male, straight DisplayPort connectors on both ends for direct connections to graphics cards and displays.
- Gold-plated contacts, tinned copper conductors, and aluminium foil plus braid shielding for stable signal transfer.
- Low smoke zero halogen (LSZH) and TPE jacket for safer use in offices and public spaces.
- Supports Multi-Stream Transport and HDCP; note that maximum refresh rate at 8K is 30Hz, so consider this if you need higher frame rates.

Product details

The Prokord Cable Displayport 1.4 - Displayport 3.0m Black is a 3 metre DisplayPort 1.4 cable designed to connect computers, workstations, and media players to high-resolution displays and projectors. With 26AWG tinned copper conductors, gold-plated contacts and dual-layer shielding, the cable balances flexibility with consistent signal performance. Its straight, male-to-male connectors make installation simple, and the LSZH jacket reduces hazardous smoke in confined environments.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	3 m
Connector 1	DisplayPort
Connector 1 gender	Male
Connector 1 form factor	Straight
Connector 2	DisplayPort
Connector 2 gender	Male
Connector 2 form factor	Straight

Product colour	Black
Maximum resolution	8K pixels
Connector contacts plating	Gold plated
DisplayPort version	1.4
Cable material	Tinned copper
Maximum refresh rate	30 Hz
HDCP	Yes
Data transfer rate	8.1 Gbit/s
Cable shielding	Aluminium foil + braid
Jacket material	LSZH, TPE
AWG wire size	26AWG
High Dynamic Range (HDR) supported	Yes
Multi-Stream Transport (MST)	Yes

Packaging data

Cable diameter	8.5 mm
Weight	247 g

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------