



TP-Cable UTP CAT.6 Unshielded Lszh RJ45 3m 10pcsRJ-45 Cat 6 3m White

Data sheet

Summary

- ✓ Shielded S/UTP RJ-45 connectors reduce electromagnetic interference, helping maintain stable links for uplinks and edge devices.
- ✓ Supports up to 10 Gbit/s and 250 MHz, suitable for high-speed LANs, switches, and server connections.
- ✓ LSZH jacket and white finish make it appropriate for indoor installations where reduced smoke and halogen are required.
- ✓ 3 meter length in a 10-piece pack, convenient for desk-to-switch patching and small rack installations. Consider the 3 m length when planning cable runs.
- ✓ Compliant with RoHS and REACH, and compatible with Power over Ethernet for VoIP phones, wireless access points, and cameras.

Product description

Why choose this patch cable?

Prokord Cat6 S/UTP LSZH RJ-45 patch cable, 3m, 10-pack delivers reliable, high-speed connections while keeping installations safe and tidy. It combines shielded connectors for stable links in electrically noisy environments with a low-smoke, zero-halogen jacket for use in offices and public buildings. The 10-pack format reduces procurement and stocking effort for routine network deployments.

Prokord Cat6 S/UTP LSZH RJ-45 patch cable, 3m, 10-pack in short:

- Shielded S/UTP RJ-45 connectors reduce electromagnetic interference, helping maintain stable links for uplinks and edge devices.
- Supports up to 10 Gbit/s and 250 MHz, suitable for high-speed LANs, switches, and server connections.
- LSZH jacket and white finish make it appropriate for indoor installations where reduced smoke and halogen are required.
- 3 meter length in a 10-piece pack, convenient for desk-to-switch patching and small rack installations. Consider the 3 m length when planning cable runs.
- Compliant with RoHS and REACH, and compatible with Power over Ethernet for VoIP phones, wireless access points, and cameras.

Product details

This Prokord Cat6 cable uses 26 AWG copper conductors and male-to-male RJ-45 plugs to deliver consistent signal quality. The shielded construction helps in environments with potential interference and supports PoE to power connected devices directly over the cable. The LSZH outer jacket reduces toxic fumes in case of fire, which is useful for installations in public or enclosed spaces. The 10-pack format simplifies bulk deployments and spare stocking.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	3 m
Cable standard	Cat 6
Cable shielding	S/UTP (STP)
Connector 1	RJ-45
Connector 1 gender	Male
Connector 2	RJ-45
Connector 2 gender	Male

Product colour	White
Jacket material	LSZH
Conductor material	Copper
Data transfer rate	10000 Mbit/s
AWG wire size	26
Power over Ethernet (PoE)	Yes
Frequency	250 MHz

Packaging data

Quantity per pack	10 pc(s)
-------------------	----------

Technical details

Sustainability compliance	Yes
Sustainability certificates	REACH, RoHS
Compliance certificates	REACH, RoHS

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------