



# Prokord S/FTP-0103

Data sheet

## Core Specs

|                 |               |
|-----------------|---------------|
| Connector 1     | RJ-45         |
| Connector 2     | RJ-45         |
| Cable standard  | Cat 6A        |
| Cable shielding | S/FTP (S-STP) |
| Cable length    | 15 m          |
| Jacket material | LSZH          |

## Summary

- ✓ Cat6A construction delivers 10Gb/s throughput for high bandwidth
- ✓ S/FTP shielding and copper conductors reduce interference and errors
- ✓ Supports PoE so devices get power and network over one cable
- ✓ LSZH yellow jacket improves safety and visibility during installation
- ✓ 15m length with RJ-45 male connectors suits racks and equipment links

# Product description

## Why choose this network cable?

Prokord TP-Cable S/FTP provides a dependable 10 Gbit/s connection with robust S/FTP shielding and PoE support, helping you maintain stable links in dense cabling environments. The 15 m length and yellow LSZH jacket make installation and routing easier while meeting safety needs for indoor and server room use.

## Prokord TP-Cable S/FTP in short:

- Cat6A performance for 10 Gbit/s connectivity at up to 500 MHz, suitable for server racks and switch-to-switch links
- S/FTP shielding and metalized RJ-45 plugs reduce electromagnetic interference in noisy installations
- Low smoke zero halogen jacket and visible yellow color improve safety and cable management in enclosed spaces
- Supports Power over Ethernet, useful for IP cameras, access points, and VoIP devices
- Not intended for outdoor use exposed to weather, consider this when planning routes

## Product details

This TP-Cable S/FTP is a shielded Cat6A patch cable with male RJ-45 connectors on both ends, designed for short to medium runs inside buildings and data closets. Copper conductors and 26 AWG wiring deliver consistent signal integrity, while the S/FTP construction protects against crosstalk and external noise. Use it to link switches, patch panels, and PoE devices where reliable, visible, and safe cabling is required.

# Technical Specification Matrix

## Header

|              |         |
|--------------|---------|
| Manufacturer | Prokord |
|--------------|---------|

## Features

|                    |               |
|--------------------|---------------|
| Cable length       | 15 m          |
| Cable standard     | Cat 6A        |
| Cable shielding    | S/FTP (S-STP) |
| Connector 1        | RJ-45         |
| Connector 1 gender | Male          |
| Connector 2        | RJ-45         |
| Connector 2 gender | Male          |
| Product colour     | Yellow        |
| Jacket material    | LSZH          |

|                           |              |
|---------------------------|--------------|
| Conductor material        | Copper       |
| Data transfer rate        | 10000 Mbit/s |
| AWG wire size             | 26           |
| Frequency                 | 500 MHz      |
| Power over Ethernet (PoE) | Yes          |

Packaging data

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

Logistics data

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733080 |
|-----------------------------|----------|