



# Prokord S/FTP-0125

Data sheet

## Core Specs

|                 |               |
|-----------------|---------------|
| Connector 1     | RJ-45         |
| Connector 2     | RJ-45         |
| Cable standard  | Cat 6A        |
| Cable shielding | S/FTP (S-STP) |
| Cable length    | 0.3 m         |
| Jacket material | LSZH          |

## Summary

- ✓ Short 0.3 m cable reduces clutter and simplifies patching.
- ✓ Cat6A and 500MHz bandwidth support 10Gbps links for server racks.
- ✓ S/FTP shielding limits interference in dense cabling environments.
- ✓ LSZH jacket improves safety in enclosed and public areas.
- ✓ PoE ready, powers devices without extra wiring.

# Product description

## Why choose this Ethernet cable?

Prokord TP-Cable S/FTP delivers short, reliable connections with Cat 6A performance and PoE support, reducing cable clutter and installation time. Its S/FTP shielding and metal-bodied RJ-45 plugs keep interference low for stable 10 Gbit/s links, while the LSZH jacket improves safety in confined spaces and the 0.3 m length simplifies tidy patching between adjacent devices.

## Prokord TP-Cable S/FTP in short:

- Cat 6A S/FTP patch cable, suitable for 10 Gbit/s connections and up to 500 MHz operation.
- 0.3 m length, ideal for patch panels, stacked switches, and close-proximity device connections.
- Shielded RJ-45 male-to-male plugs with metal housing and strain relief for secure mating and reduced EMI.
- LSZH blue jacket and 26 AWG copper conductors, supporting Power over Ethernet for powering compatible devices.
- Not suitable for long-distance cable runs; designed for short, neat connections.

## Product details

This shielded patch cable is built for short runs where performance and cleanliness matter. The S/FTP construction reduces crosstalk and external interference, while the plated copper conductors ensure consistent PoE delivery and signal integrity. The low smoke zero halogen jacket enhances safety in equipment rooms and public areas. The cable’s compact length and blue colour make it easy to route and identify in dense network cabinets.

# Technical Specification Matrix

## Header

|              |         |
|--------------|---------|
| Manufacturer | Prokord |
|--------------|---------|

## Features

|                    |               |
|--------------------|---------------|
| Cable length       | 0.3 m         |
| Cable standard     | Cat 6A        |
| Cable shielding    | S/FTP (S-STP) |
| Connector 1        | RJ-45         |
| Connector 1 gender | Male          |
| Connector 2        | RJ-45         |
| Connector 2 gender | Male          |
| Product colour     | Blue          |
| Jacket material    | LSZH          |

|                           |              |
|---------------------------|--------------|
| Conductor material        | Copper       |
| Data transfer rate        | 10000 Mbit/s |
| AWG wire size             | 26           |
| Frequency                 | 500 MHz      |
| Power over Ethernet (PoE) | Yes          |

Packaging data

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

Logistics data

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733080 |
|-----------------------------|----------|