



Prokord S/FTP-0127

Data sheet

Core Specs

Connector 1	RJ-45
Connector 2	RJ-45
Cable standard	Cat 6A
Cable shielding	S/FTP (S-STP)
Cable length	1 m
Jacket material	LSZH

Summary

- ✓ Cat6a S/FTP cable supports 10 Gbit/s at 500 MHz for fast links
- ✓ S/FTP shielding reduces crosstalk, keeps signals stable in dense racks
- ✓ LSZH jacket limits smoke and halogen, ideal for office and data rooms
- ✓ Blue jacket and RJ45 plugs, 1m fits short runs and lab setups

Product description

Why choose this network cable?

Prokord TP-Cable S/FTP delivers reliable, high-speed connectivity for short-range network links. This Cat 6A S/FTP cable supports up to 10 000 Mbit/s and 500 MHz, while the LSZH jacket reduces toxic emissions in confined spaces. Shielding and copper conductors minimise interference, and PoE compatibility lets you power devices without extra cabling.

TP-Cable S/FTP in short:

- 1 m Cat6a S/FTP patch cable for short links and bench testing.
- Shielded pairs and copper conductors for stable 10 Gbit/s performance in noisy environments.
- LSZH jacket for installations where low smoke and halogen-free materials are required.
- RJ-45 male to male connectors, plug-and-play for switches, patch panels and PoE devices.
- Not suitable for long-distance cabling installations.

Product details

It features RJ-45 male connectors and S/FTP shielding to reduce crosstalk and external interference. The 26 AWG copper conductors support high data rates up to 10 Gbit/s at 500 MHz over the 1 m length. The blue LSZH jacket makes identification easy and limits harmful emissions in enclosed spaces. Use this cable for patching, short rack-to-desk links, and powering PoE devices without running separate power lines.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	1 m
Cable standard	Cat 6A
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 1 gender	Male
Connector 2	RJ-45
Connector 2 gender	Male
Product colour	Blue
Jacket material	LSZH

Conductor material	Copper
Data transfer rate	10000 Mbit/s
AWG wire size	26
Frequency	500 MHz
Power over Ethernet (PoE)	Yes

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------