



Workplace Portreplikator Triple 4K Display 96WUSB-C

Data sheet

Core Specs

Host interface	USB-C
DisplayPorts quantity	2
HDMI ports quantity	3

Summary

- ✓ Connect up to three 4K displays simultaneously
- ✓ Two display connections via DisplayLink and one via DisplayPort Alt Mode
- ✓ Connects to computers via USB-C or USB-A
- ✓ Up to 96 W charging via USB-C
- ✓ Gigabit Ethernet

Product description

Key features

- Connect up to three 4K displays simultaneously
- Two display connections via DisplayLink and one via DisplayPort Alt Mode
- Connects to computers via USB-C or USB-A
- Up to 96 W charging via USB-C
- Gigabit Ethernet

Prokord Triple 4K Display Docking Station

The Prokord Triple 4K Display Docking Station is a versatile solution that connects displays, network access, USB accessories and audio equipment through a single docking station. It connects to your computer via USB-C and can also be used with USB-A for DisplayLink-based functionality.

Its compact design takes up minimal space on your desk, making it easy to create a complete workspace at the office or at home.

Connect up to three 4K displays simultaneously

The docking station features five video outputs and supports up to three external 4K displays simultaneously.

Two displays are connected using DisplayLink technology and can use the docking station's HDMI or DisplayPort outputs. The third HDMI output uses the computer's native video signal via DisplayPort Alt Mode and supports resolutions up to 4K at 30 Hz.

To use three displays simultaneously, the computer's USB-C port must support DisplayPort Alt Mode. When connected via USB-A, the DisplayLink outputs can be used, but the HDMI output based on DisplayPort Alt Mode will not be available.

Please note that the five video outputs provide flexibility between HDMI and DisplayPort. A maximum of three displays can be used simultaneously.

Broad compatibility with DisplayLink

DisplayLink makes it possible to transmit video through a standard USB connection. Two external displays can therefore be connected even to computers that do not support native video output via USB-C.

A combined USB-C to USB-C/USB-A cable is included, allowing the docking station's DisplayLink features to be used with computers equipped with either USB-C or USB-A.

DisplayLink requires compatible drivers to be installed on the computer.

[Download the latest DisplayLink drivers here](#)

Connections

- 5 × USB 3.0 Type-A with data transfer speeds of up to 5 Gbps
- 1 × USB-C for connecting USB devices

- 1 × USB-C host connection for connecting and charging the computer
- 1 × headphone output
- 1 × microphone input
- 1 × Gigabit Ethernet RJ-45 supporting 10/100/1000 Mbps
- 2 × HDMI via DisplayLink, supporting up to 4K at 60 Hz
- 2 × DisplayPort via DisplayLink, supporting up to 4K at 60 Hz
- 1 × HDMI via DisplayPort Alt Mode, supporting up to 4K at 30 Hz
- Up to 96 W Power Delivery to the connected computer
- Supports resolutions up to 5K, 5120 × 2880 at 60 Hz, using two DisplayPort cables

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Ports & interfaces

Connectivity technology	Wired
Host interface	USB-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
HDMI ports quantity	3
USB Power Delivery	Yes
USB Power Delivery up to	96 W
DisplayPorts quantity	2
Microphone in	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
Combo headphone/mic port	No

Performance

Product colour	Black
Card reader integrated	No
Housing material	Plastic
Cable lock slot type	Kensington
Cable lock slot	Yes
LED indicators	Power
Country of origin	China

On/off switch	Yes
Rubber feet	Yes
Daisy chain	Yes
Brand compatibility	Universal

Network

Ethernet LAN	Yes
Ethernet LAN data rates	1000 Mbit/s

Power

Power source type	DC
Output voltage	20, 15, 9, 5 V
Output current	6.75 A
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
USB cable length	1 m
Power consumption (max)	135 W

Weight & dimensions

Width	250 mm
Depth	82.25 mm
Height	34.45 mm
Weight	350 g

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Software

Mac operating systems supported	Yes
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	ChromeOS

Packaging content

Cables included	USB Type-A to USB Type-C, USB Type-C
AC adapter included	Yes
Manual	Yes