



Workplace USB-C docking station - 3x 4K, DisplayLink, 80WUSB-C 3.2 Gen 1 (3.1 Gen 1)

Data sheet

Core Specs

Host interface	USB-C 3.2 Gen 1 (3.1 Gen 1)
DisplayPorts quantity	1
HDMI ports quantity	2

Summary

- ✓ 4 × USB-A 3.1 Gen 1 (5 Gbps) – connect your mouse, keyboard, printer, and more
- ✓ 1 × USB-C (host connection) – connect to your laptop
- ✓ 1 × USB-C with Power Delivery (up to 80W) – charge your laptop while you work
- ✓ 2 × HDMI (4K support)
- ✓ 1 × DisplayPort (4K support)

Product description

Prokord Workplace Docking Station USB-C – 3x 4K, DisplayLink, 80W

? [Download the latest DisplayLink drivers here](#)

? Universal Docking Station for Your Workplace

The Prokord Workplace USB-C Docking Station is a powerful and compact port replicator for laptops with USB-C connectivity. It's designed to transform your laptop into a fully equipped workstation with support for three external 4K displays, USB-C charging, and a comprehensive set of ports – all in a sleek, space-saving design.

Thanks to DisplayLink technology, the dock is compatible with Windows 10/11, macOS (11+), Chrome OS, and Ubuntu, making it the ideal solution for businesses, home offices, and hybrid work environments.

?? Connect Three 4K Displays – Simultaneously

The docking station supports 2x 4K @ 60Hz + 1x 4K @ 30Hz via HDMI and DisplayPort, giving you the flexibility to multitask, create content, and work more efficiently.

? Connections & Features

- 4 × USB-A 3.1 Gen 1 (5 Gbps) – connect your mouse, keyboard, printer, and more
- 1 × USB-C (host connection) – connect to your laptop
- 1 × USB-C with Power Delivery (up to 80W) – charge your laptop while you work
- 2 × HDMI (4K support)
- 1 × DisplayPort (4K support)
- 1 × Gigabit Ethernet (RJ-45) – for stable, high-speed internet
- 1 × 3.5 mm headphone/microphone combo jack
- 1 × SD/MicroSD card reader

? Key Features

- Support for three external monitors – 2x 4K@60Hz + 1x 4K@30Hz
- USB-C Power Delivery up to 80W – charge your laptop with a single cable
- Fast charging via USB-A (BC1.2 support) – great for phones and accessories
- Hot Swap support – plug and play without rebooting
- Universal compatibility – works with Windows, macOS, Chrome OS, and Ubuntu
- DisplayLink chipset – ensures stable and high-quality image transfer
- Compact design – saves desk space
- LED indicator – visual status feedback

? What's in the Box

- Prokord Workplace USB-C Docking Station
- USB-C to USB-C cable
- 120W power adapter

? Compatibility

- Operating Systems: Windows 10/11, macOS (11+), Chrome OS, Ubuntu
- Connection: USB-C (for full functionality); works with USB-A (limited functionality)

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Ports & interfaces

Connectivity technology	Docking
Host interface	USB-C 3.2 Gen 1 (3.1 Gen 1)
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery	Yes
HDMI ports quantity	2
USB Power Delivery up to	80 W
HDMI version	2.0
DisplayPorts quantity	1
Microphone in	Yes
DisplayPort version	1.4
Headphone outputs	1
Combo headphone/mic port	Yes

Performance

Product colour	Black
Maximum digital resolution	3840 x 2160 pixels
Number of displays supported	3
Hub weight	400 g
HD type	4K/UHD
LED indicators	Yes

Certification	FCC, CE
Data transfer rate	5 Gbit/s
On/off switch	Yes
Maximum refresh rate	60 Hz
Charging function	Yes

Network

Ethernet LAN (RJ-45) ports	1
Ethernet LAN	Yes
Ethernet LAN data rates	1000 Mbit/s

Graphics

Maximum resolution	3840x2160 pixels
--------------------	------------------

Power

Output voltage	20 V
Output current	6 A
Power supply	120 W

Weight & dimensions

Width	304 mm
Depth	76 mm
Height	18.8 mm
Weight	400 g
Height (front)	11.5 mm

Software

Windows operating systems supported	Yes
Mac operating systems supported	Yes
Mobile operating systems supported	iOS
Other operating systems supported	ChromeOS

Packaging content

Cables included	Type-C M to M Cable
AC adapter included	Yes

Operational conditions

Operating temperature (T-T)	0 to 45 °C
Operating relative humidity (H-H)	10 to 90 %
Storage temperature (T-T)	0 to 70 °C
Storage relative humidity (H-H)	10 to 90 %

Technical details

Warranty period	1 year(s)
-----------------	-----------

Other features

Dimensions (WxDxH)	304x76x18.8 mm
USB ports quantity	5

Warranty & services

Warranty	1 Year(s)
----------	-----------