



Prokord DCP-C13-2BLSZH

Data sheet

Core Specs

Cable length	2 m
Connector 1	CEE7/7
Connector 2	C13
Product colour	Black

Summary

- ✓ 2 m length provides flexible reach for rack and desk installations
- ✓ CEE7/7 to C13 connectors ensure easy connection to EU mains and IT gear
- ✓ LSZH jacket reduces smoke and toxic gases, improving safety
- ✓ Wide temp and humidity ranges keep connections reliable across sites
- ✓ Black finish blends into racks and cable runs for neat installations

Product description

Why choose this power cable?

DCP-C13-2BLSZH Prokord is a 2 m power cable that gives a safe, low-smoke connection between CEE7/7 mains sockets and IEC C13 equipment. Its LSZH jacket reduces smoke and corrosive gases in case of fire, and the black finish helps keep installations neat. Use it where safety, reliability, and flexible placement matter.

DCP-C13-2BLSZH in short:

- Connects CEE7/7 wall sockets to IEC C13 inlets, suitable for PCs, monitors, UPS units, and other IT equipment.
- Low smoke zero halogen (LSZH) jacket reduces toxic emissions and is appropriate for enclosed spaces and public areas.
- 2 m length provides flexible placement behind desks or in racks while keeping cable runs tidy.
- Designed to operate across a wide temperature and humidity range and at altitudes up to 5000 m.
- Check that your mains outlet uses the CEE7/7 form factor before purchase.

Usage and durability

The DCP-C13-2BLSZH has a male CEE7/7 plug and a female IEC C13 connector, making it a straightforward replacement or spare cable for standard European-equipped devices. The LSZH jacket improves safety in confined environments and helps protect equipment from corrosive residues after a fire. It is built to perform in a range of conditions, with operating temperatures from -20 to 80°C and humidity tolerance from 5 to 95 percent, so you can use it in offices, server rooms, and field deployments up to 5000 m altitude.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Features

Cable length	2 m
Connector 1	CEE7/7
Connector 1 gender	Male
Connector 2	C13
Connector 2 gender	Female
Product colour	Black
Jacket material	LSZH

Operational conditions

Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95 %
Storage relative humidity (H-H)	5 - 95 %
Operating altitude	0-5000 m