



Workplace Charging Dockingstation USB-C 5K Dual Monitor 65WUSB-C 3.2 Gen 1 (3.1 Gen 1)

Data sheet

Core Specs

Host interface	USB-C 3.2 Gen 1 (3.1 Gen 1)
DisplayPorts quantity	2
HDMI ports quantity	2

Summary

- ✓ Drive dual external displays and support high-resolution output up to 5120 x 2880 at 60Hz for de...
- ✓ Charge laptops with up to 65W USB-C Power Delivery while connecting storage, keyboard and ...
- ✓ Built-in gigabit Ethernet and a 3.5 mm audio jack provide stable network access and simple audio c...
- ✓ Front-accessible ports and included USB-C and USB-C to USB-A cables make daily docking fast a...
- ✓ Consider that 65W charging may not fully power some high-performance laptops under maximum l...

Product description

Why choose this dockingstation?

Prokord Workplace Charging Dockingstation USB-C 5K Dual Monitor 65W simplifies desk setup by combining power, video and connectivity in one unit. It reduces cable clutter while giving reliable wired Ethernet and many USB ports for peripherals. The docking station supports high-resolution displays and 65W USB-C charging to keep your laptop powered during typical office use.

Workplace Charging Dockingstation USB-C 5K Dual Monitor 65W in short:

- Drive dual external displays and support high-resolution output up to 5120 x 2880 at 60Hz for detailed work and presentations.
- Charge laptops with up to 65W USB-C Power Delivery while connecting storage, keyboard and mouse to multiple USB-A and USB-C ports.
- Built-in gigabit Ethernet and a 3.5 mm audio jack provide stable network access and simple audio connections.
- Front-accessible ports and included USB-C and USB-C to USB-A cables make daily docking fast and predictable.
- Consider that 65W charging may not fully power some high-performance laptops under maximum load.

Product details

The Prokord docking station connects to a host via USB-C 3.2 Gen 1 and offers a mix of two DisplayPort 1.4 and two HDMI 2.0 outputs for flexible monitor setups. It includes three USB-C and six USB-A 3.2 Gen 1 ports for peripherals and fast file transfer. A built-in RJ45 Ethernet port supports 10/100/1000 Mbit/s for reliable wired connections. Practical features such as an on/off switch, key lock, rubber feet and a compact black plastic housing help keep your workspace organised and secure. The package contains an AC adapter, required cables, a quick start guide and documentation, and it is compatible with Windows, Mac, Linux and ChromeOS.

Technical Specification Matrix

Header

Manufacturer	Prokord
--------------	---------

Ports & interfaces

Connectivity technology	Wired
Host interface	USB-C 3.2 Gen 1 (3.1 Gen 1)
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	6
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	3
HDMI ports quantity	2

USB Power Delivery	Yes
USB Power Delivery up to	65 W
DisplayPorts quantity	2
HDCP	Yes
HDMI version	2.0
Microphone in	Yes
HDCP version	2.0
DisplayPort version	1.4
Headphone outputs	1
Headphone connectivity	3.5 mm

Performance

Product colour	Black
Housing material	Plastic
Maximum digital resolution	5120 x 2880 pixels
Number of displays supported	2
HD type	5K
On/off switch	Yes
Maximum refresh rate	60 Hz
Display modes	Duplicate, Extended, Mirror
Rubber feet	Yes
Key lock	Yes

Network

Ethernet LAN (RJ-45) ports	1
Ethernet LAN	Yes
Ethernet LAN data rates	10, 100, 1000 Mbit/s

Power

Power source type	AC
Power supply	100 W

Weight & dimensions

Width	22.3 mm
Depth	8 mm
Height	2.6 mm

Weight	890 g
--------	-------

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------

Software

Mac operating systems supported	Yes
Windows operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	ChromeOS

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Packaging content

Cables included	USB Type-C, USB Type-C to USB Type-A
Quick start guide	Yes
AC adapter included	Yes
Manual	Yes

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Technical details

Compliance certificates	REACH, RoHS
-------------------------	-------------