



## **Built-in Desk Power Outlet with USB-A, USB-C and Cable**

Data sheet

### **Summary**

- ✓ Recessed power outlet for desks, meeting tables and worktops
- ✓ Earthed type F (Schuko) power socket
- ✓ Two USB-A ports and one USB-C port for charging mobile devices
- ✓ USB output 5 V / 2 A
- ✓ Integrated cable grommet for e.g. network, monitor or charging cables

# Product description

---

## Prokord Recessed Desk Power Outlet with USB-A, USB-C and Cable Grommet

### Why choose this recessed desk power outlet?

Prokord Recessed Desk Power Outlet with USB-A, USB-C and Cable Grommet is a flexible and well designed solution for modern workspaces where power, charging and cabling all need to be gathered in one place. By combining an earthed power outlet with multiple USB ports and an integrated cable grommet, you get a neat and functional installation directly in the desktop.

The recessed design keeps the outlet flush with the surface and contributes to a clean and organised work environment, while the matte black finish blends into offices, meeting rooms and home offices.

### Recessed power outlet with USB and cable grommet, in brief

- Recessed power outlet for desks, meeting tables and worktops
- Earthed type F (Schuko) power socket
- Two USB-A ports and one USB-C port for charging mobile devices
- USB output 5 V / 2 A
- Integrated cable grommet for e.g. network, monitor or charging cables
- Fits a standard 80 mm hole for a flat and discreet installation
- 1.8 metre connection cable made of pure copper
- Durable ABS construction with matte black surface

### Smart cable management directly in the desktop

The built in cable grommet makes it easy to pull out extra cables from the underside of the table without having to drill separate holes. This provides greater flexibility when connecting monitors, docking stations or networks and contributes to a more structured workspace without loose cables on top of the desk.

The compact design means the outlet takes up minimal space, while still providing easy access to power, charging and cabling where it is needed.

### Reliable construction for everyday use

The product is made of robust ABS and is designed for continuous use in professional environments. The fixed pure copper connection cable ensures stable power supply and low energy loss, even with longer cable runs.

The power outlet is intended for standard 220–230 V mains voltage and is equally suitable for offices and meeting rooms as for educational environments and commercial installations.

### Product information

- External dimensions: 95 × 65 mm
- Cut out: 80 mm

- Material: ABS
- Colour: Black
- Rated voltage: 230 V
- Connection cable: 1.8 m (pure copper)
- Outlets: 1 × AC (type F), 2 × USB-A, 1 × USB-C
- USB output: 5 V / 2 A

# Technical Specification Matrix

## Header

|              |         |
|--------------|---------|
| Manufacturer | Prokord |
|--------------|---------|

## Design

|                  |                                       |
|------------------|---------------------------------------|
| Product colour   | Black                                 |
| Housing material | Acrylonitrile butadiene styrene (ABS) |
| Surface finish   | Matt                                  |
| Cable length     | 1.8 m                                 |

## Features

|                      |                      |
|----------------------|----------------------|
| Socket type          | Type F, USB-A, USB-C |
| Sockets quantity     | 1                    |
| Supported plug types | CEE 7/4              |
| Installation type    | Desktop embedded     |

## Power

|                    |             |
|--------------------|-------------|
| Rated voltage      | 220 - 230 V |
| USB output voltage | 5 V         |
| Rated frequency    | 50/60 Hz    |
| USB output current | 3 A         |
| USB output power   | 15 W        |

## Packaging data

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

## Weight & dimensions

|       |       |
|-------|-------|
| Width | 96 mm |
| Depth | 65 mm |

|        |                |
|--------|----------------|
| Weight | <b>338.9 g</b> |
|--------|----------------|

|               |              |
|---------------|--------------|
| Hole diameter | <b>80 mm</b> |
|---------------|--------------|