


SCD-400

Versatile Customer Display for POS Applications



For use with POS and ECR Systems.
The Star SCD-400 Display use the same Interface as the Star POS printer

- Reliable and versatile customer display
- Large, clear, easy-to-read characters
- Wide viewing angle
- Single interface for display and printer
- New charcoal grey version available

SCD-400 Printer Specifications



Display method	Vacuum fluorescent display
Display Colour	Blue-green
No. of Characters	40 (20 columns x 2 lines)
Character font	5 x 7 dot matrix
Character size	9.2 x 6.4mm
Character type	Alpha numeric 95; International 32; Graphic characters 128; 11 international character sets are selectable by control code
Message function	Download capacity of 3 x 40 characters. User defined messages can also be displayed in scroll mode or blinking mode
Dimensions	Display unit: 110 x 230 x 45mm Support: Telescopic pole from 270 to 440mm width diameter 38mm Base: 12mm with 80mm diameter
Tilt angle:	300 max. Horizontal rotation: 3600
Interface	Serial RS232 C

Baud rate	Selectable from 300 to 9,600 BPS
Reliability	25,000 hours MTBF
Power consumption	Max. 400 mA / 12 VDC
Weight	Approx. 800g
Operating conditions Temperature Humidity	5 ~ 45°C 10% ~ 85% RH
EMI approvals	FCC class A, VDE class B
Included accessories	- Y Interface cable (PC to Star POS printers and display) - Interface connector adaptor DB-25 / DB-9 - DC cable set to connect to PC power supply - Power supply adaptor 230 VAC / 12VDC (GS approved) - Mounting bracket and mounting screws
Special features	- The display can be controlled together with Star POS printers via one interface. Printer or display can be selected by control code. Epson Emulation optional




CB-92

CB-2002 and CB-92

Versatile Customer Display for POS Applications

- Sturdy reliable PC POS cash drawers
- 3 position key lock
- Options include:
Note holder bracket, note divider and lockable cash till cover
- Both versions include a compulsion switch

Star's Series of cash drawers have been specifically designed to link with Star's and other industry standard POS printers. They range from the basic entry level model to the larger version aimed at markets with more note sizes.



CB-2002 Specifications

CB-92 Specifications



Connection to Peripheral Drive Circuit of Star Printer	Via 6-pin Modular plug connected to cash drawer by shielded cable with separated ground wire
Cash Tray Combination	8 Note and 8 Coin plus external Voucher / Cheque slot
Dimensions	410 (W) x 415 (D) x 114 (H) mm
Weight	7Kg
Input Voltage & Current	DC 24 Volt, 1 amp
Pulse Time	100m.s (max), 30m.s (min)
Colour	New Star White or Charcoal Grey versions
Drawer Release	3 position key lock with Drawer Release
Options available	Note Holder Bracket, Note Divider and Lockable Cover

Connection to Peripheral Drive Circuit of Star Printer	Via 6-pin Modular plug connected to cash drawer by shielded cable with separated ground wire
Cash Tray Combination	5 Note and 8 Coin
Dimensions	460 (W) x 450 (D) x 115 (H) mm
Weight	9.5Kg
Input Voltage & Current	DC 24 Volt, 1 amp
Pulse Time	100m.s (max), 30m.s (min)
Colour	Beige Case with chrome drawer front
Drawer Release	3 position key lock with Drawer Release
Options available	Note Holder Bracket, Note Divider and Lockable Cover