




LyCOM Technology Inc.

ST-124 + Raid5 SATA II – 3Gbps 4Ports Low Profile PCI Host



Native SATA II - 300 4Ports with Port Multiplier, NCQ, Raid5, Raid10, Raid0 and Raid1!

RAID 5 (Distributed Parity RAID), JBOD (Just Bunch of Disks), RAID 0 (Striping), RAID 1 (Mirroring) and RAID 0+1 (mirrored-striping) improve the data performance and provide the data redundancy and rebuilding.

FEATURES

- o **Provides 2 Brackets to Support Low profile PCI and Regular size PCI in one card**
- o **48 bits LBA can Break Capacity-Limit to Support HDD larger than 137GB**

1. PCI

- o Compliant with PCI Specification, revision 2.3
- o Supports 66 MHz PCI with 32-bit data
- o Internal application interface multiplexed to 4 ports
- o All registers appear in unified memory space
- o Full-chip command completion status accessible with single PCI burst access
- o I/O port access to register space
- o **Low Profile PCI form factor**

2. High Speed Serial ATA

- o Fully compliant with Serial ATA 1.0a and Serial ATA II Extensions to Serial ATA 1.0a Specifications revision 1.1
- o Hot-plug capability
- o Supports Serial ATA Generation 2 transfer rate of 3.0 Gb/s
- o Supports SATA II First-party DMA commands for **Native Command Queuing (NCQ)**
- o Supports **Serial ATA II Port Multiplier** 1.0 Specifications revision 1.1
- o Plesiochronous, Single PLL architecture, 1 PLL for 4 ports
- o Supports four independent Serial ATA channels

- o Independent Link, Transport, data FIFO, command fetch, scatter/gather, and command execution
- o 31 Commands and Scatter/Gather Tables per Port
- o Supports bootable drive
- o Four Pin header on board for LED connection
- o RAID 5 (Distributed Parity RAID) has Highest Read data transaction rate and Good aggregate transfer rate
- o JBOD is a virtual disk that combines all disk drives as one entire disk drive.
- o Provides RAID 0 (Striping) to greatly increase the performance of data transfer by simultaneously writing data to multiple drives
- o Provides RAID 1 (Mirroring) to protect the data from a disk failure by writing identical data on 2 drives
- o RAID 0+1 (Mirrored-Striping) combine both Striping and Mirroring technologies to provide both the performance enhancements that come from Striping and the data availability and integrity that comes from Mirroring
- o Completely with drivers for Windows 2000 ,XP and 2003 Server