

## **HDMI®** or DVI to DisplayPort® Active Converter

StarTech ID: HDMI2DP



The HDMl2DP DVI or HDMl® to DisplayPort® Converter converts an HDMl, DVI or Mini DVI input signal into a DisplayPort (or Mini DisplayPort) output, eliminating the cost of upgrading your source device hardware or purchasing a new display.

With support for full HD resolutions up to 1920x1200, the HDMl2DP converter is the perfect solution for connecting devices that have an HDMl, DVI single-link or mini DVI output, such as video cards (desktop or laptop), video game consoles or home theater receivers, to your DisplayPort-capable display.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

- Ideal for digital entertainment centers, home offices, business conference rooms and trade show displays
- Keep your existing DisplayPort® monitor to be used with your HDM® or DVI device

#### **Features**

- Supports full HD resolutions up to 1920x1200
- Stores EDID information to ensure compatibility between source and display
- Supports HDM® uncompressed 2-channel audio such as LPCM
- Allows for conversion of DVI or mini-DVI sources with additional cables (not included)
- Compatible with HDM®, DVI and Mini DVI 1.0 Input
- Supports DisplayPort®/Mini DisplayPort 1.1a output



### **Technical Specifications**

Warranty 2 Years

Converter Type Format Converter

Audio Yes

Output Signal DisplayPort

Connector A 1 - HDMI (19 pin) Female

Connector B 1 - DisplayPort (20 pin) Female

Audio Specifications 5.1 Surround Sound Maximum Digital Resolutions 1920x1200 (50/60Hz)

Color Black Enclosure Type Steel

Product Length 82 mm [3.2 in]
Product Width 43 mm [1.7 in]
Product Height 23 mm [0.9 in]
Product Weight 14 g [0.5 oz]

LED Indicators 1 - Red Power LED

Power Adapter Included Yes

Input Voltage 110 ~ 240 AC

Input Current 0.5A
Output Voltage 5 DC
Output Current 2A
Center Tip Polarity Positive

Plug Type N

Power Consumption 5W Max

Operating Temperature 0°C to 70°C (32°F to 158°F)

Storage Temperature -10°C to 80°C (14°F to 176°F)

Humidity 5% to 90% RH (no condensation)

Shipping (Package) Weight 0.2 kg [0.4 lb]

Included in Package 1 - HDMI to DisplayPort converter

Included in Package 1 - Universal Power Adapter (US/UK/EU)

Included in Package 1 - Instruction Manual





# Certifications, Reports and Compatibility







