

ProCurve Switch 4200vl Series Modules



ProCurve Switch vl 12-Port 100FX MTRJ Module (J8763A)

With 12 100FX fiber MTRJ ports

Ports

12 100Base-FX ports (IEEE 802.3u Type 100Base-FX)
Duplex: full
Connectors: MTRJ

Physical characteristics

Dimensions: 22.78 x 20.32 x 4.45 cm (8.97 x 8.0 x 1.75 in.)
Weight: 0.81 kg (1.79 lb.)



ProCurve Switch vl 16-Port Gig-T Module (J8764A)

With 16 RJ-45 10/100/1000T ports

Ports

16 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T; 802.3u Type 100Base-TX; 802.3ab Type 1000Base-T)
ProCurve/IEEE Auto-MDIX: yes
Duplex: half or full
Connectors: RJ-45

Physical characteristics

Dimensions (D x W x H): 22.78 x 20.32 x 4.45 cm (8.97 x 8.0 x 1.75 in.)
Weight: 0.7 kg (1.54 lb.)

Cabling

Type:

- 1000Base-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000Base-T



ProCurve Switch vl 4-port Mini-GBIC Module (J8776A)

With 4 mini-GBIC XCVR slots for the Switch 4200vl series chassis

Ports

Duplex: full
Connectors: SC

Physical characteristics

Dimensions (D x W x H): 22.78 x 20.32 x 4.45 cm
(8.97 x 8.0 x 1.75 in.)
Weight: 0.65 kg (1.43 lb.)

Cabling

Either single-mode or multimode



ProCurve Switch vl 24-Port 10/100-TX Module (J8765A)

With 24 RJ-45 10/100 ports for the Switch 4200vl series chassis

Ports

24 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T; 802.3u Type 100Base-TX)
ProCurve Auto-MDIX: yes
IEEE Auto-MDI: yes
Duplex: half or full
Connectors: RJ-45

Physical characteristics

Dimensions (D x W x H): 22.78 x 20.32 x 4.45 cm (8.97 x 8.0 x 1.75 in.)
Weight: 0.65 kg (1.43 lb.)

Cabling

Type:

- 100Base-TX: Category 5 (or better), 100 Ω differential unshielded twisted pair (UTP) or shielded twisted pair (STP), complying with IEEE 802.3u 100Base-TX

Maximum distance

100 meters

Services for accessories are covered under the product in which they are installed.