

High-Performance Managed L2 Switches

Affordable Workgroup/Departmental SNMP Solution

- Powerful Switching Capacity
- Bandwidth Control Down to 64k
- Gigabit Fiber Uplinks for Backbone Attachment
- Secure/Effective Management Through RADIUS, Traffic Monitoring

FEATURES

Workgroup/Departmental Connections

- Cost-Effective Ethernet Managed Desktops
- Gigabit Uplinks for Server/Backbone Attachments

Flexible Choices

- 4 Selections of Port Densities
- Desktop and Rack-Mount Sizes
- Open Slots for Optional Uplink Modules *
- Choices of Ethernet and Gigabit Copper/Fiber Uplinks

Security

- Port Security
- 802.1x Port-Based/MAC-Based Access Control
- External RADIUS Server Support

Traffic Monitoring/Bandwidth Control

- Traffic Segmentation
- 802.3ad Link Aggregation (Port Trunks)
- GUI Traffic Monitoring
- RMON Support
- Port Mirroring

Configuration/Management

- Web-Based
- Command Line Interface (CLI)
- SNMP v.1, v.2c, v3 Standard
- Single IP Management Client for Attachment to Virtual Stack
- D-View SNMP Network Management Module Provided
- Telnet Server

* Available on DES-3018 and DES-3026 only.

** SIM Client is used for stacking with DES-3500, DES-3800 series switches, xStack or DES-6500 chassis embedded with SIM (Single IP Management) Commander v.1.0 or above.

The DES-3000 series switches are high-performance managed Layer 2 switches that provide an ideal solution for workgroups and departments. These switches present a great entry-level managed solution for the SMB just starting out or the already established business looking to bring a managed solution to the desktops. These switches provide fiber uplinks for connection of small groups of users over a larger distance such as on a campus and between indoor departments or school classrooms.

High-Performance L2 Switching. With powerful switch fabric and abundant processing memory, the DES-3000 series provides wire-speed high performance for departments and workgroups. These switches include support for traffic segmentation that isolates ports to protect privacy. They allow you to migrate end users to an 802.1x environment when existing workstations support the 802.1x authentication protocol.

Investment Protection. By supporting industry approved specifications, the DES-3000 series leverages your existing investment in a multi-vendor environment, while maximizing compatibility of business with critical features like Spanning Tree (802.1D and 802.1w), QoS (802.1p), port mirroring and network management. These switches provide robust support for standard-based management protocols such as SNMP, RMON, BOOTP, Telnet, web and port mirroring, enabling you to integrate them into many third-party network management packages.

Advanced Enterprise Features. The DES-3000 series switches bring advanced enterprise functions to a more affordable level while supporting advanced features: 802.1p and port-based QoS/CoS, rich security and management features such as port-based/MAC-based 802.1x authentication and bandwidth control. These switches also support many of the features you would expect to see on a larger managed solution such as: IGMP snooping, 802.3ad Link Aggregation, 255 VLANs, traffic segmentation, traffic monitoring and SYSLOG.

Cost-Effective Virtual Stack. With D-Link Single IP Management client support, the DES-3000 series can be attached to a higher-level core switch such as a DES-6500 chassis or a D-Link xStack to form a virtual stack. The DES-3000 series can form a workgroup or departmental stack providing 10/100Mbps speed with Gigabit uplinks to the core switch. The DES-3000 series simplifies and speeds up your management tasks, as multiple switches can be configured, monitored and maintained from a management station through one unique IP address.**



Specification Chart

DES-3010G

DES-3010F

DES-3018

DES-3026



	DES-3010G	DES-3010F	DES-3018	DES-3026	
Physical & Hardware	Size	Desktop Size, 1U Height	Desktop Size, 1U Height	Rackmount Width, 1U Height	
	Interfaces	8 10/100BASE-TX Ethernet 1 1000BASE-T Gigabit 1 SFP	8 10/100BASE-TX Ethernet 1 1000BASE-T Gigabit 1 100BASE-FX Ethernet	16 10/100BASE-TX Ethernet 2 Open Slots	24 10/100BASE-TX Ethernet 2 Open Slots
	Stackability	Virtual Stack *	Virtual Stack *	Virtual Stack *	Virtual Stack *
	Stacking Topology	Virtual Stacking via SIM *	Virtual Stacking via SIM *	Virtual Stacking via SIM *	Virtual Stacking via SIM *
Performance	Switching Capacity	5.6 Gbps	5.6 Gbps	7.2 Gbps	8.8 Gbps
	64-Byte Packet Forwarding Rate	4.2 Mpps	4.2 Mpps	5.4 Mpps	6.6 Mpps
	MAC Address Table Size	8 K	8 K	8 K	8 K
	SDRAM for CPU	32 MB	32 MB	32 MB	32 MB
	Packet Buffer	256 KB	256 KB	256 KB	256 KB
	Flash Memory	4 MB	4 MB	4 MB	4 MB
L2 Features	IGMP Snooping	✓	✓	✓	✓
	802.1D Spanning Tree	✓	✓	✓	✓
	802.1w Rapid Spanning Tree	✓	✓	✓	✓
	802.3ad Link Aggregation	✓	✓	✓	✓
	No. of Ports Per Group	8 Ports	8 Ports	8 Ports	8 Ports
	No. of Groups Per Device	3 Groups	3 Groups	3 Groups	3 Groups
	Port mirroring	✓	✓	✓	✓
Broadcast Storm Control	✓	✓	✓	✓	
VLAN	802.1Q	✓	✓	✓	✓
	Maximum VLANs	Total 255 255 Static 255 Dynamic	Total 255 255 Static 255 Dynamic	Total 255 255 Static 255 Dynamic	Total 255 255 Static 255 Dynamic
Quality of Service (QoS)	802.1p Priority Queues	✓	✓	✓	✓
	Number of Priority Queues	4	4	4	4
	Port-Based QoS	✓	✓	✓	✓
	MAC-Based (DA/SA) QoS	-	-	-	-
Network Access/Security	RADIUS Authentication	✓	✓	✓	✓
	Port Security	✓	✓	✓	✓
	Maximum MAC Entries Per Port	10	10	10	10
	802.1x Port-based Access Control	✓	✓	✓	✓
	802.1x MAC-based Access Control	✓	✓	✓	✓
	Bandwidth Control	✓	✓	✓	✓
	Rate Limit	Under 2MB: 64KB Under 100MB: 1MB Above 100MB: 8MB	Under 2MB: 64KB Under 100MB: 1MB Above 100MB: 8MB	Under 2MB: 64KB Under 100MB: 1MB Above 100MB: 8MB	Under 2MB: 64KB Under 100MB: 1MB Above 100MB: 8MB
Traffic Segmentation	✓	✓	✓	✓	
Management	Single IP for Stack Management	✓*	✓*	✓*	✓*
	D-Link Single IP Management (SIM)	SIM Client	SIM Client	SIM Client	SIM Client
	Web-GUI	✓	✓	✓	✓
	CLI	✓	✓	✓	✓
	Telnet	✓	✓	✓	✓
	TFTP	✓	✓	✓	✓
	SNMP v.1	✓	✓	✓	✓
	SNMP v.2c	✓	✓	✓	✓
	SNMP v.3	✓	✓	✓	✓
	RMON	✓ 4 Groups	✓ 4 Groups	✓ 4 Groups	✓ 4 Groups
	BooP/DHCP Client	✓	✓	✓	✓
	SNTP	✓	✓	✓	✓
	SYSLOG	✓	✓	✓	✓
	Web GUI Traffic Monitoring	✓	✓	✓	✓
Web MAC Address Browsing	✓	✓	✓	✓	
Diagnostic LEDs	Power (Per Device)	✓	✓	✓	✓
	Console (Per Device)	✓	✓	✓	✓
	Link/Activity (Per Port)	✓	✓	✓	✓
	Speed Indicator (Per Port)	✓	✓	✓	✓

* SIM Client is used for stacking with DES-3500, DES-3800 series switches, xStack or DES-6500 chassis embedded with SIM (Single IP Management) Commander v.1.0 or above.

4 Port Densities

Depending on your network size, you can select to deploy a switch with a different port density and size to handle your particular requirement. All switches in the series are completely function-compatible and interoperable.

DES-3010G FOR SMALL WORKGROUP

- 8 10/100Mbps Ethernet Ports
- Copper Gigabit Port
- SFP Gigabit Slot
- RS-232 Console Port
- Desktop Size



DES-3010F FOR SMALL WORKGROUP

- 8 10/100Mbps Ethernet Ports
- Copper Gigabit Port
- Fiber Ethernet Port (SC Connector)
- RS-232 Console Port
- Desktop Size



DES-3018 FORMID-SIZED WORKGROUP

- 16 10/100Mbps Ethernet Ports
- 2 Open Slots for Optional Fiber & Gigabit Uplinks
- RS-232 Console Port
- Rack-Mount Size



DES-3026 FOR LARGE WORKGROUP

- 24 10/100Mbps Ethernet Ports
- 2 Open Slots for Optional Fiber & Gigabit Uplinks
- RS-232 Console Port
- Rack-Mount Size



3 Optional Uplink Modules

3 user-selectable optional uplink modules are available for installation in the open slots of switch models DES-3018 and DES-3026.

DEM-301T COPPER GIGABIT MODULE

- 1 100BASE-T Gigabit Port



DEM-301G SFP GIGABIT MODULE

- 1 SFP Slot



DEM-201F FIBER ETHERNET MODULE

- 1 100BASE-FX Ethernet Port (SC Connector)
- Multi-Mode Fiber Max. 2 km Cable Distance



Physical & Environmental

	DES-3010G	DES-3010F	DES-3018	DES-3026
Power Input	100 to 240 VAC, 50 to 60 Hz Internal Universal Power Supply			
Dimensions	280 (W) x 180 (D) x 44 (H) mm Desktop Size, 1U Height		441 (W) x 207 (D) x 44 (H) mm 19-inch Rack Mount Width, 1U Height	
Operating Temperature	0° to 40°C			
Storage Temperature	-40° to 70°C			
Operating Humidity	5% to 95% non-condensing			
EMI	FCC Class A CE C-Tick VCCI			
Safety	CSA International			



D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Portugal	TEL: 351-21-8688493		Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
Czech Republic	TEL: 420-(603)-276-589		China	TEL: 86-10-58635800	FAX: 86-10-58635799
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902	Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299