


### Overview



- 1. Menu/select:** Opens, selects or exits the OSD menu.
- 2. "-" / Auto:** Navigates backward through the OSD menu and decreases adjustment levels; when the OSD menu is inactive, activates the auto adjustment feature to optimize the screen image.
- 3. "+":** Navigates forward through the OSD menu and increases adjustment levels.
- 4. Power LED:** fully powered = green; sleep mode = amber; sleep timer mode = flashing amber.
- 5. Power:** Turns the monitor on or off.

---

### Model

NK570AA

### Technical Specifications

<b>Panel</b>	<b>Type</b>	19-in (48.14-cm) Wide-Aspect Active Matrix TFT (thin film transistor)
	<b>Viewable Image Area</b> (diagonal)	19 in (48.14 cm) wide (WXGA+); diagonally measured
	<b>Screen Opening</b> (W x H)	16.1 x 10.0 in (40.82 x 25.52 cm)
	<b>Panel Type</b>	TN
	<b>Aspect Ratio</b>	16:10
	<b>Viewing Angle</b> (typical)	Up to 160° horizontal/160° vertical (10:1 minimum contrast ratio)
	<b>Brightness</b> (typical)*	250 nits (cd/m <sup>2</sup> )
	<b>Contrast Ratio</b> (typical)*	1000:1
	<b>Response Time</b> (typical)*	=5 ms (on/off)
	<b>Pixel Pitch</b>	.2835 mm
	<b>Backlight Lamp Life</b> (to half brightness)	50 K hours
	<b>Color Gamut</b>	72%
	<b>Color Support**</b>	Can display up to 16 million colors
	<i>*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. ** With the use of FRC technology.</i>	
<b>On Screen Display (OSD) Controls</b>	<b>Buttons or Switches</b>	Auto adjust/OSD down, OSD UP, OSD menu select, power
	<b>Languages</b>	English, French, German, Spanish, Italian, Dutch, and Japanese, S. Chinese, Portuguese
	<b>User Controls</b>	Brightness, contrast, positioning, color temperature (6500k, 9300k, custom), individual color control, serial number, display, clock, clock phase, monitor management, factory reset, zoom
<b>Signal Interface/ Performance</b>	<b>Horizontal Frequency</b>	24 to 83 kHz
	<b>Vertical Frequency</b>	50 to 76 Hz
	<b>Native Resolution</b>	1440 x 900 @ 60 Hz
	<b>Preset VESA Graphic Modes</b> (non-interlaced)	1280 x 1024 @ 60 Hz
		1280 x 960 @ 60 Hz
		1024 x 768 @ 60 Hz
		800 x 600 @ 60 Hz
		640 x 480 @ 60 Hz
	<b>CVT Mode</b>	1152 x 720 @ 60 Hz
		1280 x 768 @ 60 Hz
	<b>Text Mode</b>	720 x 400 @ 70 Hz
<b>Maximum Pixel Clock Speed</b>	140 MHz (analog input)	
<b>User Programmable Modes</b>	Yes, 15	
<b>Anti-Glare</b>	Yes	

### Technical Specifications

	<b>Anti-Static</b>	No
	<b>Default Color Temperature</b>	6500 K
<b>Video/Other Inputs</b>	<b>Plug and Play</b>	Yes
	<b>Self Powered USB 2.0 Hub</b>	No
	<b>Input Signal</b>	VGA
	<b>Input Impedance</b>	75 ohms ± 10%
	<b>Sync Input</b>	TTL separate synch or Composite Sync
	<b>VGA Cable</b>	15 pin D-sub VGA
	<b>VGA Cable Length</b>	5.9 ft (1.8 m)
<b>Power</b>	<b>Power Supply</b>	Internal power adapter
	<b>Input Power</b>	Auto-Sensing, 90 to 265 VAC
	<b>Frequency</b>	45 to 63 Hz
	<b>Typical Power Consumption</b>	20 watts
	<b>Maximum</b>	23 watts
	<b>Power Saving</b>	< 2 watts standby; 1 watt off
	<b>Power Cable Length</b>	6.2 ft (1.9 m)
<b>Mechanical</b>	<b>Dimensions (H x W x D)</b>	<b>Unpacked w/stand</b> 14.6 x 17.6 x 8.1 in (37.0 x 44.6 x 20.6 cm) <b>Unpacked w/o stand</b> (head only) 11.9 x 17.6 x 2.3 in (30.1 x 44.6 x 5.9 cm) <b>Packaged</b> 17.6 x 20.2 x 5.2 in (44.5 x 51.3 x 13.2 cm)
	<b>Weight</b>	<b>Unpacked</b> 8.96 lb (4.3 kg) <b>Head only</b> 8.8 lb (4.0 kg) <b>Packaged</b> 12.6 lb (5.7 kg)
	<b>Tilt Range</b>	-5° to + 25° vertical
	<b>Swivel Range</b>	No
	<b>Height Adjustable</b>	No
	<b>Pivot Rotation</b>	No
	<b>Base</b>	Detachable, ships attached
<b>Environmental</b>	<b>Temperature – Operating</b>	-29° to 140° F (-34° to 60° C)
	<b>Temperature – Non-operating</b>	-4° to 140° F (-20° to 60° C)
	<b>Humidity – Operating</b>	20% to 80% non-condensing
	<b>Humidity – Non-operating</b>	5% to 95%, 38.7° C max wet-bulb
	<b>Altitude – Operating</b>	+0 to 16,404 ft (5000 m)
	<b>Altitude – Non-operating</b>	+40,000 ft (12,192 m)
<b>Environmental Data</b>	<b>Eco-Label Certifications and Declarations</b>	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> <li>● ENERGY STAR®</li> </ul>

### Technical Specifications

<b>Energy Consumption</b> (in accordance with ENERGY STAR® test method)	<ul style="list-style-type: none"><li>• IT ECO declaration</li><li>• EPEAT™ Silver</li></ul>			
	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	
	Normal Operation	18.42W	18.36W	18.80W
	Sleep	0.52W	0.55W	0.51W
Off	0.45W	0.43W		

<b>Heat Dissipation*</b>	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	
	Normal Operation	63 BTU/hr	63 BTU/hr	64 BTU/hr
	Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr
	Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

<b>Additional Information</b>	<p>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) Directive, 2002/95/EC.</p> <p>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive, 2002/96/EC.</p> <p>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</p> <p>This product is in compliance with the IEEE 1680 (EPEAT) standard at the Silver level, see: <a href="http://www.epeat.net">www.epeat.net</a>.</p> <p>Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</p> <p>Display meets the requirement for low frequency electromagnetic fields per TCO and prEN50279 A/B/C.</p> <p>This product contains 0% post-consumer recycled plastic (by wt.)</p> <p>This product is 93.8% recycle-able when properly disposed of at end of life.</p> <p>Packaging Materials</p> <ul style="list-style-type: none"><li>• External:<ul style="list-style-type: none"><li>○ Polypropylene 28 g</li></ul></li><li>• Internal:<ul style="list-style-type: none"><li>○ PET 74g</li></ul></li></ul>
<b>RoHS Compliance</b>	<p>Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction</p>

### Technical Specifications

#### Material Usage

of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at:

[www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

#### Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.

### Technical Specifications

- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: [www.hp.com/recycle](http://www.hp.com/recycle) or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment: Global Citizenship Report

[www.hp.com/hpinfo/globalcitizenship/gcreport/index.html](http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html)

Eco-label certifications

[www.hp.com/hpinfo/globalcitizenship/environmentproductdesign/ecolabels.html](http://www.hp.com/hpinfo/globalcitizenship/environmentproductdesign/ecolabels.html)

ISO 14001 certificates:

[www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html](http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html)

### Options

#### HP LCD Speaker Bar-Part number NQ576AA

Powered directly by the connected PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP LCD monitors. Features include dual speakers with full sound range and dual external headphone jacks. Sold separately. For more information, refer to the product's QuickSpecs.

#### HP LCD Monitor Quick Release-Part number EM870AA\*

An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.

\* The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

#### HP USB Graphics Adapter-Part number NL571AA

Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.

#### HP Business PC Security Lock Kit-Part number PV606AA

Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.

### Technical Specifications

	<b>HP Integrated Work Center Stand-Part number LH526AA</b>	Allows mounting of a 17 - 24 inch (43.18- to 60.96 cm) diagonal HP LCD monitor and an HP Compaq 8000 series Ultra-slim Desktop PC as well as select HP Thin Clients on a single stand for the convenience of an "all-in-one" form factor. For more information, refer to this product's QuickSpecs document.
	<b>HP Integrated Work Center for Small Form Factor-Part number QK549AT</b>	Allows mounting of a 17- to 24-inch (43.18 to 60.96 cm) diagonal HP LCD monitor with an HP Compaq Small Form Factor Desktop PC. This compact system configuration saves you valuable desktop room to make the most of a space-constrained office environment.
<b>Other</b>	<b>Accessories Included</b>	VGA cable - connects the graphic card's VGA connector to the monitor's VGA input
	<b>Software</b>	HP Display Assistant is a software utility that allows monitor adjustment and color calibration using the Display Data Channel Command Interface (DDC/CI) protocol of the connected PC.  HP Display LiteSaver allows you to schedule Sleep mode at preset times to help protect the monitor against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	<b>User Guide Languages</b>	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	<b>Warranty Languages</b>	English, Canadian French, LA Spanish, Brazilian Portuguese, Danish, German, Castilian Spanish, French, Italian, Dutch, Norwegian, Finnish, Swedish, Bahasa Indonesian, Korean, T. Chinese, S. Chinese
	<b>Color</b>	Black
	<b>VESA External Mounting</b>	Yes, standard 4 hole pattern, 100 mm
	<b>Kensington Lock-Ready</b>	Yes
<b>Certification and Compliance</b>		TCO 5.0 Displays, ISO 9241-307, CISPR Requirements, VCCI Approvals, KC and KCC (Korean) Requirements, CSA 60950-1, UL 60950-1, EN55022 Class B, CNS 13438 Class B, IEC 60950-1, China Energy Label (CEL), China MEPS, Korea MEPS (pending, Energy Boy), SmartWay - NA only - Energy logistics, EUP Lot 6 Tier 1 AS/NZS 3548 Class B Approval, "GS" Mark, TUV Approvals, GEEA, CE Marking, FCC Part 15 class B Approval, ENERGY STAR® qualified, EN55024 Class B, EN60950 -1, CUL, CCIB, CCEE, IT ECO (EDS), EPEAT™ Silver
<b>Compatibility</b>		Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
<b>Service and Warranty</b>		Three years parts, labor, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion.* With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or contact HP Customer Support.  * HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <a href="http://www.hp.com/go/lookuptool">www.hp.com/go/lookuptool</a> . Additional HP Care Pack Services information by product is available at: <a href="http://www.hp.com/hps/carepack">www.hp.com/hps/carepack</a> . Service levels and response times for HP Care Packs may vary depending on your geographic location.

### *Technical Specifications*

© Copyright 2011, 2012 Hewlett-Packard Development Company, L.P.

ENERGY STAR is a US registered mark of the United States Environmental Protection Agency. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.