IN136

The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN136

The InFocus IN136 WXGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

Key Features

- WXGA (1280 x 800) resolution
- TechStation lets you customize your projector with the devices you already use
- Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design





Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless





when not in use, and save even more money over the life of the projector.

Over 1 Billion Colors

BrilliantColor[™] DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free <u>ProjectorNet 4.1 software</u> from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are <u>144Hz DLP Link 3D</u> <u>glasses</u> (sold separately).

Save Energy with Value that Lasts

Quietest Projector in its Class

enclosure, and silent bearings.

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP[®] chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

Make sure students always hear the lessons, not the fans. With

only 21dB in eco mode, IN136 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient



Specifications*

Projector	IN136
Resolution – Native	WXGA (1280 x 800)
Display Technology	DLP
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Eco Mode	3,200 lumens
Lamp Life	5,500 hours
Lamp Life – Low Power	10,000 hours

Lamp Deve 5000 Hours Lamp Dever 245W Lamp Dever 107 Dillon Synch Sam Frequery – Hurbord 35 *728 Hbz Synch Sam Frequery – Hurbord 56 *728 Hbz Synch Sam Frequery – Hurbord 57 *728 Hbz Synch Sam Frequery – Hurbord 57 *728 Hbz Synch Sam Frequery – Hurbord 250 Preliciton Lam F Stop Maximum 267 Lamp Size Maximum 250 in Prejiciton Carro 250 in Connetzor - Inputs 35mm audio Consorts vidos, VGA HDM1 14a 30 oxith 14a 30	Projector	IN136
Jamp Rever 265W Jam Rever Floor Node 70W Calur Mode 28500.1 1000000000000000000000000000000000000		
Lamb New - Eco Mode70WContrast Ratio255001Color MedHgh Speed B Segment RYGCWBNumber of Colors107 bilineSynch Scan Frequery - Horizont55 * 205 KHzSynch Scan Frequery - Horizont55 * 105 KHzAspect Ratio610Aspect Ratio Compatibility43, 169, 2351.11.21, 139, 159, 54Prolection Later FStop - Ministre257Constant Size - Maximum257Constant Size - Maximum257Constant Size - Maximum256 inProjection Later FStop - Ministre256 inConstant Size - Maximum256 inConsectors - Nutry Ratio256 inConsectors - Outputs256 inConsectors - Outputs256 inConsectors - Outputs36m maxile composite vides. WGA, HDM 14a 33 (with 14a 33 support), USPA (TechStation Consectors)Consectors - Outputs256 man audie coupt, Monter out (VGA)Consectors - Outputs250 Bill Consectors, HDM 14a 31 Gormats, DLP Link 33 support), USPA (TechStation Consectors)Consectors - Outputs250 Bill Consectors, HDM 14a 30 Gormats, DLP Link 30 Support, USPA (TechStation Consectors)Consectors - Outputs250 Bill Consectors, HDM 14a 30 Gormats, DLP Link 30 Support, USPA (TechStation Consectors)Consectors - Outputs250 Bill Consectors, HDM 14a 30 Gormats, DLP Link 30 Support, USPA (TechStation Consectors)Consectors - Outputs250 Bill Consectors, HDM 14a 30 Gormats, DLP Link 30 Support, USPA (TechStation Consectors)Power Consectorion - Stated W Bill Consectors, HDM 14a 30 Gormats, DLP Link 30 Support, HDM 14a 30 Gormats, DLP Link 30 Suppo		
Contrast Ratio 285.001 Calor Wheal High Spaced S Segment RVGCWB Number of Colors 107 billion Synch Saan Prequency – Horizontal 31.5 ° 92.6 kt/z Synch Saan Prequency – Horizontal 51.5 ° 92.6 kt/z Aspect Ratio Compatibility 43.169.2 35.1, 12, 13.9, 15.9, 5.4 Projection Lens F Stop – Minimum 250 Projection Lens F Stop – Minimum 250 Projection Lens F Stop – Maximum 250 Projection Correction 407 Connectors – Anguts 35mm audio, Composite video, VGA HDM L4a x3 (with L4a 30 support), USB-A (fichStation Connector) Control Correction 407 Connectors – Culpatis 35mm audio, Composite video, VGA HDM L4a x3 (with L4a 30 support), USB-A (fichStation Connector) Control Correction 407 Control Correction 407 Prover Consumption – Standby Mode 13W max Power Consumption – Low Power Starby 05W max <td></td> <td></td>		
IndexHigh Space IS Segment FVRCWBNumber of Colors167 billionSynch San Frequency – Horizontal157 976 KHzSynch San Frequency – Vertrait65 120 KHzAspent Ratio Compatibility43, 169, 2381, 11, 21, 139, 159, 54Projectio Lans FSop – Minium20Projectio Compatibility4.24 H - 5% VKaystan Cornection36m audio Compatibility CompatibilityCornectors – Joupta's36m audio Compatibility CompatibilityCornectors – Dutpatis36m audio Compatibility CompatibilityAddible Accessories9.0000 KLRAddible Accessories9.0000 KLROstrophone30.0000 MaxProver Consumption – Exor Mode9.5000 KLROstrophone5.0000 KLRProver Consumption – Exor Mode9.5000 KLRProver Consumption – Exor Mode <td>•</td> <td></td>	•	
Number of Colors 107 Nilion Synch Scan Frequency - Merizantal 315° 976 KHz Synch Scan Frequency - Merizantal 151° 976 KHz Aspect Ratic Compatibility 43, 169, 2351, 11, 21, 139, 159, 54 Projection Lens F-Stop - Maximum 250 Projection Lens F-Stop - Maximum 250 Image Size - Minimum 251 Image Size - Maximum 256 in Projection Lens F-Stop - Maximum 256 in Projection Clens - Stop - Maximum 256 in Projection Clens - Maximum 256 in Projection Offset 112,44' - 55 V Keystone Correction 40'V Connectors - Duptus 35mm audio composite videa, VGA, HDM 14a, 33 (syith 14a, 30 support), USB-A (TechStation Connection) Connectors - Duptus 35mm audio output, Monter out (VGA) Control Keystone Correction Prower Consumption 1000,00 w max Power Consumption 1000,00 w max Power Consumption - Exandbay Mode 189 w max Power Consumption - Exandbay Mode 200,00 w max Power Consumption - Exandbay Mode 200,00 w max Power Osmauntein		
Synch Scan Frequency - Harizental 315 1276 KHz Synch Scan Frequency - Wartial 56 120 KHz Aspect Ratio Compatibility 43, 169, 2351, 11, 21, 139, 159, 54 Projection Lens FStop - Minium 260 Projection Lens FStop - Minium 261 Lans Type Manual focus Image Size - Minium 28 in Projection Offstop 12 kM + 58 V Keystop Correction 295 in Projection Offstop 35mm audio, Composite video, VGA, HOMI 14a, 33 (with 14a 30 support), USB A (TechStation Connection) Connectors - Inputs 35mm audio, antput, Monitor out (VGA) Connectors - Inputs 35mm audio, antput, Monitor out (VGA) Connectors - Conputs 20 (BA or Off -/ 128°C Include Accessories Power Consumption JD Support 1000 W max Power Consumption - Low Rowed 20 (OW max Power Consumption - Standby Mode 12 W - 150 W CM Power Consumption - Standby Mode 12 W - 150 W CM Power Consumption - Standby Mode 120 W anx Power Consumption - Standby Mode 120 W anx Power Consumption - Standby Mode 120 W anx		
Synch Scan Frequency - Vertical 56 · 120 KHz Aspect Ratio 15:10 Aspect Ratio Compatibility 43, 169, 2.35 · 1, 12, 139, 159, 54 Projection Lens F.Sop - Minimum 250 Projection Lens F.Sop - Minimum 250 Lans Type Manual focus Image Size - Minimum 23 in Image Size - Minimum 23 in Projection Driss 35m - Minimum Projection Offset 112,44 · 58 v Keystone Correction 40° v Connectors - Inputs 35mm audio, Composite video, VGA, HDMI 14a, v3 (with 14a, 30 support), USP-A (TechStation Connector) Connectors - Loquizs 35mm audio, Composite video, VGA, HDMI 14a, v3 (with 14a, 30 support), USP-A (TechStation Connector) Connectors - Loquizs 35mm audio, Composite video, VGA, HDMI 14a, v3 (with 14a, 30 support), USP-A (TechStation Connector) Connectors - Loquizs 35mm audio, Composite video, VGA, HDMI 14a, v3 (with 14a, 30 support), USP-A (TechStation Connector) Connectors - Loquizs 35mm audio, Composite video, VGA, HDMI 14a, v3 (with 14a, 30 support), USP-A (TechStation Connector) Dologin & Col-L, HAR & O' B (Table, Documentation, USer Manual (CD) 3000W max Power Cossanghion - Statio W Mode 41 to 1047 at O' to		
Aspect Ratio 16/0 Aspect Ratio Constibility 43, 169, 2,351, 11, 21, 13, 159, 54, 54, 54 Projection Lans F.Stop – Minimum 250 Projection Lans F.Stop – Maximum 257 Lens Type Manual focus Image Size – Maximum 256 in Projection Offsat 12,4% - 5% V Keystone Correction 4,07 V Connectors - Dutputs 3,5m madio curput, Manior out (VGA) Connectors - Dutputs 3,5m madio curput, Manior out (VGA) Connectors - Dutputs 4,07 P / 120° Include Accessories 9,892,31 R Renote Audible Noise - Eco Mode < 21 dBA a 10° / 120°		
Aspect Ratio Compatibility 43, 169, 2, 351, 11, 21, 139, 159, 54 Projection Line F-Stop – Minimum 2.60 Projection Line F-Stop – Minimum 2.67 Line Type Manual locus Image Size – Minimum 256 in Image Size – Minimum 256 in Projection Offset 112.44 + 58 V Keystone Correction 4.67 V Connectors – Inputs 3.5mm audio, Composite videe, VGA, HDM 1.4a x3 (with 1.4a 3D support), USB A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite videe, VGA, HDM 1.4a x3 (with 1.4a 3D support), USB A (TechStation Connection) Connectors – Outputs 3.5mm audio duptut, Moniter out (VGA) Control RS232, IR Remote Auditib Nolice – Eca Mode < 21 dBA at 0F / 173 °C		
Projection Lens F-Stop – Maximum 250 Projection Lens Fybe Amaul focus Image Size – Maximum 23 in Image Size – Maximum 25 in Projection Offset 12.4% + 5% V Kaystane Correction 24 OP Connectors – Inpuds 35mm audio composite video, VGA, HDM114a x3 (with 14a 3D support), USB A (TechStation Connection) Connectors – Outputs 35mm audio composite video, VGA, HDM114a x3 (with 14a 3D support), USB A (TechStation Connection) Connectors – Outputs 35mm audio composite video, VGA, HDM114a x3 (with 14a 3D support), USB A (TechStation Connection) Connectors – Outputs 35mm audio composite video, VGA, HDM114a x3 (with 14a 3D support), USB A (TechStation Connection) Power Consumption – Standby Mode 85232, IR Remote Audible Noise – Eco Mode 200.0W max Power Consumption – Standby Mode 18W max Power Consumption – Standby Mode 18W max Power Consumption – Eco Mode 200.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions Fordits, French, German, Sparish, Halian, Norvegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Prinziah, Polian, Tercho, German, Sparish, Halian, Norvegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Prinziah, Makay		
Projection Lens F-Stop - Maximum 2.67 Lens Type Manual focus Image Size - Maximum 23 in Image Size - Maximum 256 in Projection Offsat 112.45 + 58 V Keystone Correction ± 40°V Connectors - Inputs 3.5mm audio contputs ivides, VGA, HDM1 14a x3 (with 14a 3D support), USB-A (TechStation Connection) Control S.5mm audio contputs ivides, VGA, HDM1 14a x3 (with 14a 3D support), USB-A (TechStation Connection) Control RS232 JR Remote Audialis Noise - Eco Made < 21 dBA at 0°F / 128°C		
Leris TypeManual focusImage Size – Minimum23 inImage Size – Minimum25 inProjection Offset12.4X + 5X VKeyston Correction± 40VConnectors – Inputs3.5mm audio composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Connectors – Dutputs3.5mm audio composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Connectors – Dutputs3.5mm audio composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Connectors – Dutputs3.5mm audio composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Connectors – Dutputs3.5mm audio composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Connectors – Dutputs3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection)Dower Consumption10.900 (PGA 2H) HDMI 14a 3D formats, DLP Link 3D glasses requiredPower Consumption – Low Power Standby0.5W maxPower Consumption – Low Power Commentation, Norvegian, Dutch, Simp		
Image Size – Maximum 23 in Image Size – Maximum 256 in Projection Offset 112.4% – 5% V Ksystone Correction ± 40°V Connectors – Inputs 35mm audio, Composite video, VGA, HDM114a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 35mm audio output, Monitor out (VGA) Control R5232, IR Remote Audia Holise – Eco Mode < 21 dBA at 0°T / 178°C		
Image Size - Maximum 256 in Projection Offset 1124% + 5% V Keystone Correction 4 dVV Connectors - Inputs 35mm aucio, Composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (FechStation Connection) Connectors - Outputs 35mm aucio, Composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (FechStation Connection) Aucible Noise - Eco Mode 521 dBA at 07F / 737C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 10800 g6 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required Power Consumption - Standby Mode 18W max Power Consumption - Low Power Standby 0.SW max Power Consumption - Low Power Standby 0.SW max Power Consumption - Eco Mode 20.0W max Power Consumption - Eco Mode 20.0W max Power Consumption - Eco Mode 20.0W max Power Standard Act 100 to 2040, 50/60 Operating Conditions English, French, German, Spanish, Italian, Norvegian, Dutch, Simplified Chinese, Karean, Swaish, Talian, Norvegian, Dutch, Simplified Chinese, Karean, Swaish, Talian, Norvegian, Dutch, Simplified Chinese, Karean, Neusgian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vetnamese, Czech, Romanian, Hungarian, Mala, Hindi, Filinine, Farsi, Japa		
Projection Difset 112.4% + 5% V Keystone Correction 4 dVV Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI L4a x3 (with 1.4a 3D support), USB A (TechStation Connection) Connectors - Outputs 3.5mm audio coutput, Monitor out (VGA) Control R5232, IR Remote Audible Noise - Eco Mode <21 dBa L4 CF / -T3C C	-	
Keystone Correction $\pm 40^{V}$ Connectors - Inputs3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a D3 support), USB-A (TechStation Connection)Connectors - Outputs3.5mm audio output, Monitor out (VGA)ControlRS232, IR RemoteAudible Noise - Eco Mode< 21 dBA at 0°F / 173°C		
Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control R5232, IR Remote Audible Noise - Eco Mode < 21 dBA at 0°F / 178°C	•	
Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise - Eco Mode < 21 dBA at 0°F / 178°C	•	
Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at OF / 17.8°C		
Audible Noise - Eco Mode< 21 dBA at 0°F / 178°CIncluded AccessoriesPower cord, Remote, HDMI Cable, Documentation, User Manual (CD)3D Support1080p @ 60Hz. All HDMI 1Aa 3D formats, DLP Link 3D glasses requiredPower Consumption300.0W maxPower Consumption - Standby Mode18W maxPower Consumption - Low Power Standby0.5W maxPower Consumption - Low Power Standby0.5W maxPower Consumption - Eco Mode220.0W maxPower StandardAC 100 to 240V, 50/60Operating Conditions5 to 40°C at 0 to 3048 mPower StandardAC 100 to 240V, 50/60Operating Conditions5 to 40°C at 0 to 3048 mPower StandardConsumption - Eco ModePower Consumption - Eco ModeEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, PortuguesePower Consumption - Standby ModeEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hundi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTrov Mato10 mThrow Distance - Minimum1 mThrow Bitsnee - Minimum1 mThrow Ratio - Minimum154:1Throw Ratio - Maximum10 mThrow Ratio - Maximum10 mThrow Ratio - Maximum154:1Throw Ratio - Maximum10 mThrow Ratio - Maximum10 mThrow Ratio - Maximum124.5 x 236.2 x 312.3 in / 124.5 x 236.2 x 312.4		
Included AccessoriesPower cord, Remote, HDMI Cable, Documentation, User Manual (CD)3D Support1080p @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses requiredPower Consumption300.0W maxPower Consumption – Low Power Standby0.5W maxPower Consumption – Low Power Standby0.5W maxPower Consumption – Low Power Standby0.5W maxPower Consumption – Eco Mode220.0W maxDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, Anabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Distance – Maximum124.1Throw Ratio – Minimum1 %49.2.9.3.x12.3 in /Throw Ratio – Maximum124.1Product Dimensions49.2.9.3.x12.3 in /For		
3D Support 1080p @ 60Hz, All HDM1 14a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption - Standby Mode 18W max Power Consumption - Standby Mode 20.0W max Power Consumption - Low Power Standby 0.5W max Power Consumption - Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 1 to 104F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Ortuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filpino, Farsi, Japanese, Thai Security Features Kensington lock port Trow Stance - Minimum Im Throw Distance - Minimum Im Throw Ratio - Minimum 154:1 Throw Distance - Maximum 10 m Throw Ratio - Minimum 154:1 Throw Ratio - Minimum 154:1 <tr< td=""><td></td><td></td></tr<>		
Power Consumption300.0W maxPower Consumption – Standby Mode1.8W maxPower Consumption – Low Power Standby0.5W maxPower Consumption – Low Power Standby0.5W maxPower Consumption – Eco Mode220.0W maxPower StandardAC 100 to 240V, 50/60Operating Conditions41 to 104F at 0 to 10000 f / 5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portThrow And ZoonWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Ratio – Minimum1 mThrow Ratio – Maximum10 mThrow Ratio – Maximum122.1Product Dimensions49 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight71 lbs / 32.8 kgShipping Dimensions77 x 13.3 x 157 in / 156 k 337.8 x 398.8 mm		
Power Consumption - Standby Mode1.8W maxPower Consumption - Low Power Standby0.5W maxPower Consumption - Eco Mode220.0W maxPower StandardAC 100 to 240V, 50/60Operating Conditions1 to 104T at 0 to 10000 ft / 5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, Arabic, Indonesian, Portuguese, Nenu LanguagesMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Mlay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTrech StationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus With Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus With Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Askus With Google Chromecast, Stick and Chromecast,		
Power Consumption – Low Power Standby0.5W maxPower Consumption – Eco Mode220.0W maxPower StandardAC 100 to 240V, 50/60Operating Conditionsd' to 104° at 0 to 10000 ft / 5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Maximum1.54:1Throw Ratio – Maximum1.54:1Throw Ratio – Maximum4.9 × 9.3 × 12.3 in / 12.45 × 236.2 × 312.4 mmProduct Dimensions4.9 × 9.3 × 12.3 in / 12.45 × 236.2 × 312.4 mmProduct Weight7.1 ks / 3.2 kg 3.7 × 13.3 × 15.7 in / 19.56 × 3378 × 398.8 mm		
Power Consumption – Eco Mode220.0W maxPower StandardAC 100 to 240V, 50/60Operating Conditions41 to 104'F at 0 to 10000 ft / 5 to 40'C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum154:1Throw Ratio – Maximum154:1Product Dimensions49 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mmProduct Weight7.1 Iso 3.2 kgShipping Dimensions77 × 13.3 × 157 in / 195.6 × 3378 × 398.8 mm		
Power StandardAC 100 to 240V, 50/60Operating Conditions41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Maximum1.54:1Throw Ratio – Maximum1.54:1Throw Ratio – Maximum4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions4.9 x 9.3 x 12.3 in / 195.6 x 337.8 x 398.8 mm		
Operating Conditions41 to 104'F at 0 to 10000 ft / \$ to 40'C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Mungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portThrow Ad ZoonVorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum10 mThrow Ratio – Minimum154.1Throw Ratio – Maximum10.21.1ShippingYengla, Yang, Yan	•	
Operating Conditions5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Menu LanguagesMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow ad ZoomInThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.54:1Orbut Veight1.41 × 23.6.2 × 312.4 mmProduct Weight7.11 ks / 3.2 kgShipping Dimensions7.7 × 1.33 × 15.7 in / 195.6 × 337.8 × 398.8 mm	i ower Standard	
Documentation LanguagesFinnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and Zoom1Throw Distance – Minimum1 mThrow Distance – Maximum10 m1.54:11.54:1Throw Ratio – Maximum1.72:1Shipping49 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 19.5.6 x 337.8 x 398.8 mm	Operating Conditions	
Menu LanguagesRussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomInThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Maximum1.54:1Throw Ratio – Maximum1.54:1Product Dimensions49 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Documentation Languages	
TechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomImmediate Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1ShippingImmediate – State Pro Dongle and Other HDMI devicesProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Menu Languages	Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian,
Iternstation Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Innov Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 19.6 x 337.8 x 398.8 mm	Security Features	Kensington lock port
Throw Distance - Minimum 1 m Throw Distance - Maximum 10 m Throw Ratio - Minimum 1.54:1 Throw Ratio - Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	TechStation	
Throw Distance - Maximum 10 m Throw Ratio - Minimum 1.54:1 Throw Ratio - Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw and Zoom	
Throw Distance - Maximum 10 m Throw Ratio - Minimum 1.54:1 Throw Ratio - Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Minimum	1 m
Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm		
Throw Ratio – Maximum 1.72:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Minimum	
Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm		
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm		
Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm		
Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Weight	
Shipping Dimensions 195.6 x 337.8 x 398.8 mm	רוטעענו אפונו	-
Shipping Weight9.9 lbs / 4.5 kg	Shipping Dimensions	
	Shipping Weight	9.9 lbs / 4.5 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1) Universal Projector Ceiling Mount (PRJ-MNT-UNIV) 1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1) DLP Link 3D Glasses by XPAND (X103-EDUX3-R1) Soft Carry Case for Value Projectors (CA-SOFTVAL-2) SimpleShare (INA-SIMS1) SimpleShare Touch Presentation System (INA-SIMINT1) SimpleShare Transmitter (INA-SIMTM1) SimpleShare Receiver (INA-SIMRC1) SimpleShare Transmitter with Paired USB Touch Adapter (INA-SIMTTM1) SimpleShare Interactive Receiver (INA-SIMRINT1) SimpleShare Charging Station (INA-SIMCH1) LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+) 2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)