IN134



The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN134

The InFocus IN134 XGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

Key Features

- ♦ XGA (1024 x 768) resolution
- TechStation lets you customize your projector with the devices you already use
- Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design















Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless



projector.

Over 1 Billion Colors

BrilliantColor™ DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

when not in use, and save even more money over the life of the

Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free ProjectorNet 4.1 software from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -- including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).

Save Energy with Value that Lasts

Quietest Projector in its Class

enclosure, and silent bearings.

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP* chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

Make sure students always hear the lessons, not the fans. With

only 21dB in eco mode, IN134 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient



Specifications*

Projector	IN134
Resolution – Native	XGA (1024 x 768)
Display Technology	DLP
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Eco Mode	3,200 lumens
Lamp Life	5,500 hours
Lamp Life – Low Power	10,000 hours

Projection Lens F-Stop — Maximum 2.53	Projector	IN134
Lamp Power — Eco Mede 155W Contrast Raini 28,500.1 Contrast Raini 107 billion Number of Colors 117 billion Synch Scan Frequency — Horizontal 315 **96 kHz Synch Scan Frequency — Vertical 56 **120 kHz Aspect Ratio Compatibility 163, 1610, 2,354, kt, 24, 139, 159, 54 Projection Lens F Stop — Maximum 241 Projection Lens F Stop — Maximum 243 Lens Tyoe Marual focus Image Size — Maximum 244 in Projection Construction 154 ** 58 V Keystone Correction 145 ** 58 V Keystone Correction 4 40°V Connectors — Outputs 3.5mm audio, composite videa, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB A (TachStation Connection) Connectors — Outputs 3.5mm audio subput, Monitor out (VGA) Connectors — Outputs 3.5mm audio subput, Monitor out (VGA) Controll RS282, IR Remote Audition Notice — Eco Mode 2 12 Mart DF 7-7B°C Included Accessories Power cond, Bemote, HDM1 Cable, Documentation, User Manual (ED) 30 Support 1600 pc 60Hz, All DM11 4.a 3D formats, DLP Link 3D	Lamp Life – Dynamic Mode	15,000 hours
Central Ratio 28,5001 Cofor Wheel High Speed & Segment RYGCWB Number of Edoles 1,07 billion Synch Scan Frequency – Horzontal 31,5 ° 97,6 kHz Synch Scan Frequency – Vertral 56 - 120 kHz Aspect Ratio Compatibility 169, 1610, 2,351, 11, 21, 13.9, 15.9, 5.4 Projection Lens F Stop – Minimum 2.41 Projection Lens FStop – Minimum 2.52 Lens Type Manual focus Image Size – Minimum 2.2 in	Lamp Power	220W
Color Wheel High Speed 6 Segment RYGCWB Number of Colors 1.07 billion Swnch Stan Frequency – Horizontal 31.5" 976 KHz Synch Stan Frequency – Vertical 56 - 120 KHz Aspect Ratio 43 Aspect Ratio Compatibility 169, 18:10, 2,351, tt, 2:1, 13:9, 15:9, 5:4 Projection Lens F Stop – Minimum 2.41 Projection Lens F Stop – Maximum 2.43 Lens Type Manual focus Image Size – Maximum 2.41 in Projection Offset 115% + 5% V Keystone Correction 1.40 V Connectors – Guptar 3.5mm audio Loupensite video, VEGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TachStation Connection) Connectors – Outputs 3.5mm audio Loupensite video, VEGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TachStation Connection) Control RSS-23, IR Remote 2.40 V Authority of Land 4.21 Remote 4.21 Remote Authority of Land 4.21 Remote 4.21 Remote Power Consumption – Eco Mode 2.21 Remote 4.20 Remote 4.21 Remote Power Consumption – Sandaly Mode 1.8W max 4.22 Remote 4.22 Remote </td <td>Lamp Power – Eco Mode</td> <td>145W</td>	Lamp Power – Eco Mode	145W
Number of Coters 107 billion 107 billi	Contrast Ratio	28,500:1
Synch Scan Frequency – Horizontal 31.5 ° 978 KHz Synch Scan Frequency – Vertical 56 · 120 KHz Aspect Ratio Compatibility 169.9 1610, 2.351, 1:1, 2:1, 139, 15-9, 54 Projection Lens F-Stop – Maximum 2.41 Projection Lens F-Stop – Maximum 2.53 Lens Type Manual focus Image Size – Maximum 24 in Projection Offse 115% + 5% V Keystone Correction 4 40°V Connectors – Dutputs 3.5mm audio output, Monitor out (VGA) Connectors – Dutputs 3.5mm audio output, Monitor out (VGA) Control 85.232, IR Remote Control 85.232, IR Remote Included Accessories Power roard, Remote, LBMI (Cable, Documentation, User Manual (CD) 30 Support 1080, © 80 Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 18W max Power Consumption – Ece Mode 2.00 W max Power Consumption – Ece Mode 2.00 W max Power Standard AC 100 to 240Y, 50/60 Oberating Consistions 41 to 10.4°F at 0 to 100000 ft / 5 to 40°C at 0 to 50.48 m Power Standby Ac 100 to	Color Wheel	High Speed 6 Segment RYGCWB
Synch Scan Frequency - Vertical 56 - 120 KHz Aspeck Ratio 43 Aspeck Ratio Compatibility 16-9, 16:10, 2-35:1, 1:1, 2:1, 13:9, 15:9, 5:4 Projection Lens F-Stop - Minimum 2.41 Projection Lens F-Stop - Maximum 2.53 Lens Type Manual focus Image Size - Minimum 22 in Image Size - Maximum 244 in Projection Offset 155.4 × 55.V Keystone Correction 1 407V Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Operating Conditions 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Operating Conditions 4.10 to 0.4 to 0.4 to 0.4 to 0.4 to 0.4 to 0.4	Number of Colors	1.07 billion
Aspect Ratio 4.3 Aspect Ratio Compatibility 16:9, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4 Projection Lens F-Stop - Minimum 2.53 Lens Type	Synch Scan Frequency – Horizontal	31.5 ~ 97.6 KHz
Aspect Ratio Compatibility 16.9, 16.10, 2.351, 11, 2.1, 13.9, 15.9, 5.4 Projection Lens F-Stop – Mainium 2.41 Lens Type Manual focus Image Size – Maximum 224 in Projection Diffset 115% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Output, Monitor out (VGA) Control RS223, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 128°C	Synch Scan Frequency – Vertical	56 - 120 KHz
Projection Lens F-Stop – Minimum 2.41 Projection Lens F-Stop – Maximum 2.53 Lens Type Manual focus Image Size – Minimum 2.2 in Image Size – Minimum 2.44 in Projection Offset 115% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), US8-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control 85232, IR Remote Audible Noise – Eco Mode 4.21 dBA at 07 t-7.8°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) Support 1080pg 6 GHz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 4.20 to 0 to 240V, 50/60 Operating Conditions 4.1 to 104° at 0 to 100000 ft / 5 to 40° c at 0 to 30.48 m Documentation Languages English, Franch, German, Spanish, Italian, Norvegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Crech, Romanian, Hungarian, Malay, Hindt, Filipine, Franci, Japanese, Thai </td <td>Aspect Ratio</td> <td>4:3</td>	Aspect Ratio	4:3
Projection Lens F-Stop — Maximum 2.53	Aspect Ratio Compatibility	16:9, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Lens Type Manual focus Image Size – Minimum 22 in Image Size – Maximum 244 in Projection Offset 115% + 5% V Keystanc Correction ± 40°V Connectors – Inputs 3.5mm audio coutout, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 17.8°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 1080 p@ 60.Pt., All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.00 max Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 2.00 W max Power Consumption – Eco Mode 2.00 W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104° at 0 to 300.80 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Tirowa Ratao – Minimum 1 m Throw Distance – Mi	Projection Lens F-Stop – Minimum	2.41
Image Size – Miximum 224 in Image Size – Maximum 224 in Image Size – Maximum 115% + 5% V Keystone Correction 4 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / +178°C	Projection Lens F-Stop – Maximum	2.53
Image Size − Maximum 244 in Projection Offset 115% + 5% V Keystone Cornectors ± 40°V Connectors − Inputs 3.5mm audio. Ocmposite video, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors − Outputs 3.5mm audio output, Monitor out (VGA) Control 8.5323, IR Remote Audible Noise − Eco Mode < 21 dBA at 0°F / -17.8°C	Lens Type	Manual focus
Projection Offset 115% + 5% V Keystone Correction ± 40°V Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise - Eco Mode < 21 dBA at OTF / 178°C	Image Size – Minimum	22 in
Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at O°F / 178°C	Image Size – Maximum	244 in
Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 178°C	Projection Offset	115% +- 5% V
Connectors — Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise — Eco Mode < 21 dBA at O°F / 17.8°C	Keystone Correction	± 40°V
Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 17.8°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080p @ 60Hz, All HDM1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby Mode 1.8W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104° F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Parbic, Indonesian, Portruguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Flinnish, Polish, Turkish, Danish, Arabic, Indonesian, Portruguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hind, Flitipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast. Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance — Minimum 1 m Throw Ratio — Minimum 1 seq. 1	Connectors – Inputs	3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)
Audible Noise – Eco Mode < 21 dBA at 0°F / 17.8°C	Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080 p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption Standby Mode 18W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard Ac 100 to 240V, 50/60 Operating Conditions 4t to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Finnish, Portuguese Finnish, Arabic, Indonesian, Portuguese Finnish, Arabic, Indonesian, Portuguese Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Throw Distance — Maximum 1 m 1 m 1.94:1 Throw Ratio — Minimum 1 p94:1 Throw Ratio — Maximum 1 p34:1 x 1.8 x 236.2 x 312.4 mm Product Weight 7, 118 x 237.8 x 398.8 mm Shipping Dimensions 1 p30.00 m ax 200.00 m ax 200	Control	RS232, IR Remote
3D Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104° at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Minimum 1 m Throw Distance – Maximum 1 p.41 Throw Ratio – Maximum 1.941 Throw Ratio – Maximum 1.941 Throw Ratio – Maximum 1.942 × 3.3 × 3.12.3 in / 12.45 × 236.2 × 312.4 mm	Audible Noise – Eco Mode	< 21 dBA at 0°F / -17.8°C
Power Consumption	Included Accessories	Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)
Power Consumption – Standby Mode Power Consumption – Low Power Standby Power Consumption – Low Power Standby Power Consumption – Eco Mode Power Standard Oct 100 to 240V. 50/60 Operating Conditions Operating Conditions Ocumentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Assuchromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m 1 m 1 m 1 m 1 m 1 m 1 m 1 m 1 m 1	3D Support	1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Power Consumption – Low Power Standby Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions Sto 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 1 2 m Throw Ratio – Maximum 1 2.16:1 Throw Ratio – Maximum 2 .16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption	300.0W max
Power Consumption — Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions \$\frac{1}{2}\text{ to 1040V} \text{ to 100000 ft / 5 to 40°C at 0 to 3048 m}\$ Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance — Maximum 1 m Throw Distance — Maximum 1.94:1 Throw Ratio — Maximum 2.16:1 Shipping Product Dimensions 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 × 13.3 × 15.7 in / 195.6 × 337.8 × 398.8 mm	Power Consumption – Standby Mode	1.8W max
Power Standard AC 100 to 240V, 50/60 Operating Conditions 31 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Ratio – Minimum 1 2 m Throw Ratio – Maximum 1 2.46:1 Throw Ratio – Maximum 2 1.94:1 Throw Ratio – Maximum 3 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Dimensions 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 5 This / 3.3 × 15.7 in / 195.6 × 337.8 × 398.8 mm	Power Consumption – Low Power Standby	0.5W max
Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Maximum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Eco Mode	220.0W max
Decumentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Standard	AC 100 to 240V, 50/60
Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 12.4.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Operating Conditions	
Menu Languages Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Documentation Languages	
TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Menu Languages	Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian,
Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Security Features	Kensington lock port
Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	TechStation	
Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw and Zoom	
Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Minimum	1 m
Throw Ratio – Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Maximum	12 m
Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Minimum	1.94:1
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Maximum	2.16:1
Product Dimensions 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Shipping	
7.7 x 13.3 x 15.7 in / Shipping Dimensions 195.6 x 337.8 x 398.8 mm	Product Dimensions	
Shipping Dimensions 195.6 x 337.8 x 398.8 mm	Product Weight	7.1 lbs / 3.2 kg
	Shipping Dimensions	7.7 x 13.3 x 15.7 in /
	Shipping Weight	9.9 lbs / 4.5 kg

 $^{^{\}ast}$ Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1)
Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)

SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare Transmitter (INA-SIMTM1)

SimpleShare Receiver (INA-SIMRC1)

SimpleShare Transmitter with Paired USB Touch Adapter (INA-SIMTTM1)

SimpleShare Interactive Receiver (INA-SIMRINT1)

SimpleShare Charging Station (INA-SIMCH1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)