

DIGITUS Industrial 4 Port Fast Ethernet PoE Switch, Unmanaged, 1 Uplink

DN-650107
EAN 4016032458852



Industrial 4-port Fast Ethernet PoE Switch 1 uplink port, DIN rail, extend. temp. range

The DIGITUS® Industrial Fast Ethernet Switch is designed for harsh environments where it is exposed to moisture, temperature fluctuations and vibration. With a temperature range of -40°C to 85°C, the Industrial Fast Ethernet Switch can be used under the most adverse conditions. The PoE ports with IEEE802.3af/at support can supply PoE capable devices with up to 30 W per port. It ensures a constant availability in highly sensitive areas such as transport, production, traffic and safety monitoring. The simple plug and play system allows the Industrial Fast Ethernet Switch to be quickly integrated into the respective environment. With its Fast Ethernet connectivity, the Industrial Fast Ethernet Switch is a flexible, cost-effective solution for the industrial environment.

Robust and durable industrial solutions with integrated Power over Ethernet (PoE) function

- 4 x 10/100Base-TX Ethernet PoE Ports
- 1 x 10/100Base-TX Ethernet uplink port
- Supports IEEE802.3af/at
- Automatic cable detection - Auto MDI / MDI-X function
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE802.3af, IEEE802.3at
- IEEE802.3x Flow Control und Back Pressure
- Store and forward technology for optimized data transfer
- Automatic speed and half/full duplex recognition/adjustment
- Backplane with 1Gbps

- Supports up to 2K MAC addresses
- Compact, robust metal housing
- Excellent short-circuit protection
- Lightning and overvoltage protection
- DIN rail (top-hat rail) and wall mounting possible
- Redundant power supply: 48-57 V DC, redundant power supply with reverse polarity protection function
- Extended operating temperature range, -40 °C ~ +85 °C
- Removable terminal connection
- Protection class: IP40
- Ethernet speed: Fast Ethernet
- Industrial usage: yes
- Number of ports: 4
- PoE (Power over Ethernet): yes
- Protection against vanadism: no
- Managed: no
- Installation type: DIN rail
- Outdoorsuitable: no
- Number of ports (Uplink): 1
- Uplink port connection: RJ45
- VLAN: no
- VLAN: no
- PoE standard: IEEE802.3at (PoE+)

Package contents

- Industrial 4-Port Fast Ethernet PoE Switch + 1 uplink port
- quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	72	34.80	46.00	64.50	36.00	106,812.00
Packaging Unit Inside	1	0.48	13.50	16.20	5.30	1,159.11
Packaging Unit Single	1	0.48	13.50	16.20	5.30	1,159.11
Net single without Packaging	1	0.40	13.50	16.20	5.30	1,159.11