Overview

Models

HP 7500 SSL VPN Module with 500-user License

Key features

- High performance hardware encryption
- Thin client and browser based access
- Multiple access authentication methods
- Remote security status checking
- Low Running Cost

Product overview

HP SSL VPN modules enable SSL VPN gateways to be established directly in an HP networking infrastructure, as part of chassis switches and router. Equipped with high-performance multi-core processors and embedded hardware encryption acceleration engines, these modules support high throughput and over 600K concurrent SSL VPN connections. With SSL VPN functionality, end users will benefit from remote file access, client/server applications running over either TCP or UDP, granular access rights and policy management capabilities, as well as dynamic user authorization based a number of authentication mechanisms. Through integration with the modular networking platforms, the modules provide an easy to deploy and manage remote access solution for medium to large organizations.

Features and benefits

Application highlights

- High performance hardware encryption: Use a multi-core processor with built-in encryption accelerators, which greatly increases the volume of SSL VPN traffic and the number of connections, ensuring adequate performance for enterprise requirements
- Thin client and browser based access: SSL VPN supports a Web access mode which requires no VPN client installation on the user side; remote users access network resources through a regular Web browser.
- Security assessment of remote hosts: SSL VPN module automatically checks the status of the endpoint device, including its operating environment, browser version, anti-virus system, installed patches, and required files and applications. This security status is feedback to the gateway, which will then authorize the user and endpoint according to the security policies of the organization; this effectively prevents infected mobile devices from contaminating the internal network.
- Multiple access authentication methods: provides multiple popular authentication and external authorization platforms including local authentication, RADIUS, LDAP, AD, RSA SecurID, and third-party PKI authentication. Supporting authentication, authorization, and management of different users
- Dynamic authorization and security policies: Support differing access control policies based on the URL connected to the gateway, the IP address and the port number requested, or the IP network segment accessed.Policies can also be applied based on user identity or the security posture of the remote device
- Support for CLIENT/SERVER applications: SSL VPN supports client-server applications by enabling the gateway to act as the proxy to terminate the SSL connection from the client and establish a TCP/UDP connection with the internal server. The VPN gateway then forwards packets to the server, ensuring only compliant connections are passed through. This port-forwarding technology provides better network security than similar IPSec VPN technology.
- Support for IP layer based applications: To support more IP-based network applications, SSL VPN modules assign a temporary IP address to the remote device via an IP access client program. The remote device will then be connected with the internal network at the IP layer, as if they were in the same LAN. Through this way, the SSL VPN modules support granular policies; they can restrict which IP network segments can be accessed by users, further reducing the security risks involved with



JD253A

Overview

remote user

Warranty and support

- 1-year warranty: with advance replacement and 10-calendar-day delivery (available in most countries)
- Electronic and telephone support: limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- Software releases: to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary



Technical Specifications

Module with 500-user License (JD253A) Physical characteristics Dimensions 14.84(d) x 15.71(w) x 1.57(h) in. (37.7 x 39.9 x 4 cm) (1U height) Weight 7.05 lb. (2.3 kg) Memory and Processor 22.DD82 SDRAM; packet buffer size: 64 M8 flash Performance Throughput up to 2 Gbps Concurrent sassions 60000 Number of users 10000 Number of users 10000 Number of users 10000 Performance Oparating relative Invitight 32?F to 104*F (0°C to 40°C) Oparating relative 10% to 90%, noncondensing homidity Velo Boroser - Hitip protocol - Web proxy Performance desktop share - UNIC remote desktop share - UNIC remote desktop share - Outlook - Notes - Roonect by route - Redites dwodes dwode - Rearter - Redites dwodes dwodes dwodes dwode - Redite aupport VINS Service - Cleant support VINS Service - Liter aupport VINS Service - Liter aupport VINS Service - Liter aupport VINS Service - Liter aupport VINS Service - Liter aupport VINS Service - Liter aupport VINS Service	HP 7500 SSL VPN	Ports	1 RJ-45 serial console po	rt
Memory and Processor 2G DDR2 SDRAM; packet buffer size: 64 MB flash Performance Throughpui up to 2 Gbps Concurrent sessions 60000 New sessions/second 5000 Number of users 10000 Environment Operating temperature 32° ft to 104° F (0°C to 40°C) Operating relative 10% to 90%, noncondensing humidity Web Access - Hip protocol - - - Web Browser - - - Minil languaga - - - Javascript - - - Woldok renote desktop share - - Vindows remote desktop share - - - Vindows - - - Notes - - - - TCP opplication by fixed service port - - - Internet restrict visit to internet offer user log in SSL VPN - - Authentication - - - Guidos - - - - Internet restrict visit to internet offer user log in SSL VPN - - Authentinitition - -	Module with 500-user	Physical characteristics		14.84(d) x 15.71(w) x 1.57(h) in. (37.7 x 39.9 x
Performance Throughput up to 2 Gbps Concurrent sessions 60000 Number of users 10000 Environment Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative 10% to 90%, noncondensing humidity Features Web Access - Hitp protocol - Web Browser - Intim language - Javascript - web proxy Port Forward Access Mode - Talnat - Windows remote desktop share - VNC remote desktop share - Outlook - Notes - TCP application by fixed service port Extend Network Access Mode - Reference - Robits - TCP application by fixed service - client support DNS Service - client support DNS Service - land authentication - assign client IP address dynamically - Calo authentication - Reference - Robits Secure - Internet restrict visit to internet after user log in SSL VPN Authentication - Robits authentication - Robits authentication - Calo authentication - Robits authentication - certificate authentication - Southentication - certificate authentication - Southentication - certificate authentication - Robus authentication - certificate authentication			Weight	7.05 lb. (3.2 kg)
Concurrent sessions 60000 New sessions/second 5000 Number of users 10000 Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative 10% to 90%, noncondensing humidity Features Web Access - Http protocol - Web Browser - Intil language - Javascript - web proxy Port Forward Access Mode - Telnet - Windows remote desktop share - VNC remote desktop share - Outlook - Notes - TCP application by fixed service port - TCP application by fixed service port - TCP application by fixed service port - Internet restriction for accessing network segment - TCP/UDP/IP filter - assign client IP address dynamically - client support VINS Service - Internet restrict visit to internet after user log in SSL VPN Authentication - Radius authentication - Radius authentication - Radius authentication - certificate authentication - Services - syear, 4-hour onsite, 13x5 coverage for hardware (HN001E) - syear, 4-hour onsite, 24x7 coverage for hardware (HN001E) - syear, 4-hour onsite, 24x7 coverage for hardware (HN001E) - syear, 4-hour onsite, 24x7 coverage for hardware (HN001E) - syear, 4-hour onsite, 24x7 coverage for hardware (HN001E) - syea		Memory and Processor	2G DDR2 SDRAM; packe	et buffer size: 64 MB flash
New sessions/second 5000 Number of users 10000 Environment Operating relative 32°F to 104°F (0°C to 40°C) Operating relative 10% to 90%, noncondensing humidity 10% to 90%, noncondensing humidity 10% to 90%, noncondensing Hitp protocol Web Access - Hitp protocol Web proxem - Javascript - web proxy Port Forward Access Mode - Telnet - Windows remote desktop share - Outlook - Notes - TCP application by fixed service port - TCP application by fixed service port Extend Network Access Mode - IP connect by route - restriction for accessing network segment - TCP/UDP/IP filter - assign client IP address dynamically - client support DNS Service - Client support DNS Service - Internet restrict visit to internet after user log in SSL VPN Authentication - Rod authentication - RSA SecureID - Ladp authentication - Abour onsite, 24x7 coverage for hardware (HN001E) 3-year, 4-hour onsite, 24x7 coverage for hardware (HN001E) - Syear, 4-hour onsite, 24x7 coverage for hardware (HN001E) 3-year, 24x7 SV phone support, software updates (HN01E)		Performance	Throughput	up to 2 Gbps
Number of users 10000 Environment Operating temperature 32'F to 104'F (0'C to 40'C) Operating relative minility 10% to 90%, noncondensing Features Web Access - Http protocol - Http protocol - web proxer - html Inguage - Jordscript - web proxy - Windows remote desktop share - VNC remote desktop share - Outlook - Notes - TCP application by fixed service port Extend Network Access Mode - IP connect by route - restriction for accessing network segment - TCP/IDP/IP filter - assign client IP address dynamically - client support UNIS Service - Client support UNIS Service <th></th> <th></th> <th>Concurrent sessions</th> <th>60000</th>			Concurrent sessions	60000
Environment Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative 10% to 90%, noncondensing humidity 10% to 90%, noncondensing Features Web Access - Http protocol - Web Browser - Introl language - Javascript - web proxy Port Forward Access Mode - Telnet - Windows remote desktop share - VNC remote desktop share - Outlook - Notes - TCP papication by fixed service port - Extend Network Access Mode - IP connect by route - restriction for accessing network segment - TCP/UDP/IP filter - assign client IP address dynamically - client support WINS Service - Internet restrict visit to internet after user log in SSL VPN Authentication - Radius authentication - Radius authentication - Abourthentication - Abourthentication - Services - syeer, 4-hour onsite, 13x5 coverage for hardware (HN001E) - yeer, 4-hour onsite, 24x7 SW phone support and SW updates (HN008E) - yeer, 24x7 SW phone support and SW updates (HN008E)			New sessions/second	5000
Operating relative humidity 10% to 90%, noncondensing humidity Features Web Access Http protocol Web Access - Http protocol - Web proxy - Port Forward Access Mode - Telnet - Windows remote desktop share - VNC remote desktop share - VNC remote desktop share - Outlook - Notes - TCP application by fixed service port Extend Network Access Mode - IP connect by route - restriction for accessing network segment - TCP application by fixed service port Extend Network Access dynamically - client support WINS Service - Internet restrict visit to intermet after user log in SSL VPN Authentication - Acdus authentication - Ab authentication - Ab authentication - Ab authentication - Ab authentication - Services 3-year, 4-hour onsite, 24x7 coverage for hardware (HN001E) -year, 4-hour onsite, 24x7 coverage for hardware (HN001E) -year, 4-hour onsite, 24x7			Number of users	10000
Humidity Web Access I Http protocol Web Browser I http protocol Web Browser I httm I language Javascript - web proxy Port Forward Access Mode - Telnet Windows remote desktop share - VNC remote desktop share Outlook - Notes - Outlook - TCP / Opplication by fixed service port Extend Network Access Mode - IP connect by route - restriction for accessing network segment - TCP/UDP/IP filter - assign client IP address dynamically - client support WINS Service - Internet restrict visit to internet after user log in SSL VPN Authentication - Rodius authentication - Rodius authentication - AD authenticati		Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
 Http protocol Web Browser Ihmil language Javascript web proxy Port Forward Access Mode Telnet Windows remote desktop share Outlook Notes TCP application by fixed service port Extend Network Access Mode IP connect by route restriction for accessing network segment TCP/UDP/IP filter assign client IP address dynamically client support DNS Service Internet restrict visit to internet after user log in SSL VPN Authentication Radius authentication Radius authentication Services Services Services Services 				10% to 90%, noncondensing
3-year, 4-hour onsite, 24x7 coverage for hardware (HN004E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HN008E) 3-year, 24x7 SW phone support, software updates (HN011E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR760E)		Features	 Http protocol Web Browser html language Javascript web proxy Port Forward Access Mod Telnet Windows remote desktop sh Outlook Notes TCP application by fixed Extend Network Access M IP connect by route restriction for accessing TCP/UDP/IP filter assign client IP address client support DNS Servi Internet restrict visit to in Authentication Radius authentication RSA SecureID Ldap authentication certificate authentication 	p share are I service port lode network segment dynamically vice ice ternet after user log in SSL VPN
		Services	3-year, 4-hour onsite, 24x7 coverage for hardware (HN004E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone suppor and SW updates (HN008E) 3-year, 24x7 SW phone support, software updates (HN011E)	



Technical Specifications

1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR762E) 4-year, 4-hour onsite, 13x5 coverage for hardware (HN002E) 4-year, 4-hour onsite, 24x7 coverage for hardware (HN005E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HN009E) 4-year, 24x7 SW phone support, software updates (HN012E) 5-year, 4-hour onsite, 13x5 coverage for hardware (HN003E) 5-year, 4-hour onsite, 24x7 coverage for hardware (HN006E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HN010E) 5-year, 24x7 SW phone support, software updates (HN013E) 3 Yr 6 hr Call-to-Repair Onsite (HN014E) 4 Yr 6 hr Call-to-Repair Onsite (HN015E) 5 Yr 6 hr Call-to-Repair Onsite (HN016E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR764E) 1-year, 24x7 software phone support, software updates (HR763E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Accessories

HP 7500 SSL VPN Module License			
with 500-user License	HP 7500 SSL VPN 5000-user License	JD258A	
accessories	HP 7500 SSL VPN 1000-user License	JD257A	

To learn more, visit: www.hp.com/networking

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

