



<b>Model</b>	20104193
<b>Product</b>	<b>2 Port Gigabit PoE Network Extender</b>
PoE Input Port	Supports 1/2(+), 3/6(-); 4/5(+), 7/8(-) MAX Input Power 30W(
PoE Output Port	Supports IEEE802.3af/at MAX Output Power30W
Dc in	1: Default:No Power 2: Optional 12V 0.5A as network extender 3: Optional 52V 0.5A power can be used as single port PoE Switch
Watt	Standby Power Consumption: ≤3W; Full-load Power Consumption: ≤30W;
Fixed Network Port	1*PoE Input port, 10/100/1000M Rj45 2*PoE Output port, 10/100/1000M Rj45
DC In	As Network Extender: DC9-57V MAX 0.5A As PoE Network Extender: DC37-57V MAX 0.5A
Function	EXT(Port Isolation)
LED Indicator	Pwr:Power LED Port: (Green=Link LED+Orange=PoE LED) ON/OFF: ( EXTFunction LED) Link:(Link LED=10/100M Link、1000M=Gigabit Link)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab1000BASE-T IEEE 802.3x IEEE 802.3af/at
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	1Gbps
Packet Forwarding	7.2Mpps
MAC Address	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)

Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	70mm*85mm*25mm 105mm*105mm*63mm
N.W/G.W (kg)	0.15kg/0.2kg
Installation	Desktop
Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

# **DIREKTRONIK**

Direktronik AB tel. 08-52 400 700 [www.direktronik.se](http://www.direktronik.se)