

Kramer KronoMeet

Cloud–Based Room Scheduling and Meeting Management Platform



Kramer KronoMeet is an enterprise class, user-friendly, cloud-based, room scheduling and management platform for Kramer KronoMeet touch panels. It streamlines and automates the management de of room bookings and provides live notifications to meeting participants. Kramer KronoMeet is designed to work seamlessly with Kramer anagement software and Kramer AV products habling you to sync your room management with your V management and deployment

FEATURES

Enterprise Class Comprehensive Room Scheduling, and Management - Empower your staff and guests with intuitive room scheduling, live on-site and remote notifications, and easy meeting search for employees and guests. Kramer KronoMeet is fully integrated with widely used scheduling platforms, including Google Calendar, Microsoft Office 365, and Microsoft Exchange

Fully Customizable and Scalable - Kramer KronoMeet is scalable to your needs, from a small business with a few meeting rooms to a large corporation

On-Screen Information Inside the Meeting Room - Integration with VIA collaboration devices enables automatic reminders on the main display when the meeting is nearly over and another meeting will be starting

Convenient Scheduling Displays - Display meeting schedules on Kramer KronoMeet touch panels at the entrance to each room

Superior User Experience - IPS 1280x800 hi–resolution screen with ±80° horizontal and vertical wide viewing angles, built–in lighting sensor for auto–adaptable brightness, with advanced 10 multi–touch points and 2–finger gesture capabilities

Secured Operation - Highly secured operation of applications such as password protected exit, hidden control buttons and so on

Secured Deployment - Flexible locking options to prevent unwanted panel-mount removal, elegantly designed to remain out of site



TECHNICAL SPECIFICATIONS

KT-107SC	PORTS 1 1000/100/10BaseT Ethernet: On an RJ–45 connector 1 DC power supply: On a 2–pin terminal block 1 USB: On a micro USB 2.0 connector (tabletop mount only)
	GENERAL CPU Performance: 1.6GHz Quad Core, GPU, 2GB RAM, 16GB flash OS Software: Android 6.0.1 Multi Touch: 10 points, 2-finger gesture Display: 7" IPS, 1280x800 RGB pixels, 16:10 aspect ratio, ±85° horizontal/vertical viewing angles, 400cd/m2 brightness, 800:1 contrast ratio Ethernet Port: 10/100/1000Mbps PoE LAN Wireless Communication: Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.0
	AUDIO Speakers: 2x1W, 8Ω Microphone: -42dB ±3dB @1kHz sensitivity
	VIDEO Decoding Format: HEVC/H.265, H.264, H.263, MPEG-1/2/4, VC-1, VP6/8, RV8/9/10, AVS, MVC, Sorenson Spark, M-JPEG Encoding Format: H.264, MVC, VP8, M-JPEG Camera: Front, 2M pixels, HD 720p
	POWER Battery: Rechargeable, supports up to 3 hours of Wi–Fi operation Power over Ethernet: Complies with IEEE802.3af and IEEE802.3at PoE standards Consumption: 5V DC, 3A
	USER INTERFACE Controls: Hidden Reset, power (ON/OFF), volume buttons Indicators: Touch panel status LED: flashes green during charging, steady green for fully charged, red for camera on
	PHYSICAL Case: Black body and cover Mounting Options: Table top (with docking station), on-wall (with mount unit and panel mount plate)
	ACCESSORIES Included: Power supply unit adapter (5V, 4.0A AC/DC), tabletop mount, on-wall mount unit, panel-mount plate, right-angle OTG USB cable, installation screws
	MEASUREMENTS Product Dimension: 17.80cm x 13.00cm x 1.30cm (7.01" x 5.12" x 0.51") W, D, H Product Weight: 0.4kg (0.9lbs) approx. Shipping Dimension: 35.00cm x 21.00cm x 7.00cm (13.78" x 8.27" x 2.76") W, D, H Shipping Weight: 1.2kg (2.5lbs) approx
KT-1010SC	PORTS 1 Ethernet: On an RJ-45 connector 1 SD card: On an SD card (SDHC Class10 compatible) slot 1 USB: On a USB 2.0 type A connector 1 USB: On a micro USB 2.0 connector 1 Headphone: On a 3.5mm mini jack connector
	GENERAL CPU Performance: GCortex-A17, quad core, up to 1.8 GHz GCPU: Mali-T764, with TE, ASTC, AFBC technology System Memory: 2GB DDR3 SDRAM Internal Storage Memory: 8GB eMMC External Storage Memory: SD card (SDHC Class10 compatible) Touch Panel Type: 10 point capacitive multi-touch type Wireless Communication : IEEE 802.11 a/b/g/n/ac, Bluetooth: BT4.2 Ethernet: 10/100/1000 Mbps LAN

AUDIO Speaker unit: 2W+2W

VIDEO Supported Formats: MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV Camera: 2M pixels (optional) Supported Formats: MP2, WMA, WAV, AAC, OGG, ASF

POWER Source: 12V/2A DC adapter POE: Power over Ethernet (optional)

USER INTERFACE Controls: Volume, menu, and power buttons Indicators: LED sidebars to indicate room status

PHYSICAL Display: TFT LCD, 10.1" (16:9 diagonal), 1280 RGB (H) x 800(V) pixels Back-light: LED Side-light type VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount

INCLUDED ACCESSORIES 12V AC/DC power adapter, on-wall mounting bracket, installation screws, 2 LED side bars, panel mounting bracket

MEASUREMENTS Product Dimension: 25.21cm x 18.00cm x 3.00cm (9.93" x 7.09" x 1.18") W, D, H Product Weight: 0.6kg (1.3lbs) approx. Shipping Dimension: 49.70cm x 20.50cm x 5.20cm (19.57" x 8.07" x 2.05") W, D, н

Shipping Weight: 1.6kg (3.4lbs) approx

ENVIRONMENTAL Operating Temperature: 0° to +40°C (32° to 104°F) CONDITIONS Storage Temperature: -10° to +55°C (14° to 131°F) Humidity: 10% to 90%, RHL non-condensing



CONFIGURATIONS

KT-107SC	7-Inch, wall mount, dedicated touch panel for Kramer KronoMeet – application with 1 year license pre-installed
KT-1010SC	10-Inch, wall mount, dedicated touch panel for Kramer KronoMeet – application with 1 year license pre-installed
KT-1010SC-5Y-SUB	10-Inch, wall mount, dedicated touch panel for Kramer KronoMeet – application with 5 year license pre-installed
KRONOMEET-SW- EXT-1Y	Kramer KronoMeet cloud based application - 1 year license
KRONOMEET-SW- EXT-2Y	Kramer KronoMeet cloud based application - 2 year license
KRONOMEET-SW- EXT-4Y	Kramer KronoMeet cloud based application - 4 year license