

C-19P



An excellent and affordable 19" display for home and office environments where quality, reliability and price are important considerations.

The valuable C-19P delivers the high image clarity and outstanding display performance that is well suited for the demands of modern office and home applications. Featuring 1,000:1 typical contrast ratio and built-in speakers, the slim modern design and convenient VESA compatible wall mounts make the C-19P a perfect value choice for home and office environments.

- > LED-backlit technology
- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 1,000:1 typical contrast ratio
- > Built-in speakers (3W x 2)
- > Tilt from -5 ° to +20 ° for optimal viewing
- > Kensington® security socket
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified

C-19P

Specifications

C-19P

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	19.0" (482 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294 mm
	Brightness	250cd/m2 (Typical)
	Contrast Ratio	1,000:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare treatment
	Viewing Angle (H/V)	170°/170° (Typical)
	Display Colour	16.7M
Frequency (H/V)	Response Time	3ms (GTG)
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	1 x Stereo audio in for PC
	Speaker	(audio jack, 3.5ø)
		3W x 2
Power	Power Supply	Internal
	Power Requirements	AC 100 - 240 V, 50 - 60 Hz
	Consumption	< 18 W (On)
		< 0.5 W (Stand-by)
		< 0.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-25 °C ~ 55 °C
	Humidity	10% ~ 85%
Mounting	VESA FPMPI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +20°
Dimensions	Product (W x H x D)	422 x 388 x 195 mm (16.6" x 15.3" x 7.7")
	Packaging (W x H x D)	478 x 403 x 140 mm (18.8" x 15.9" x 5.5")
Weight	Product Weight	3.9 kg (8.6 lbs)
	Packaged Product Weight	5.8 kg (12.8 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
Accessories	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5 °C to +20 °C for optimal viewing