

Tech Specs

Size and Colour

Dimensions 24.6 cm x 29.9 cm x 17.9 cm

Base/Mounting Bracket 12 cm Diameter

Available Colours White, Black

Features

Video 1080p HD, Colour Night Vision, Advanced Pre-Roll [1](#)

Motion Detection 270 Degrees, Advanced Motion Detection

Field of View 140° horizontal, 80° vertical

Audio Two-Way Talk

Siren 105 dB @ 10 cm

Lights 2000 Lumen with adjustable brightness
Colour Temperature: 3000°K

Power and Connectivity

Power Hardwired (100–240 VAC)

Internet Requirements Recommended minimum upload speed of 2 Mbps per device

Connectivity 802.11 b/g/n Wi-Fi @ 2.4GHz

Installation

Operating Conditions	-20°C to 50°C, Weather Resistant
Setup Requirements	AC Power (100-240 VAC) Wiring at setup location Professional installation recommended [2]
Floodlight Fixture	Integrated and Adjustable Floodlight. Floodlight Camera can be mounted on a Wall or Ceiling.

General

Box Includes	Floodlight Cam Mounting Bracket Installation Tools and Screws Quick Start Guide Security Sticker
Warranty	One-year limited warranty, and including theft protection. If you are a consumer, the limited warranty is in addition to your consumer rights, and does not jeopardise these rights in any way. This means you may still have additional rights at law even after the limited warranty has expired. Learn more here .

Disclaimer:

1. Feature available with a Ring Protect Plan.
2. The installation must be done according to local electrical regulations.